



## HLXS.EX27489 Butterfly Valves

[Page Bottom](#)

### Butterfly Valves

[See General Information for Butterfly Valves](#)

#### GULF FIRE FLOW CONTROL FZE

EX27489

PLOT NO. S31118, JEBEL ALI FREE ZONE

DUBAI, UNITED ARAB EMIRATES

Model	Size, NPS	Body Type	Pressure Rating, psig (Bar)	Indicator Post	Supervisory Switch*
<b>Butterfly valve</b>					
GF-BVG	2, 2.5(76.1mm), 2.5, 3, 4, 5, 5 (139.7 mm), 6, 6 (165.1 mm)	Groove	300	—	I/O
	8, 8 (216.3 mm), 10, 10 (267.4 mm)			—	I/O
	12, 12 (318.4 mm)			—	I/O
GF-BVW	2, 2.5, 3, 4, 5, 6	Wafer	300	—	I/O
	8, 10			—	I/O
	12			—	I/O

\* I = Indoor installation; O = Outdoor installation

[Last Updated](#) on 2017-04-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".