



HMRZ.EX27488 Gate Valves

[Page Bottom](#)

Gate Valves

[See General Information for Gate Valves](#)**GULF FIRE FLOW CONTROL FZE**

EX27488

PLOT NO. S31118, JEBEL ALI FREE ZONE
DUBAI, UNITED ARAB EMIRATES

Model	Type	Size, in.	Rated Pressure, psig	Rated Pressure, psig End Configuration
GF-GVF-2	O.S & Y	2.5,3,4,5,6,8,10,12	300	Flange & Flange
GF-GVF-6	NRS	2.5,3,4,5,6,8,10,12	300	Flange & Flange
GF-GVF-1	O.S & Y	2,2.5,3,4,5,6,8,10,12	200	Flange & Flange
GF-GVG-3				Flange & Grooved
GF-GVG-4				Grooved & Grooved
GF-GVF-5	NRS	2.5,3,4,5,6,8,10,12	200	Flange & Flange
GF-GVG-7				Flange & Grooved
GF-GVG-8				Grooved & Grooved

Note: O.S & Y, outside-screw-and-yoke type NRS, nonrising stem type.

Flanges comply with ANSI B16.1 Class 125; for 300 psi, use Face flange, for 200 psi, use Raised-face flange.

[Last Updated](#) on 2017-04-26

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".