



GULF FIRE

FIRE HOSE REEL CABINET



MILD STEEL FIRE CABINETS

STANDARD MODELS

Our entire MSC Series Cabinets shall be Fabricated from ElectroGalvanized Mild Steel Sheets with fully welded joints, Single Door & Red Colour Powder Coated. Standard cabinets will have sheet thickness of 1.2mm, but also available from 1mm to 2mm as per client's requirement.

MODEL	SIZE (CM)			APPLICATION
	Height	Width	Depth	
MSC 160	160	80	40	To Keep 1 No. Hose Reel & 2 Nos. Fire Extinguishers
MSC 80	80	80	40	To Keep 1 No. Fire Hose Reel
MSC 90	90	40	25	To Keep 2 Nos. Fire Extinguishers

Features:

- Hinges will be of Continuous Type
- Dust Proof Enclosure
- Recessed Circular chrome plated Handle

Options:

- Solid Door or Door with Wired Glass 6 mm Thick
- Double Door Models also available
- Recessed Type available with Architrave
- Right or Left-Hand Opening



MSC 160



MSC 90



MSC 80



STAINLESS STEEL FIRE CABINETS

STANDARD FLOOR MOUNTING MODELS

Our entire SSC Series Cabinets shall be Fabricated from Stainless Steel Sheets with fully welded joints, Single Door. Sheet thickness will vary from 1 mm to 2 mm as per client's requirement. Available Grades of Stainless steel sheets are SS304, SS316 of Brush or Mirror finish.

MODEL	SIZE (CM)			APPLICATION
	Height	Width	Depth	
SSC 160	160	80	40	To Keep 1 No. Hose Reel & 2 Nos. Fire Extinguishers
SSC 80	80	80	40	To Keep 1 No. Fire Hose Reel
SSC 90	90	40	25	To Keep 2 Nos. Fire Extinguishers
SSC-2W	40	60	30	To Keep Fire Brigade Breaching Inlet – 2 way
SSC-4W	60	60	30	To Keep Fire Brigade Breaching Inlet – 4 way

Features:

- Hinges will be of Continuous Type
- Dust Proof Enclosure
- Recessed Circular chrome plated Handle

Options:

- Solid Door or Door with Wired Glass 6 mm Thick
- Double Door Models also available
- Recessed Type available with Architrave
- Right or Left-Hand Opening



SSC 160



SSC 80



SSC 90



SSC- 4W



STAINLESS STEEL FIRE CABINETS

RECESSEED MODELS

Construction:

Body: Mild Steel, Red Color Powder Coated

Door & Architrave: Stainless Steel in Grades SS304, SS316 of Brush or Mirror finish.

Fully welded joints: Standard cabinets will have sheet thickness of 1.2mm, but also available in sheet thickness from 1 mm to 2 mm as per client's requirement.

MODEL	SIZE (CM)			APPLICATION
	Height	Width	Depth	
SSCR 160	160	80	40	To Keep 1 No. Hose Reel & 2 Nos. Fire Extinguishers
SSCR 80	80	80	40	To Keep 1 No. Fire Hose Reel
SSCR-2W	40	60	30	To Keep Fire Brigade Breaching Inlet – 2 way
SSCR-4W	60	60	30	To Keep Fire Brigade Breaching Inlet – 4 way

Features:

- Double Door Models also available
- Hinges will be of Continuous Type
- Dust Proof Enclosure
- Recessed Circular chrome plated Handle

Options:

- Solid Door or Door with Wired Glass 6 mm Thick
- Recessed Type available with Architrave
- Right or Left-Hand Opening



SSCR- 4W

SSCR 160



SSCR 80

