19" Hover Touch Overlay (HTO-19)



Key Features :


- Edge-based Contactless Touch Upgrade Kit
- Plug & Play Design for Multiple Platforms
- Haptics Design for Enhanced User Experience
- Supports Portrait & Landscape Modes
- Omni Industry Self-Service Application
- Access to Customer Education Graphics Library

Specifications		Order Information	
Touch Type	Hover (Air) Touch	Part Number	Description
Size Support	19″ 5:4	HTO-19-H3U	19" 5:4 hover frame / 3-tier haptic design: LED + visual + sound / USB2.0 Type A connectivity (180cm) / enhanced IR sensor arrays / proprietary light filter / metallic black coating finish
Response Time	125RPS (30ms touch / 12ms draw)		
Haptic Feedback	LED / Visual / Sound visual haptic (GUI) will be provided upon request		
Interface	USB 2.0 HID	HTO-Mount-L1	L shape screw mount bracket / 2CM height / 16 screw points to surface / 8 screw points to HTO
Input Method	Finger / Gloved / Stylus (7mm+)	L shap	tape contact surface / 8 screw points to HTO
Operating Voltage	DC 5V±5% (via USB)	HTO-Mount-L2	
OS Support	Windows / Linux / Android		HTO Tailored Services
Certifications	CE / FCC class B	Calibration Service	Remote touch calibration service can be requested
Mounting	Tape Mount / Screw Mount	Custom Service 1	Color customization with MOQ = 200 units
Application	Indoor / Semi-Outdoor	Custom Service 2	Bracket customization without MOQ

Dimension

Unit: mm

Mechanical Design





KOGI Corporation | Address: 7F #335 Ruiguang Road, Neihu Dist., Taipei, Taiwan R.O.C.



Phone #: +886-2-2799-8808 | Web: https://www.kogicorp.com | Email: inquiry@kogicorp.com