
27" 16:9 Ratio Hover Touch Overlay (HTO-27)



Key Features :


- Edge-based Contactless Touch Upgrade Kit
- Plug & Play Design (USB Type B)
- Haptic Design for Enhanced User Experience
- Supports Portrait & Landscape Modes
- Omni Industry Self-Service Application
- Size Customization Services Available (MOQ)

Mechanical Design

Specifications		Order Information	
Touch Type	Hover (Air) Touch	Part Number	Description
Size Support	27" 16:9	HTO-27-H2U	27" 16:9 hover frame / 2-tier haptic design: visual + sound / USB2.0 Type A connectivity (180cm) / enhanced IR sensor arrays / proprietary light filter / metallic black coating finish
Response Time	125RPS (30ms touch / 12ms draw)		
Haptic Feedback	For <24" : LED / Visual / Sound For >24" : Visual / Sound (LED Optional)		
Interface	USB 2.0 HID	HTO-Mount-L3	L shape screw mount bracket / 2CM height / 16 screw points to surface / 8 screw points to HTO
Input Method	Finger / Gloved / Stylus (7mm+)	HTO-Mount-L4	L shape tape mount bracket / 2CM height / 266cm ² tape contact surface / 8 screw points to HTO
Operating Voltage	DC 5V±5% (via USB)		
OS Support	Windows / Linux / Android		HTO Tailored Services
Certifications	CE / FCC class B	Calibration Service	Remote touch calibration service can be requested
Mounting	Tape Mount / Screw Mount	Custom Service 1	Color customization with MOQ = 200 units
Application	Indoor / Semi-Outdoor	Custom Service 2	Bracket customization without MOQ

Dimension (HTO-27-H2U)

Unit: mm





KOGI Corporation | Address: 7F #335 Ruiguang Road, Neihu Dist., Taipei, Taiwan R.O.C.

Phone #: +886-2-2799-8808 | Web: https://www.kogicorp.com | Email on Website

VISIT OUR WEBSITE