## 32" Hover Touch Overlay (HTO-32)



## Key Features:

- Edge-based Contactless Touch Upgrade Kit
- Plug & Play Design for Multiple Platforms
- Haptic Design for Enhanced User Experience
- Supports Portrait & Landscape Modes
- Omni Industry Self-Service Application
- Access to Customer Education Graphics Library

|  | Specifications |
|--|----------------|
|--|----------------|

| Touch Type           | Hover (Air) Touch   |
|----------------------|---|
| Size Support         | 32″ 16:9  |
| Response Time        | 125RPS (30ms touch / 12ms draw)   |
| Haptic Feedback      | For <24": LED / Visual / Sound<br>For >24": Visual / Sound (LED Optional) |
| Interface            | USB 2.0 HID   |
| Input Method         | Finger / Gloved / Stylus (7mm+)   |
| Operating<br>Voltage | DC 5V±5% (via USB)  |
| OS Support           | Windows / Linux / Android   |
| Certifications       | CE / FCC class B  |
| Mounting             | Tape Mount / Screw Mount  |
| Application          | Indoor / Semi-Outdoor   |
|                      |   |

## **Order Information**

| Part Number           | Description   |  |
|-----------------------|---|--|
| HTO-32-H2U            | 32" 16:9 hover frame / 2-tier haptic design: visual + sound / USB2.0 Type A connectivity (180cm) / enhanced IR sensor arrays / proprietary light filter / metallic black coating finish |  |
| HTO-Mount-L3          | L shape screw mount bracket / 2CM height / 16 screw points to surface / 8 screw points to HTO   |  |
| HTO-Mount-L4          | L shape tape mount bracket / 2CM height / 266cm <sup>2</sup> tape contact surface / 8 screw points to HTO   |  |
| HTO Tailored Services |   |  |
| Calibration Service   | Remote touch calibration service can be requested   |  |
| Custom Service 1      | Color customization with MOQ = 200 units  |  |
| Custom Service 2      | Bracket customization without MOQ   |  |









