



KNEES & FEET TECHNICAL REFERENCE

Product Name and Description	Part Number	K Level	Recommended L Code	Technical Data
------------------------------	-------------	---------	--------------------	----------------

KNEES

KINEGEN.stream – Polycentric Knee Joint with Hydraulic Swing Phase Control	3A2500	K3-4		<ul style="list-style-type: none"> max. patient weight: 330 lbs
			L-5814	<ul style="list-style-type: none"> connection proximal: adjustment core • connection distal: adjustment core
			L-5850	<ul style="list-style-type: none"> knee flexion angle: 136°
			L-5950	<ul style="list-style-type: none"> overall height: 224 mm
			L-5920	<ul style="list-style-type: none"> overall height of joint head: 36 mm
		<i>If K-4 use an additional code of</i>	L- 5930	<ul style="list-style-type: none"> effective height: 196 mm effective proximal height: 23 mm effective distal height: 173 mm approx weight 1110 g warranty 12 months
KINEGEN.air-active – Polycentric Knee Joint with Pneumatic Swing Phase Control and Integrated Extension Assist Spring	3A1800	K2-3	L-5920	<ul style="list-style-type: none"> max. patient weight: 275 lbs
			L-5950	<ul style="list-style-type: none"> proximal connection: pyramid adapter
			L-5850	<ul style="list-style-type: none"> distal connection: tube clamp Ø 30 mm • knee flexion angle: 150°
			L-5818	<ul style="list-style-type: none"> overall height: 228 mm overall height joint head: 28 mm
				<ul style="list-style-type: none"> effective height: 178 mm effective proximal height: 14 mm effective distal height: 164 mm approx weight 960 g warranty 12 months
KINEGEN.smart – Brake knee joint with lock	3A860	K1-2	L5812	<ul style="list-style-type: none"> max. patient weight: 275 lbs.
			L5845	<ul style="list-style-type: none"> connection proximal: adjustment core
			L5850	<ul style="list-style-type: none"> connection distal: tube clamp Ø 30 mm • knee flexion angle: 145°
			L5925	<ul style="list-style-type: none"> overall height: 115 mm effective height: 65 mm effective proximal height: 27 mm effective distal height: 38 mm Accessory warranty 12 months
KINEGEN.air – Brake Knee Joint with Pneumatic Swing Phase Control	3A1000	K1-2	L-5812	<ul style="list-style-type: none"> max. patient weight: 275 lbs.
			L-5850	<ul style="list-style-type: none"> connection proximal: adjustment core
			L-5920	<ul style="list-style-type: none"> connection distal: tube clamp Ø 34 mm • knee flexion angle: 145°
			L-5950	<ul style="list-style-type: none"> overall height: 249 mm proximal height: 53 mm distal height: 196 mm effective height: 185 mm effective proximal height: 39 mm effective distal height: 146 mm warranty: 24 months

FEET

GO.smart - Carbon foot	5A410/	K2	L-5972	<ul style="list-style-type: none"> max. body weight up to 330 lbs. (depending on size)
			L-5986	<ul style="list-style-type: none"> connection: pyramid heel height: 10 mm / 0,4" weight: 594 g (size 27 incl. foot shell and spectra-sock) construction height: size 22 – 25 cm = 61 mm, Größe 26 – 29 cm = 69 mm maintenance-free warranty: 24 months Foot shell sold separately
GO.free - Carbon foot	5A430/	K3	L-5980	<ul style="list-style-type: none"> max. body weight up to 150 kg / 330 lbs. (depending on size) • mobility class (walky): 3 bis 4
			L-5986	<ul style="list-style-type: none"> connection: pyramid heel height: 10 mm / 0,4" weight: 660 g / lbs. (Gr. 27 incl. foot shell and spectra-sock) construction height: size 22 – 25 cm = 144 mm, size 26 – 29 cm = 155 mm • maintenance-free warranty: 36 months Foot shell sold separately