



KNEES & FEET TECHNICAL REFERENCE

Product Name and Description	Part Number	K Level	Recommended L Code	Technical Data			
KNEES							
KINEGEN.stream – Polycentric Knee Joint with Hydraulic Swing Phase Control	3A2500	K3-4	L-5848	• max. patient weight: 330 lbs			
			L-5814	• connection proximal: adjustment core • connection distal: adjustment core			
			L-5850	• knee flexion angle: 136°			
			L-5950	• overall height: 224 mm			
			L-5920	• overall height of joint head: 36 mm			
			<i>If K-4 use an additional code of</i>			L-5930	• effective height: 196 mm
						L-5930	• effective proximal height: 23 mm
						L-5930	• effective distal height: 173 mm
						L-5930	• approx weight 1110 g
						L-5930	• warranty 12 months
KINEGEN.air-active – Polycentric Knee Joint with Pneumatic Swing Phase Control and Integrated Extension Assist Spring	3A1800	K3	L-5920	• max. patient weight: 275 lbs			
			L-5950	• proximal connection: pyramid adapter			
			L-5850	• distal connection: tube clamp Ø 30 mm • knee flexion angle: 150°			
			L-5818	• overall height: 228 mm			
			L-5818	• overall height joint head: 28 mm			
			L-5818	• effective height: 178 mm			
			L-5818	• effective proximal height: 14 mm			
L-5818	• effective distal height: 164 mm						
L-5818	• approx weight 960 g						
L-5818	• warranty 12 months						
KINEGEN.smart – Brake knee joint with lock	3A860	K2	L-5812	• max. patient weight: 275 lbs.			
			L-5845	• connection proximal: adjustment core			
			L-5850	• connection distal: tube clamp Ø 30 mm • knee flexion angle: 145°			
			L-5925	• overall height: 115 mm			
			L-5925	• effective height: 65 mm			
L-5925	• effective proximal height: 27 mm						
L-5925	• effective distal height: 38 mm Accessory						
L-5925	• warranty 12 months						
KINEGEN.air – Brake Knee Joint with Pneumatic Swing Phase Control	3A1000	K2	L-5822	• max. patient weight: 275 lbs.			
			L-5850	• connection proximal: adjustment core			
			L-5920	• connection distal: tube clamp Ø 34 mm • knee flexion angle: 145°			
			L-5950	• overall height: 249 mm			
			L-5950	• proximal height: 53 mm			
L-5950	• distal height: 196 mm						
L-5950	• effective height: 185 mm						
L-5950	• effective proximal height: 39 mm						
L-5950	• effective distal height: 146 mm						
L-5950	• warranty: 12 months						
FEET							
GO.smart - Carbon foot	5A410/	K2	L-5972	• max. body weight up to 275 lbs. (depending on size)			
			L-5986	• connection: pyramid			
			L-5986	• heel height: 10 mm / 0,4"			
			L-5986	• weight: 594 g (size 27 incl. foot shell and spectra-sock)			
			L-5986	• construction height: size 22 – 25 cm = 61 mm, Größe 26 – 29 cm = 69 mm			
			L-5986	• maintenance-free			
			L-5986	• warranty: 24 months			
L-5986	• Foot shell sold separately						
GO.relax - Carbon foot	5A420/	K3	L-5980	• max. body weight up to 150 kg / 330 lbs. (depending on size) • mobility class (walky): 3 bis 4			
			L-5986	• connection: pyramid			
			L-5986	• heel height: 10 mm / 0,4"			
			L-5986	• weight: 620 g / 1.37 lbs. (Gr. 27 incl. foot shell and spectra-sock)			
			L-5986	• construction height: size 22 – 25 cm = 103 mm, size 26 – 29 cm = 106 mm • maintenance-free			
			L-5986	• warranty: 24 months			
			L-5986	• Foot shell sold separately			
GO.free - Carbon foot	5A430/	K3	L-5980	• max. body weight up to 150 kg / 330 lbs. (depending on size) • mobility class (walky): 3 bis 4			
			L-5986	• connection: pyramid			
			L-5986	• heel height: 10 mm / 0,4"			
			L-5986	• weight: 660 g / 1.45 lbs. (Gr. 27 incl. foot shell and spectra-sock)			
			L-5986	• construction height: size 22 – 25 cm = 144 mm, size 26 – 29 cm = 155 mm • maintenance-free			
			L-5986	• warranty: 36 months			
			L-5986	• Foot shell sold separately			
GO.adventure - Carbon foot	5A440/	K4	L-5986	• max. body weight up to 150 kg / 330 lbs. (depending on size) • mobility class (walky): 3 bis 4			
			L-5987	• connection: pyramid			
			L-5987	• heel height: 10 mm / 0,4"			
			L-5987	• weight: 700 g / 1.54 lbs. (Gr. 27 incl. foot shell and spectra-sock)			
			L-5987	• construction height: size 22 – 25 cm = 144 mm, size 26 – 29 cm = 155 mm • maintenance-free			
			L-5987	• warranty: 36 months			
			L-5987	• Foot shell sold separately			