



# CALI VINYL<sup>®</sup> PRO

BUILDER'S CHOICE WITH MUTE STEP<sup>®</sup>

[www.CaliFloors.com](http://www.CaliFloors.com)










Aged Hickory Vinyl Builder's Choice

## Where Luxury Looks Meet Commercial Strength

This exclusive luxury vinyl collection delivers the same high standards of any Cali Vinyl floor for a better value. Offered only to builders, designers, and architects, it's the LVP for high-style spaces armed for stampede-level traffic. Made in our most popular colors, this special forces flooring is made for domineering strength, faster installations, and 100% waterproofing. Rugged to the bone, each plank is fortified by GeoCore<sup>®</sup>, a fortifying backbone of limestone composite for superior structural stability.

### Available Colors





Superior Wear Layer



Waterproof Flooring



Fast Install



Matching Accessories



Easy to Clean



Built to Last



Gray Ash Vinyl Builder's Choice

### Leaner & Meaner

Designed with the large-scale commercial installer in mind, the strongest drop-lock system in the industry is also easier to snap together, meaning flooring can be laid in half the time.

### GeoCore: Bad to the Bone

This backbone of limestone composite resists indentation and delivers 50% better dimensional stability (less expansion and contraction), requiring no acclimation or transition pieces.

### Fear No Moisture

A more muscular construction translates to 100% waterproof flooring over any type of subfloor, and zero acclimation even in kitchens, bathrooms, and sub-grade installations.

### Pros Only

This exclusive line is not available to the public and reserved only for industry professionals who demand the fastest installations and superior, commercial-grade durability.

### Accessories



<b>Grain</b>	HiFi Imaging®
<b>Plank Length</b>	48 inches
<b>Plank Width</b>	7-1/8 inches
<b>Plank Thickness</b>	4.7mm
<b>Wear Layer</b>	0.5mm (20mil)
<b>Attached Pad</b>	1mm IXPE Pad
<b>Sqft./Box</b>	23.77 sqft.
<b>Milling</b>	Click Lock (Rapid Locking System)
<b>Construction</b>	100% Waterproof GeoCore® (SPC Composite)
<b>Installation Method</b>	Floating, Glue Down
<b>Sound Rating (No Drop Ceiling)</b>	<i>With Cali Complete:</i> STC 51 & IIC 54 <i>Without Underlayment:</i> STC 52 & IIC 53
<b>Sound Rating (Drop Ceiling)</b>	<i>With Cali Complete:</i> STC 62 & IIC 66 <i>Without Underlayment:</i> STC 62 & IIC 66
<b>Resin</b>	Low Emitting VOC & Prop 65 Compliant (VOC and Phthalate test results available upon request)
<b>Warranty</b>	50 Year Residential 15 Year Commercial
<b>Fire Rating</b>	1.12 W/cm2 (Class 1)
<b>Radiant Heat Compatible</b>	Yes (up to 85°F)