

## HF5000 Tack<sup>TM</sup>

## **High Performance Tackifier**

## HF5000 Tack<sup>TM</sup>

**Description:** HF5000 Tack<sup>TM</sup> is an organic tackifier specially

formulated to provide long-term strength and

erosion control. HF5000 Tack  $^{\rm TM}$  may be utilized with fiber or as a stand-alone overspray for dust control or to tack straw/hay to

prevent wind/water erosion.

Application Guideline:  $HF5000 \ Tack^{TM} \ may \ be \ prepared \ for$ 

application by mixing at 10 to 35-lb per 1000 gallons of water. Higher concentrations may be used with equipment capable of mixing and

pumping higher viscosity.

HF5000 Tack<sup>TM</sup> reduces pumping friction and improves spray patterns due to its unique

polymer properties.

Application Rates: Slope: FLAT 4:1 3:1 2:1 1:1

Lb./acre: 15-40 40-60 60-80 80-120 120-220

**Loading Sequence:** Refer to the equipment manufacturers loading

sequence instructions.

Site Preparation: Grade preparation should divert water flow

away from the face of the slope.

Storage: Maintain packaging integrity. Protect

from weather, moisture, and high temperatures.

Handling: Slippery when wet. Clean up spills immediately.

**Manufactured by:** Rantec Corp.

P.O. Box 729

Ranchester, WY 82839

Distributed by: Innovative Turf Solutions

513-317-8311

www.innovativeturfsolutions.com

HF5000 Tack<sup>TM</sup> is packaged in 50-lb bags, 40 per pallet.

innovative turf solutions