

Material Safety Data Sheet



ArcusStone®

Date: 7.1.08

1. Product and Company Information

Product Name: **Topcoat Acrylic Sealer**

HMIS Classification: **Health: 1 Flammability: 0 Physical Hazard: 0**

Personal Protection: I (safety glasses, gloves, and vapor respirator)

Product Use: An aqueous blended acrylic resin emulsion that is applied to ArcusStone® coatings to provide a topical water and stain barrier.

ArcusStone Products, LLC Office 415.339.4060 Fax 415.339.4065
180 Harbor Drive, Suite 200
Sausalito, CA 94965 www.arcustone.com

2. Composition / Information on Hazardous Ingredients

Ingredients	%	CAS#	ACGIH TLV (ppm)	OSHA PEL (ppm)	OSHA TLV (ppm)
Ethylene Glycol Monobutyl Ether	3.3	111-76-2	N/E	25	25
Diethylene Glycol Monobutyl Ether	3.3	112-34-5	N/E	N/E	N/E
Ethylene Glycol	2.1	107-21-1	N/E	50	100

OSHA Hazardous Communication Standard 29 CFR 1910.1200 allows the MSDS information as to non-hazardous components to be unlisted if they are considered proprietary, therefore, identities of proprietary ingredients in this product are not listed here.

3. Hazards Identification

Routes of exposure:

Skin contact : Yes
Skin Absorption: No
Eye Contact: Yes
Inhalation: Yes
Ingestion: Yes

Emergency Overview:

Exposure to the product may result in temporary or transient breathing difficulty, nausea, headache, or mild sore throat.

Potential Health Effects:

Health effects, if any, would be very minimal and transient. Any potential health effects would most likely be due to continuous breathing of vapors in poorly ventilated areas, or the product contacting eye or mucus membranes. Refer to the following section on first aid measures should any of these this occur.

4. First Aid Measures

Skin: Wash affected areas thoroughly with soap and water for at least 5 minutes. Consult Physician if irritation persists.

Eyes: In the event of direct contact, rinse / flood eyes with clean water immediately and repeatedly for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion: Immediately consult a physician. Induce vomiting only as directed by medical personnel. Do not give anything by mouth to an unconscious person.

For Gross Inhalation: Immediately move subject to fresh air. Seek immediate medical attention. If breathing has stopped or is significantly impaired, give artificial respiration.

5. Fire Fighting Measures

Flammable: Not flammable or combustible.

Means of Extinction: Use water, foam, dry chemical or carbon dioxide on dried film.

Flashpoint: non-flammable in liquid state.

Upper Flammable Limit (% by volume): N/E

Lower Flammable Limit (% by volume): N/E

Auto ignition Temperature: Will not auto ignite.

Explosion Data – Sensitivity to Impact: Will not explode.

Explosion Data – Sensitivity to Static Discharge: Possibility of pressure buildup in closed containers. Use water stream to cool before opening.

Hazardous Combustion Products: N/A

NFPA: Non-combustible classification.

6. Accidental Release Measures

Leak and Spill Procedures:

Stop the leak and ventilate area. Construct a containment dike to limit the spread of material. Mix with a dry soil or other non-reactive absorbent and place in container then dispose of as common waste. Flush contaminated area with water as soon as possible before material dries. Prevent runoff into storm sewer, streams or other bodies of water. Wear butyl rubber protective gloves, footwear, and clothing if cleaning up larger spills. For disposal, see Section 13, "Disposal Considerations".

Product is not considered a hazardous waste under EPA Hazardous Waste Regulation 40 CFR 261.

7. Handling and Storage

Handling Procedures and Equipment:

Handle with adequate ventilation and avoid direct and prolonged breathing of vapors. Do not eat, drink, smoke, or otherwise allow wet material to contact mucus membranes or skin while handling. To avoid possible back strain or other injury, use a back brace, hand truck, pallet jack, or fork lift to move material containers.

Storage Requirements:

Store unopened in manufacturer's original containers out of direct sunlight, extreme heat or cold, precipitation, and weather exposure. Do not store near open flame or other sources of ignition. Do not stack more than 2 pallets in height. Rotate stock. Product shelf life is one year from date of manufacture, in unopened containers. Store where temperature is between 40° and 100°F. (4.5 ° and 38 ° C). Do not freeze. Discard if product becomes frozen or laden with ice crystals.

8. Exposure Control / Personal Protection

Exposure Limits:

ACGIH -TWA: N/E

OSHA PEL: No TLV assigned to this product.

Engineering Controls:

General - None required.

Local Exhaust - Ventilate if needed using mechanical means

Personal Protective Equipment:

Eye - Chemical tight splash goggles (ANSI Z-87, 1, or approved equal) required.

Respiratory - Not normally required if good ventilation is maintained. Use of an appropriate OSHA MSHA or NIOSH approved respirator in poorly ventilated areas is required.

Hand - latex, vinyl, or rubber gloves are recommended but typically not required.

Other - Provide means of rinsing eyes (eyewash station) in case of emergency.

9. Physical and Chemical Properties

Physical State: Liquid

Odor and Appearance: Milky white with slight monomer odor.

Odor Threshold (ppm): no designation

Specific Gravity (H₂O =1): 1.1

Vapor Density (air =1): no designation

Vapor Pressure (mmHg): no designation

Evaporation Rate (Ether = 1): no designation

Boiling Point: 212 ° F. (100 ° C)

Freezing Point: 32 ° F. (0 ° C)

Melting Point: N/A

pH (in water): not available

Solubility in Water: Dilutable

Molecular Weight: Mixture

Weight /Gal.: 8.50

10. Stability and Reactivity

Chemical Stability:

Stable at ambient temperatures

Incompatibility with other substances:

Product may coagulate if mixed with highly iodized or organic materials.

Hazardous Decomposition Products:

Carbon dioxide.

Reactivity:

Hazardous polymerization will not occur.

11. Toxicological Information

Effects of Acute Exposure:

Can cause slight irritation to the eyes, skin, and upper respiratory system, headache, dizziness, and mild nausea.

Effects of Chronic Exposure:

Vapors can cause inflammation of the lining tissue of the interior nose, throat, and upper respiratory system.

Irritancy of Product:

Exposure can affect the skin, eyes and mucous membrane.

Respiratory Sensitization:

Mild and temporary sore throat may occur with extended inhalation of vapors in poorly ventilated areas.

Carcinogenicity:

No carcinogens in concentrations of 0.1% or greater under OSHA, NTP, IARC, ACGIH, and Calif. Prop. 65.

NTP – Not classified.

OSHA regulated – Not as a carcinogen.

IARC Monographs – No

Calif. Prop. 65 – No

12. Ecological Information

Aquatic Toxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation: Not available.

Toxicity of Products of Biodegradation: Not available.

13. Disposal Considerations

Waste Disposal:

Product in liquid form can be disposed as common waste in small quantities < 100 gallons (378.5 L) to municipal or industrial wastewater treatment plants, with prior approval from these authorities and in accordance with local, state, provincial, and federal regulations. For > 100 gallons (378.5l), disposal through a licensed disposal facility is recommended. Product that is mixed with an amount of an appropriate absorbent material to produce a non-flowable state can be disposed of as common waste in accordance with Federal, Provincial, State, and Municipal regulations.

14. Transport Information

PIN - N/A

TDG - N/A

DOT - Classified as PAINT, Non-hazardous, not regulated. Keep from freezing.

IMO - N/A

ICAO - N/A

IATA - Not regulated.

15. Regulatory Information

WHMIS Classification - N/A

OSHA – not available.

SARA - Product does not contain any toxic chemicals subject to reporting requirements of Section 313 of The Superfund Amendments and Reauthorization Act of 1986.

TSCA - no components considered toxic under this reporting requirement.

16. Other Information

Abbreviations:

ACGIH - American Conference of Governmental Hygienists

ANSI - American National Standards Institute

C - Celsius

Cal/OSHA - Calif. Division of Occupational Health Administration

CARB - California Air Resources Board

CAS - Chemical Abstract Service

CERCLA - Comprehensive Environmental Response and Liability Act (Superfund) of 1980

CFR 49 - Title 49 of the Code of Federal Regulations

DOT - Department of Transportation

EPA - Environmental Protection Agency

F - Fahrenheit

HMIS - Hazardous Materials Identification System

IARC - International Agency for Research on Cancer

IATA - International Air Transport Association

ICAO - International Civil Aviation Organization

IMO - International Maritime Organization

M3 - Cubic Meter

Mg - milligram

MSDS - Material Safety Data Sheet

N/A - Not Applicable

N/E - Not Established

NFPA - National Fire Protection Association

NIOSH - National Institute of Occupational Safety and Health

NTP - National Toxicity Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act of 1976

SARA - Superfund Amendments and Reauthorization Act of 1986

SCAQMD - South Coast Air Quality Management District

SiO₂ - Crystalline Silica (quartz)

TGD - Transportation of Dangerous Goods Act of 1992 (Canadian)

TLV - Threshold Limit Values

TSCA - Toxic Substances Control Act of 1976

TWA - Time Weighted Average

WHMIS - Workplace Hazardous Materials Information System

Statement:

While the information provided in this MSDS is believed to provide a useful summary of the hazards of this product as it is commonly used, the MSDS cannot anticipate and provide all of the information that might be needed in every situation. In particular, product users who have not had the benefit of proper training in the application of the product may be using it in a manner that this MSDS does not address or that may be hazardous. The information herein is given in good faith but no warranty, expressed or implied, is made.