



Safety Data Sheet BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : BRAKE CLEAN SELECT

Manufacturer or supplier's details

Company : Motor Oil Supply

Address : 1123 4th Ave N.
Kent, WA. 98032
USA

Emergency telephone number:

Motor Oil Supply:-253-854-5454

Additional Information: : Phone: 253-854-5454
Regulatory Information Number: 253-854-5454
Email: mos@motoroilsupply.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Specific target organ toxicity
- single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equip-
ment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical name	Weight percent
64742-49-0 / 426260-76-6 / 64742-89-8	Naphtha (pet), hydrotreated It AND/OR Heptane, branched, cyclic and linear AND/OR Solvent naphtha (pet), It aliph.	90 - 100
142-82-5	**Heptane	30 - 50

Any Concentration shown as a range is due to batch variation.

Special Notes: : ** Other substances in the product which may present a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

- | | |
|-------------------------|---|
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |



Safety Data Sheet BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Container may be opened only under exhaust ventilation hood.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-49-0 / 426260-76-6 / 64742-89-8	Naphtha (pet), hydrotreated lt AND/OR Heptane, branched, cyclic and linear AND/OR Solvent naphtha (pet), lt aliph.	TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
142-82-5	**Heptane	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm	OSHA Z-1



Safety Data Sheet BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

			2,000 mg/m ³	
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
		STEL	500 ppm 2,000 mg/m ³	OSHA P0
		PEL	400 ppm 1,600 mg/m ³	CAL PEL
		STEL	500 ppm 2,000 mg/m ³	CAL PEL
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Clear, colorless

Odour : characteristic, hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Freezing Point : No data available

Boiling Point (Boiling point/boiling range) : 88 - 100 °C (190 - 212 °F)

Flash point : -9 - -7 °C (16 - 19 °F)

Evaporation rate : > 1
(Butyl Acetate = 1)

Flammability (solid, gas) : No data available

Upper explosion limit : 7 %(V)

Lower explosion limit : 1 %(V)

Vapour pressure : < 45 mmHg @ 20 - 25 °C (68 - 77 °F)



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

Relative vapour density	: < 3.52 @ 20 - 25 °C (68 - 77 °F) (Air = 1.0)
Relative density	: 0.7 - 0.71 @ 20 - 25 °C (68 - 77 °F) Reference substance: (water = 1)
Density	: 0.7 g/cm ³ @ 20 - 25 °C (68 - 77 °F)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 246 - 260 °C
Thermal decomposition	: No data available
Viscosity	
Viscosity, kinematic	: 0.64 mm ² /s @ 25 °C (77 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: halogens peroxides Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	: Carbon oxides Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Acute oral toxicity	: LD ₅₀ (Rat, male and female): > 5,000 mg/kg
Acute inhalation toxicity	: LC ₅₀ (Rat, male and female): > 73.5 mg/l Exposure time: 4 h Test atmosphere: vapour Remarks: Information given is based on data obtained from similar substances.



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Species: Rabbit

Exposure time: 24 h

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Result: No eye irritation

Respiratory or skin sensitisation

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Test Type: Maximization test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Based on a similar product formulation.

Germ cell mutagenicity

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Germ cell mutagenicity - Assessment : Mutagenicity classification not possible from current data

Carcinogenicity

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

Reproductive toxicity

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Reproductive toxicity - Assessment : Fertility classification not possible from current data.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

STOT - single exposure

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Aspiration toxicity

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Toxicity to fish : LC50 (Carassius auratus (goldfish)): 4 mg/l
Exposure time: 24 h
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.5 mg/l
Exposure time: 48 h
Test Type: static test
Remarks: Information given is based on data obtained from similar substances.

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

mg/l
Exposure time: 96 h
Test Type: static test

Acute aquatic toxicity- Assessment : Very toxic to aquatic life.
Chronic aquatic toxicity- Assessment : Very toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Biodegradability : aerobic
Inoculum: activated sludge
Biodegradation: 74.30 %
Exposure time: 56 d
Remarks: Inherently biodegradable.

Bioaccumulative potential

Components:

64742-49-0 / 426260-76-6 / 64742-89-8:

Partition coefficient: n-octanol/water : log Pow: 2.13 - 4.85 (25 °C)

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.



Safety Data Sheet BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

UN1206, HEPTANES, 3, II

IATA (International Air Transport Association):

UN1206, HEPTANES, 3, II

IMDG (International Maritime Dangerous Goods):

UN1206, HEPTANES, 3, II, Marine Pollutant (HEPTANE) , Flash Point:-9 - -7 °C(16 - 19 °F)

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B2: Flammable liquid
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Toluene	108-88-3	1000	*
**Benzene	71-43-2	10	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3	**Toluene
71-43-2	**Benzene
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3	**Toluene
71-43-2	**Benzene
100-41-4	**Ethylbenzene
91-20-3	**Naphthalene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

Massachusetts Right To Know

142-82-5	**Heptane
71-43-2	**Benzene

Pennsylvania Right To Know

64742-49-0 /	Naphtha (pet), hydrotreated It AND/OR
426260-76-6 /	Heptane, branched, cyclic and linear
64742-89-8	AND/OR Solvent naphtha (pet), It aliph.
142-82-5	**Heptane
108-88-3	**Toluene

California Prop 65

⚠ WARNING: This product can expose you to chemicals including **Cumene, **Benzene, **Ethylbenzene, **Naphthalene, which is/are known to the State of California to cause cancer, and **Toluene, **Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PHIL	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory




Safety Data Sheet BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

SECTION 16. OTHER INFORMATION

NFPA:



HMIS III:

HEALTH	1
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 11/12/2024

Material number:
16219448,

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value



Safety Data Sheet

BRAKE CLEAN SELECT

Version 1.1

Revision Date: 11/12/2024

IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		