

Version 1.2 Revision Date: 11/12/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : MOS METHANOL

Recommended use of the chemical and restrictions on use

Recommended use : SOLVENT

Manufacturer or supplier's details

Company : Motor Oil Supply Address : 1123 4th Ave N. Kent, WA. 98032

USA

Emergency telephone number:

Motor Oil Supply: -253-854-5454

Additional Information: : Phone: 253-854-5454

Regulatory Information Number: 253-854-5454

Email: mos@motoroilsupply.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Specific target organ toxicity

- single exposure

: Category 1 (Eyes, Central nervous system)

GHS label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or

if inhaled.

H370 Causes damage to organs.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

SDS Number: 100000078261 1 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

ment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/

physician.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

CAS-No.	Chemical name	Weight percent
67-56-1	Methanol	90 - 100

Any Concentration shown as a range is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

SDS Number: 100000078261 2 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

: Carbon oxides formaldehyde

toxic fumes

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

: Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for : Contain spillage, and then collect with non-combustible ab-

SDS Number: 100000078261 3 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

containment and cleaning up

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust. Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation

hood.

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
67-56-1	Methanol	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
		TWA	200 ppm 260 mg/m3	OSHA P0

SDS Number: 100000078261 4 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

PEL	200 ppm 260 mg/m3	CAL PEL
С	1,000 ppm	CAL PEL
STEL	250 ppm	CAL PEL
	325 mg/m3	

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and immediately after handling the

product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : Clear, colorless
Odour : alcohol-like
Odour Threshold : 4.2 - 5960 ppm

pH : No data available

Freezing Point (Melting point/freezing point)

: -97.8 - -97.6 °C (-144.0 - -143.7 °F)

Boiling Point (Boiling

: 64.7 °C (148.5 °F)

point/boiling range)
Flash point

: 11 °C (52 °F)

Evaporation rate : 4.1

(Butyl Acetate = 1)

Flammability (solid, gas) : No data available

Upper explosion limit : 36.5 %(V)

SDS Number: 100000078261 5 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

Lower explosion limit : 5.5 %(V)

Vapour pressure : 96.00 mmHg Relative vapour density : 1.1 @ 20 °C (68 °F)

(Air = 1.0)

Relative density : 0.791 - 0.793 @ 20 °C (68 °F)

Reference substance: (water = 1)

Density : 0.792 g/cm3 @ 20 °C (68 °F)

Solubility(ies)

Water solubility : completely miscible Solubility in other solvents : No data available Partition coefficient: n- : log Pow: 0.82

octanol/water

Auto-ignition temperature : 464 °C

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : 0.8 mPa.s @ 25 °C (77 °F)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- : Vapours may form explosive mixture with air.

tions

Conditions to avoid : Keep away from heat, flame, sparks and other ignition

sources.

Exposure to moisture

Incompatible materials : Acids

Alkali metals Alkalis

Oxidizing agents Reducing agents

Hazardous decomposition : Carbon oxides

products Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

67-56-1:

Acute oral toxicity : Assessment: The component/mixture is toxic after single in-

gestion.

SDS Number: 100000078261 6 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term

inhalation.

Remarks: Supporting toxicological evidence is limited for this classification. This harmonized classification will replace the indicated classification due to industry leaders and the EU

Harmonized Classification (Annex VII).

Acute dermal toxicity : Assessment: The component/mixture is toxic after single con-

tact with skin.

Serious eye damage/eye irritation

Product:

Result: Irritating to eyes.

Carcinogenicity

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

STOT - single exposure

Components:

67-56-1:

Target Organs: Eyes, Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 1.

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

SDS Number: 100000078261 7 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

tection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

DOT (Department of Transportation):

UN1230, Methanol, 3, II

IATA (International Air Transport Association):

UN1230, Methanol, 3 (6.1), II

IMDG (International Maritime Dangerous Goods):

UN1230, METHANOL, 3, (6.1), II, Flash Point:11 °C(52 °F)

Special Notes: : This product may be marked LTD QTY (Limited Quantity) and

may be considered not regulated for transport by road and rail, due to its form, quantity, and packaging presenting a lim-

ited hazard during transportation.

SECTION 15. REGULATORY INFORMATION

WHMIS Classification : B2: Flammable liquid

D2B: Toxic Material Causing Other Toxic Effects

SDS Number: 100000078261 8 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	•	Calculated product RQ
		(lbs)	(lbs)
Methanol	67-56-1	5000	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting re-

quirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

67-56-1 Methanol

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

67-56-1 Methanol

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

67-56-1 Methanol

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

Massachusetts Right To Know

67-56-1 Methanol

Pennsylvania Right To Know

67-56-1 Methanol

California Prop 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

SDS Number: 100000078261 9 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory


KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

SECTION16. OTHER INFORMATION

NFPA:



Special hazard

HMIS III:

HEALTH	2/
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Revision Date : 11/12/2024

Material number: 16219784, 16219293

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Govern- ment Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenar- io Tool	OSHA	Occupational Safety & Health Administration

SDS Number: 100000078261 10 / 11 MOS METHANOL



Version 1.2 Revision Date: 11/12/2024

EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and
			Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		

SDS Number: 100000078261 11 / 11 MOS METHANOL