

RENOVATIONS TO PALMERTON HIGH SCHOOL WEIGHT ROOM

3525 FIRELINE ROAD
PALMERTON, PA 18071

PALMERTON AREA SCHOOL DISTRICT

680 FOURTH STREET PALMERTON, PA 18071

GENERAL CONDITIONS

- IN CASE OF CONFLICT BETWEEN NOTES, DETAILS, AND SPECIFICATIONS, THE MOST STRINGENT REQUIREMENTS SHALL GOVERN.
- PERFORM ALL WORK INCLUDING CONSTRUCTION PRACTICES, USE AND DISPOSAL OF MATERIALS, AND QUALITIES OF WORKMANSHIP, IN STRICT ACCORDANCE WITH THE REQUIREMENTS OF THE GOVERNING LOCAL, STATE, AND NATIONAL CODES AND SPECIFICATIONS FOR THIS CONSTRUCTION PROJECT. PROVIDE APPROPRIATE SAFETY MEASURES SATISFYING ALL OSHA REQUIREMENTS.
- QUALITY OF MATERIALS AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE BEST STANDARDS AND PRACTICES OF THE TRADES INVOLVED.
- THE CONTRACTOR SHALL FILE ALL REQUIRED INSURANCE CERTIFICATES AND OBTAIN ALL REQUIRED BUILDING PERMITS PRIOR TO COMMENCEMENT OF THE WORK. COSTS OF PERMITS TO BE PAID BY BUILDER, APPROVED PERMIT TO BE POSTED.
- A COMPLETE SET OF PROJECT DOCUMENTS, INCLUDING AN ORIGINAL STAMPED SET OF DRAWINGS AND ALL SUBSEQUENT CHANGES AND CLARIFICATIONS SHALL BE KEPT ON SITE AT ALL TIMES. ALL PROPOSED CHANGES TO ORIGINAL PROJECT DOCUMENT BID SET ARE TO BE SUBMITTED BY CONTRACTOR IN THE FORM OF CHANGE ORDERS, INCLUDING ALL BACKUP INFORMATION, FOR APPROVAL BY OWNER/ARCHITECT.
- PRIOR TO COMMENCEMENT OF WORK, CONTRACTOR, OWNER, AND ARCHITECT SHALL HOLD A PRE-CONSTRUCTION CONFERENCE TO CONFIRM SITE ACCESS ROUTE, SCHEDULE, AND SEQUENCE OF WORK.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SECURITY AND PROTECTION OF ALL CONDITIONS AND MATERIALS WITHIN THE PROPOSED CONSTRUCTION AREA. THE CONTRACTOR SHALL HAVE SOLE RESPONSIBILITY FOR ANY DAMAGE OR INJURY CAUSED BY OR DURING THE EXECUTION OF WORK.
- SECTIONS AND DETAILS SHOWN, WHILE DRAWN FOR SPECIFIC LOCATIONS, ARE INTENDED TO ESTABLISH THE GENERAL TYPES OF DETAILS TO BE USED THROUGHOUT. WORK NOT INDICATED ON A PART OF THE DRAWINGS BUT REASONABLY IMPLIED TO BE SIMILAR TO THAT SHOWN AT CORRESPONDING PLACES, SHALL BE REPEATED. MINOR DETAILS NOT USUALLY SHOWN OR SPECIFIED, BUT REQUIRED FOR PROPER CONSTRUCTION OF ANY PART OF THE WORK SHALL BE INCLUDED AS IF THEY WERE INDICATED IN THE DRAWINGS.
- CONTRACTOR TO VERIFY AND/OR ESTABLISH ALL EXISTING CONDITIONS AND DIMENSIONS AT THE SITE AND TO NOTIFY THE OWNER/ARCHITECT OF ANY DISCREPANCIES AND/OR DEVIATIONS FROM DRAWINGS. PROPOSED REMEDIES, IF REQUIRING ADDITIONAL WORK, ARE TO BE SUBMITTED FOR APPROVAL IN THE FORM OF WRITTEN CHANGE ORDERS TO THE OWNER IN ACCORDANCE WITH THE TERMS OF THE CONTRACT BEFORE ORDERING MATERIAL OR COMMENCING WITH WORK.
- CONTRACTOR TO VERIFY LOCATION OF ALL BELOW GRADE UTILITIES AND STORM WATER SYSTEMS PRIOR TO EXCAVATION. NOTIFY ARCHITECT OF ANY CONFLICTS WITH PROPOSED CONSTRUCTION.
- ARCHITECT/ENGINEER IS NOT RESPONSIBLE FOR WORK THAT THE ARCHITECT/ENGINEERS DOES NOT REVIEW AND/OR WORK NOT COMPLETED IN ACCORDANCE WITH ARCHITECT/ENGINEER'S PLAN AND/OR INSTRUCTIONS. NO DEVIATION FROM DESIGN DRAWINGS IS PERMITTED WITHOUT WRITTEN APPROVAL.
- PROVIDE DAILY CLEAN-UP OF AREAS ADJACENT TO CONSTRUCTION AS WELL AS PERIODIC CLEAN-UP OF CONSTRUCTION AREAS.
- AT JOB COMPLETION, BESIDES FINAL GENERAL CLEANING, REMOVE ALL STAINS AND PAINT FROM ALL NEW GLASS, TILE, AND OTHER FINISHES AND WASH AND POLISH STONE.

GENERAL DRAWING NOTES

- WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALED DIMENSIONS.
- ITEMS NOT NOTED AS EXISTING ARE NEW. DOORS AND WINDOWS NOT NUMBERED ON THE FLOOR PLAN OR ELEVATIONS ARE EXISTING TO REMAIN, UNLESS NOTED OTHERWISE.
- ALL DIMENSIONS TO EXISTING SURFACES ARE TO FINISH, AND ALL DIMENSIONS TO NEW CONSTRUCTION ARE TO ROUGH FRAMING, UNLESS NOTED OTHERWISE.
- MECHANICAL, ELECTRICAL, PLUMBING & FIRE PROTECTION SYSTEMS INDICATED ON ARCHITECTURAL DRAWINGS ARE FOR REFERENCE ONLY. COORDINATE WITH MEPP DRAWINGS.
- ENCLOSED ACCESSIBLE SPACE UNDER STAIRS SHALL HAVE WALLS AND SOFFITS PROTECTED BY 5/8" FIRE RATED GWB UNLESS NOTED OTHERWISE.

MATERIALS

	GYPSUM WALLBOARD
	FOAM INSULATION
	BATT INSULATION
	RIGID INSULATION
	LOOSE FILL INSULATION
	WOOD BLOCKING
	ROUGH WOOD
	FINISH WOOD
	PLYWOOD/SHEATHING
	MDO/MDF
	ORIENTED STRAND BOARD (OSB)
	CORK
	GLASS
	BRICK
	CONCRETE
	CONCRETE UNIT MASONRY
	STONE
	TILE
	TERRAZZO
	EARTH
	GRAVEL
	CLAY
	STEEL
	ALUMINUM

SYMBOLS

	KEYED NOTE IDENTIFIER		CEILING HEIGHT & MATERIAL IDENTIFIER
	KEYED NOTE (DEMOLITION)		GLAZING PANEL IDENTIFIER
	CASEWORK/MILLWORK IDENTIFIER		FURNITURE IDENTIFIER
	REVISION IDENTIFIER		FLOOR FINISH PLAN - FLOOR/WALL/BASE FINISH IDENTIFIER
	COLUMN LINE OR GRID IDENTIFIER		SPOT ELEVATION INDICATOR
	DETAIL INDICATOR		NORTH INDICATOR
	SECTION INDICATOR		LEVEL INDICATOR
	EXTERIOR ELEVATION INDICATOR		SLOPE INDICATOR
	INTERIOR ELEVATION INDICATOR		DIMENSION STRING
	ROOM NAME		EXISTING DOOR TO REMAIN (SWING @ 45 DEGREES)
	DOOR & RATING IDENTIFIER		DOOR TO BE DEMOLISHED
	WINDOW / GLAZING IDENTIFIER		NEW DOOR AS SCHEDULED (SWING @ 90 DEGREES)
	PARTITION TYPE IDENTIFIER		
	ACCESSORIES IDENTIFIER		


LINE TYPES

	EXISTING CONSTRUCTION		BREAK LINE
	ITEM / WALL TO BE DEMOLISHED		MATCH LINE
	NEW CONSTRUCTION		MOISTURE / VAPOR BARRIER
	HIDDEN ITEM		DAMPDROOFING / WATER PROOFING
	ITEM ABOVE		1 HR FIRE-RATED WALL
	CENTERLINE		2 HR FIRE-RATED WALL
	GRID LINE		3 HR FIRE-RATED WALL
			PATH OF EGRESS

DRAWING INDEX

NO.	SHEET NAME
GENERAL	
G0.00	COVER SHEET
G1.00	GENERAL INFORMATION
G1.01	LIFE SAFETY PLAN
ARCHITECTURE	
A0.01	DEMOLITION PLAN - LEVEL 01
A1.01	REFERENCE PLAN - LEVEL 01
A1.02	FLOOR PLAN - LEVEL 01
A1.20	REFLECTED CEILING PLAN - LEVEL 01
A1.60	FINISH PLAN & SCHEDULE - LEVEL 01
A4.00	WALL SECTIONS
A6.00	DOOR SCHEDULE & DETAILS
PLUMBING	
P0.00	COVER SHEET - PLUMBING
P0.01	DEMOLITION PLAN - PLUMBING
P1.01	FLOOR PLANS - PLUMBING
P2.01	ENLARGED FLOOR PLANS - PLUMBING
P3.01	DETAILS - PLUMBING
P3.02	DETAILS - PLUMBING
P4.01	SPECIFICATIONS - PLUMBING
MECHANICAL	
M1.1	FIRST FLOOR PLAN - MECHANICAL (FOR COORDINATION PURPOSES ONLY)
ELECTRICAL	
E0.00	COVER SHEET - ELECTRICAL
E0.01	DEMOLITION PLAN - LEVEL 01 - ELECTRICAL
E1.01	FLOOR PLAN - LEVEL 01 - LIGHTING
E2.01	FLOOR PLAN - LEVEL 02 - POWER
E3.01	DETAILS & DIAGRAMS - ELECTRICAL
E4.01	SPECIFICATIONS - ELECTRICAL
E4.02	SPECIFICATIONS - ELECTRICAL

SITE LOCATION MAP



PROJECT:

RENOVATIONS TO PALMERTON HIGH SCHOOL WEIGHT ROOM

3525 FIRELINE ROAD
PALMERTON, PA 18071

OWNER:

PALMERTON AREA SCHOOL DISTRICT

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:

ARCHITECT: ALLOYS ARCHITECTURE
STRUCTURAL: PANY & LENTZ ENGINEERING

CIVIL: KEYSTONE CONSULTING ENGINEERS, INC.
MEPE: SNYDER HOFFMAN & McCLURE COMPANY

SUBMISSIONS:


NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION:

ALLOY5 ARCHITECTURE
530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055




SHEET TITLE:

COVER SHEET


DATE:	02/16/2024
SCALE:	As indicated
DRAWN BY:	MC
CHECKED BY:	RG
PROJ NO:	22-0073

GO.00


ADA STANDARDS




URINAL CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




KNEE & TOE CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




IPC 2017: 405.5 URINAL PARTITIONS.
EACH URINAL UTILIZED BY THE PUBLIC OR EMPLOYEES SHALL OCCUPY A SEPARATE AREA WITH WALLS OR PARTITIONS TO PROVIDE PRIVACY EXCEPT AS NOTED:
1. URINAL PARTITIONS SHALL NOT BE REQ'D IN A SINGLE-OCCUPANCY OR FAMILY/ASSISTED-USE TOILET ROOM W/ A LOCKABLE DOOR.
2. TOILET ROOMS LOCATED IN CHILD DAY CARE FACILITIES AND CONTAINING TWO OR MORE URINALS SHALL BE PERMITTED TO HAVE ONE URINAL W/O PARTITIONS




ACCESSORY CLEARANCES AND MOUNTING HEIGHTS
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




PLAN OF WHEEL CHAIR ACCESSIBLE STALL
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




PLAN OF AMBULATORY ACCESSIBLE STALL
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




TOILET COMPARTMENTS & TOILET FIXTURE CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




LAVATORY CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




DRINKING FOUNTAIN CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




SHOWER COMPARTMENT CLEARANCES
SCALE: N.T.S.
ANSI A117.1-2017




MANUAL SWINGING DOOR CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




SIGNAGE MOUNTING
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




CLEAR FLOOR SPACE - NEW BUILDINGS
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




OBSTRUCTED HIGH FORWARD REACH
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




SIDE & FRONT REACH CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




GRAB BARS IN TRANSFER-TYPE SHOWER COMPARTMENTS
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017




GRAB BARS IN STANDARD ROLL-IN-TYPE SHOWER COMPARTMENTS
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017



GRAB BARS IN STANDARD ROLL-IN-TYPE SHOWER PLANS
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017



MANUAL SWINGING DOOR CLEARANCES
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017



CLEAR FLOOR SPACE - NEW BUILDINGS
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017

OBSTRUCTED HIGH SIDE REACH
SCALE: 1/4" = 1'-0"
ANSI A117.1-2017

KEY PLAN

REGISTRATION:
ALLOY5
ARCHITECTURE
530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055

SHEET TITLE:
GENERAL INFORMATION

DATE:	02/16/2024
SCALE:	1/4" = 1'-0"
DRAWN BY:	Author
CHECKED BY:	Checker
PROJ NO:	22-0073

G1.00

PROJECT:
RENOVATIONS TO PALMERTON HIGH SCHOOL WEIGHT ROOM

3525 FIRELINE ROAD
 PALMERTON, PA 18071

OWNER:
PALMERTON AREA SCHOOL DISTRICT

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:

ARCHITECT: ALLOYS ARCHITECTURE
STRUCTURAL: PANY & LENTZ ENGINEERING

CIVIL: KEYSTONE CONSULTING ENGINEERS, INC.
MEPE: SNYDER HOFFMAN & McCLURE COMPANY

SUBMISSIONS:


NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION:

ALLOY5
 ARCHITECTURE
 530 WEST BROAD ST BETHLEHEM, PA 18018
 610.419.4055



SHEET TITLE:

LIFE SAFETY PLAN

DATE: 02/14/2024

SCALE: As Indicated


DRAWN BY: Author

CHECKED BY: Checker

PROJ NO: 22-0073

G1.01

BUILDING CODE DATA SUMMARY		
APPLICABLE BUILDING CODES & REGULATIONS:		
TOWNSHIP OF LOWER TOWAMENSING ZONING CODE	2018 INTERNATIONAL MECHANICAL CODE	
2018 INTERNATIONAL BUILDING CODE	2018 INTERNATIONAL PLUMBING CODE	
2018 INTERNATIONAL EXISTING BUILDING CODE	2017 NATIONAL ELECTRICAL CODE	
2017 ICC A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES	2018 INTERNATIONAL FIRE CODE	
PROJECT DESCRIPTION:		
SINGLE STORY RENOVATION TO ATHLETIC FIELD HOUSE		
IEBC ALTERATION LEVEL: 3	EXISTING BUILDING	RENOVATION
OCCUPANCY CLASSIFICATION:	GROUP A3	NO CHANGE
OCCUPANCY SEPARATION PROVIDED:	N/A	1 HR
AREA OF WORK:	N/A	4,175 GSF
CONSTRUCTION CLASSIFICATION:	TYPE III B	NO CHANGE
AUTOMATIC SPRINKLERS PROVIDED:	NONE	NO CHANGE
PORTABLE FIRE EXTINGUISHERS:	2 PROVIDED	NO CHANGE
# OF EXITS REQUIRED / # OF EXITS PROVIDED	2 / 5	2 / 4
TOTAL OCCUPANT LOAD:	-	135 OCCUPANTS
MAXIMUM EXIT ACCESS TRAVEL DISTANCE:	200 FT.	250 FT.



1 LEVEL 01 - EGRESS PLAN
 1/8" = 1'-0"

OCCUPANT LOAD - FIRST FLOOR																	
Level	NO.	Name	Use Group	Room Calcs		Room Capacity	Male Water Closet Load	Plumbing Loads		Plumbing Loads		Female Lav Load	Required Female Lavs	Male Lav Load	Plumbing Loads Required Male Lavs	Drinking Fountain Load	Plumbing Loads Required Drinking Fountains
				Area	SF Per Person			Required WC (Male)	Female Water Closet Load	Required WC (Female)	Female Lav Load						
(none)																	
Level 01	104	BOYS RESTROOM	(none)	113		0		0.00		0.00		0.00		0.00			0.000
Level 01	105	GIRLS RESTROOM	(none)	113		0		0.00		0.00		0.00		0.00			0.000
Level 01	110	JAN.	(none)	23		0		0.00		0.00		0.00		0.00			0.000
Level 01	103	RESTROOM - A	(none)	78		0		0.00		0.00		0.00		0.00			0.000
Level 01	102	RESTROOM - B	(none)	85		0		0.00		0.00		0.00		0.00			0.000
Not Placed	111	Room	(none)	0		0		0.00		0.00		0.00		0.00			0.000
(none): 6			A3	413		0		0.00		0.00		0.00		0.00			0.000
A1 (exercise room)			A3														
Level 01	100	WEIGHT ROOM	A1 (exercise room)	2870	50	58	125	0.23	65	0.45	200	0.14	200	0.14	500		0.116
Level 01	111	WRESTLING ROOM	A1 (exercise room)	2574	50	52	125	0.21	65	0.40	200	0.13	200	0.13	500		0.104
A1 (exercise room): 2				5443		110		0.44		0.84		0.27		0.27			0.220
B																	
Level 01	101	OFFICE	B	79	150	1	25	0.02	25	0.02	40	0.01	40	0.01	100		0.010
B: 1				79		1		0.02		0.02		0.01		0.01			0.010
E																	
Level 01	106	BOYS LOCKERS	E	211	20	11	50	0.11	50	0.11	50	0.11	50	0.11	100		0.110
Level 01	107	GIRLS LOCKERS	E	211	20	11	50	0.11	50	0.11	50	0.11	50	0.11	100		0.110
E: 2				422		22		0.22		0.22		0.22		0.22			0.221
S																	
Level 01	108	STORAGE	S	112	300	1	100	0.00	100	0.00	100	0.00	100	0.00	1000		0.001
Level 01	109	UTILITY	S	82	300	1	100	0.00	100	0.00	100	0.00	100	0.00	1000		0.001
S: 2				194		2		0.01		0.01		0.01		0.01			0.002
Grand total: 13				6550		135		0.69		1.09		0.52		0.52			0.452

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24




GENERAL DEMOLITION NOTES

- DEMOLITION DRAWINGS AND KEYED DEMOLITION NOTES ARE FOR CONTRACTOR'S CONVENIENCE ONLY. THE CONTRACTOR SHALL REMOVE ALL MATERIALS THAT ARE NOT REQUIRED IN THE FINISHED WORK UNLESS NOTED OTHERWISE. ALL PATCH MATERIAL SHALL MATCH EXISTING TYPE, PLANE, AND FINISH UNLESS NOTED OTHERWISE.
- SEE MECHANICAL, ELECTRICAL, PLUMBING, AND FIRE PROTECTION DRAWINGS FOR ADDITIONAL SCOPE OF DEMOLITION OF EQUIPMENT AND SERVICES. CONTRACTOR SHALL REMOVE ALL MATERIALS NOT INTENDED TO BE INCORPORATED INTO THE NEW WORK.
- PROVIDE STRUCTURAL SUPPORT FOR ALL EXISTING LOAD BEARING WALLS TO REMAIN.
- WHERE REMOVING WALLS OR PARTITIONS EXTENDS ONE FINISHED AREA INTO ANOTHER FINISHED AREA, FLOOR PATCH BETWEEN AREAS SHALL HAVE A LEVEL TOLERANCE NOT TO EXCEED 1/8" PER FOOT.
- REMOVE ALL EXISTING CASEWORK, BULKHEADS, AND SOFFITS THAT ARE NOT INDICATED TO REMAIN UNLESS NOTED OTHERWISE.
- CONTRACTOR TO PROVIDE OPENINGS IN EXISTING PARTITIONS AND FLOOR/CEILING ASSEMBLIES AS REQUIRED FOR NEW DUCT AND PIPING PENETRATIONS WHETHER OR NOT INDICATED ON THE ARCHITECTURAL DRAWINGS OR SPECIFICATIONS. REFER TO MEP DRAWINGS FOR MORE INFO. PROVIDE NEW FRAMING AS REQUIRED.
- REMOVE ALL MISCELLANEOUS EQUIPMENT AND ACCESSORIES NOT INDICATED TO REMAIN UNLESS NOTED OTHERWISE.
- REMOVE ALL EXISTING CEILINGS, SOFFITS, AND ASSOCIATED COMPONENTS UNLESS NOTED OTHERWISE.
- COORDINATE ALL NEW OPENING DIMENSIONS WITH PLANS.
- VERIFY ALL DIMENSIONS IN FIELD ASSOCIATED WITH ANY NEW WORK.
- PATCH AND REPAIR ALL SURFACES AFFECTED BY DEMOLITION. CONTRACTOR TO PATCH AND REPAIR OPENINGS LEFT BY OTHER TRADES WHERE APPLICABLE.
- CONTRACTOR TO PATCH, REPAIR, AND REFINISH ALL EXISTING BUILDING ELEMENTS TO REMAIN.

COORDINATION OF DEMOLITION:

- GC WILL PROVIDE FLOOR CUTTING, EXCAVATION, BACKFILL, PATCHING, AND FINISHING OF CONCRETE FLOORS WHERE NEEDED FOR INSTALLATION OF UNDERGROUND SANITARY PIPING. REFER TO MEP COORDINATION DRAWINGS. REFER TO DEMOLITION NOTE #12 FOR PREPARATION OF SLAB FOR NEW FINISH.
- WHERE FLOOR MOUNTED PLUMBING FIXTURES OR FLOOR DRAINS ARE TO BE REMOVED, GC SHALL OPEN FLOOR. ESCO CONTRACTOR WILL REMOVE PIPING TO BELOW FLOOR AND THE GC WILL PATCH CONCRETE FLOOR AND FINISH. REFER TO COORDINATION DRAWINGS.
- GC WILL REMOVE EXISTING CEILINGS AND PROVIDE NEW WHERE REQUIRED FOR ABOVE CEILING PIPING INSTALLATION. ESCO CONTRACTOR WILL PROVIDE WALL OR ROOF PENETRATIONS FOR WATER HEATER FLUE AND COMBUSTION OF AIR DUCTS. ESCO CONTRACTOR WILL BE RESPONSIBLE FOR PATCHING AND / OR REPAIRING ANY WALL OR ROOF DAMAGE.



1 LEVEL 01- DEMOLITION PLAN
1/8" = 1'-0"

KEYED DEMOLITION NOTES

NO.	NOTE
1	REMOVE FULL HEIGHT OF WALL CONSTRUCTION, COMPONENTS AND BASE FOR EXTENT INDICATED DOWN TO FLOOR SLAB. IF FLOOR STRUCTURE STOPS EACH SIDE OF WALL (I.E. EDGE OF SLAB) DEMOLISH WALL DOWN TO 8" BELOW FINISH FLOOR. WHERE NEW FOOTINGS CROSS EXISTING FOOTINGS, DEMOLISH ENTIRE EXISTING FOOTING. REPLACE WITH STRUCTURAL FILL. PATCH FLOOR AND ADJACENT WALLS AS REQUIRED AND PREPARE FOR NEW FINISHES. PROVIDE NEW LINTEL IF REQUIRED AS SHOWN ON STRUCTURAL PLANS. ASSUME SLAB ON EITHER SIDE DO NOT ALIGN AND GRINDING WILL BE REQUIRED.
2	REMOVE DOOR, FRAME, AND HARDWARE IN THEIR ENTIRETY. SEE FLOOR PLANS FOR NEW DOOR/ WINDOW CONFIGURATION OR INFILL INFORMATION. MASONRY INFILL SHALL BE TOOTHED TO ADJOINING CMU. PROVIDE LINTEL AS REQUIRED. REMOVE WALL CONSTRUCTION ABOVE IF REQUIRED. PREPARE ADJACENT WALLS TO RECEIVE NEW FINISHES.
3	REMOVE TOILET PARTITIONS AND ACCESSORIES IN THEIR ENTIRETY. REFER TO PLUMBING DRAWINGS FOR REMOVAL OF FIXTURES. PLUMBING FIXTURES TO BE REMOVED. PLUMBING CONTRACTOR TO PATCH WALLS AND FLOOR AFFECTED BY REMOVAL AND PREPARE FOR NEW FINISHES. COORDINATE WITH MPE CONTRACTORS AND MPE DEMOLITION PLAN FOR CAPPING OF UTILITIES. WORK IS TO BE PERFORMED BY P.C. REFER TO PLUMBING DRAWINGS.
4	REMOVE PORTION OF EXTERIOR MASONRY WALL FOR NEW OPENING TO EXTENT SHOWN. TOOTH IN TO EXISTING MASONRY TO PROVIDE FINISHED ENDS AND PREPARE NEW OPENING. REFERENCE PLANS FOR EXTENT. PROVIDE NEW LINTEL AS REQUIRED. REF. STRUCT. DWGS. PREPARE OPENING TO RECEIVE NEW FINISHES.
5	REMOVE CONCRETE FLOOR SLAB TO EXTENTS INDICATED ON FLOOR AND FOUNDATION PLANS. PREPARE TO RECEIVE NEW CONCRETE SLAB. COORD. WITH STRUCTURAL DRAWINGS. REMOVE OR ADD SUB BASE AND VAPOR BARRIER AS REQUIRED TO ACHIEVE NEW FLOOR SLAB ELEVATION SO THAT NEW FLOOR FINISHES ARE FLUSH WITH EXISTING FLOOR FINISH. COORDINATE WITH MPE DRAWINGS TO PREP FOR NEW DRAINS.
6	REMOVE EXISTING ELECTRICAL LIGHTING. COORD. WITH ELECTRICAL DRAWINGS. WORK IS TO BE PERFORMED BY E.C. REFER TO ELECTRICAL DRAWINGS.
7	TRENCH OUTSIDE OF BUILDING. IN ORDER TO CONNECT NEW WATER SERVICE TO BUILDING. WORK PERFORMED BY P.C. REFER TO CIVIL AND PLUMBING DRAWINGS
8	REMOVE EXISTING SHOWERS AND ACCESSORIES IN ITS ENTIRETY. ACCESSORIES ARE INCLUDING, BUT NOT LIMITED TO SHOWER CURTAINS, SOAP DISPENSERS, PAPER TOWEL DISPENSERS AND RECEPTACLES. WORK PERFORMED BY P.C. REFER TO PLUMBING DRAWINGS
9	REMOVE AND SALVAGE FIRE EXTINGUISHER AND CABINET AND OR AUTOMATED DEFBRILLATOR. PATCH INFILL WALL AS REQUIRED AND PREPARE FOR NEW FINISHES. SEE PLAN FOR REINSTALLATION LOCATIONS.
10	EXISTING LIGHTING AND CEILINGS SYSTEM TO REMAIN IN OLD LOCKER ROOM. ALTERNATE #1 REMOVE CEILING AND COMPONENTS IN ITS ENTIRETY SEE DIV 01 SPEC FOR FULL DESCRIPTION OF ALTERNATE. REFERENCE ELECTRICAL DRAWINGS
11	ALL EXISTING FITNESS EQUIPMENT TO BE REMOVED BY OWNER UNLESS NOTED OTHERWISE
12	PLUMBING CONTRACTOR TO REMOVE EXISTING WATER HEATER AND ITS COMPONENTS IN ENTIRETY AND PREP FOR NEW INSTALLATION OF WATER HEATER. REFER TO PLUMBING DRAWINGS

PROJECT:

**RENOVATIONS TO
PALMERTON HIGH
SCHOOL WEIGHT ROOM**

3525 FIRELINE ROAD
PALMERTON, PA 18071

OWNER:

**PALMERTON AREA
SCHOOL DISTRICT**

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:


ARCHITECT: ALLOYS ARCHITECTURE
STRUCTURAL: PANY & LENTZ ENGINEERING

CIVIL: KEYSTONE CONSULTING ENGINEERS, INC.
MEPE: SNYDER HOFFMAN & McCURE COMPANY

SUBMISSIONS:

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION:

ALLOY5
ARCHITECTURE
530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055

SHEET TITLE:

**REFERENCE PLAN -
LEVEL 01**

DATE: 02/16/2024


SCALE: As Indicated

DRAWN BY: Author

CHECKED BY: Checker

PROJ NO: 22-0073

A1.01




1 LEVEL 01 - REFERENCE PLAN
1/8" = 1'-0"

GENERAL PLAN NOTES


1. REFERENCE CIVIL, STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, FIRE PROTECTION, TELECOM, AND FOOD SERVICE DRAWINGS FOR ADDITIONAL INFORMATION. - **ESCO DRAWINGS**
2. ALL DIMENSIONS ARE NOMINAL UNLESS NOTED OTHERWISE.
3. ALL CONTRACTORS SHALL BE RESPONSIBLE FOR IDENTIFYING ROOMS, SIGNS, DOORS, KEYS, EQUIPMENT, PANELS, ETC BY THE OWNER'S FINAL NUMBERING - **NOT** THE ARCHITECTURAL NUMBERS.
4. GC TO PROVIDE FIRE EXTINGUISHERS AS REQUIRED BY CODE.
5. ALL NEW WALLS TO
6. B - BULLNOSE BLOCK LOCATION, TYPICAL AT ALL OUTSIDE CORNERS
7. REFERENCE SHEET G1.00 FOR ANSI 117.1-2009 REQUIRED ADA CLEARANCES.
8. PC TO COORDINATE W/ GC FOR ALL PLUMBING FIXTURE LOCATIONS.
9. FE - FIRE EXTINGUISHER CABINET
10. O.F.O.I. - OWNER FURNISHED OWNER INSTALLED

SUBMISSIONS:

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24



2 LEVEL 01 - FLOOR PLAN
 3/16" = 1'-0"



1 LEVEL 01 - FLOOR PLAN - ENLARGED LOCKER ROOMS
 1/4" = 1'-0"

KEYED PLAN NOTES


NO.	NOTE
1	DOUBLE STACKED METAL LOCKERS. SEE SPECIFICATIONS.
2	ADA SHOWER STALL WITH SHOWER CURTAIN AND ROD. SEE SPECIFICATIONS.
3	SHOWER STALL WITH PARTITION DOOR. SEE SPECIFICATIONS.
4	ADA LOCKER ROOM BENCH. SEE SPECIFICATIONS.
5	INSTALL PRIVACY FILM ON EXISTING WINDOW. SEE SPECIFICATIONS.
6	ADA AND STANDARD WATER FOUNTAIN TO BE PROVIDED AND INSTALLED BY PC
7	36" x 48" WINDOW WITH HM FRAME TO BE PAINTED. SEE DETAILS, AND SPECIFICATIONS.
8	TOOTHE IN CMU TO INFILL WHERE OPENINGS HAVE BEEN REMOVED. VERIFY EXISTING OPENINGS IN FIELD. REFERENCE DEMO PLAN. PAINT TO MATCH EXISTING COLOR. SEE STRUCTURAL DRAWINGS
9	WHITEBOARD. SEE SPECIFICATIONS
10	NEW SLAB TO BE LEVELED AND SMOOTH. PREPARE NEW CONCRETE SLAB TO RECEIVE NEW FINISH. SEE SPECIFICATIONS/STRUCTURAL DWGS FOR MORE INFORMATION
11	EXISTING DATA RACK TO REMAIN. GC TO PROTECT DURING ALL PHASES OF DEMOLITION AND CONSTRUCTION.
12	JANITOR SINK. SEE PLUMBING DWGS.

WALL TYPE GENERAL NOTES:

- DETAILS ARE NOT NUMBERED SEQUENTIALLY
- WALL TYPES DO NOT INCLUDE WALL FINISHES. SEE ROOM FINISH SCHEDULE & INTERIOR ELEVATIONS FOR FINISH INFORMATION.
- P = GENERAL PARTITION, F = FIRE RATED PARTITION, M = MASONRY PARTITION
- ALL RATED WALLS ARE TO BE CONSTRUCTED IN ACCORDANCE WITH TESTING AGENCY REQUIREMENTS. REFER TO SPECIFIC TEST REPORTS FOR REQUIRED COMPONENTS AND ASSEMBLY. SEE WALL TYPE REFERENCES AND LIFE SAFETY PLANS FOR RATED WALL LOCATIONS. PROVIDE FIRESTOPPING PER FIRESTOPPING MANUFACTURER'S RECOMMENDATIONS FOR PENETRATIONS THROUGH RATED WALLS.
- AT STEEL STUD WALLS WHICH DO NOT EXTEND TO STRUCTURE ABOVE, PROVIDE BRACE AT CENTERLINE OF DOOR OPENINGS AND BRACE @ 64" O.C. UNLESS NOTED OTHERWISE
- PROVIDE BLOCKING AS REQUIRED AT ALL WALL MOUNTED ITEMS INCLUDING BUT NOT LIMITED TO: WALL CABINETS, TOILET ROOM ACCESSORIES AND PARTITIONS, DOOR HARDWARE, COUNTER TOPS, WALL MOUNTED EQUIPMENT, ETC.
- ALL INTERIOR WALLS WHERE SOUND BATT INSULATION IS INDICATED ARE CONSIDERED ACOUSTIC WALLS. WHERE SPECIFIC STC RATINGS ARE REQUIRED, SEE INDIVIDUAL WALL TYPE PARTITIONS.
- COORDINATE RATINGS REQUIREMENTS INDICATED ON SPECIFIC PARTITIONS WITH LIFE SAFETY PLANS.
- WHERE TILE FINISH OCCURS, PROVIDE CEMENT BACKER BOARD IN LIEU OF GYPSUM BOARD AS SUBSTRATE. THICKNESS TO MATCH GYPSUM BOARD. REFER TO FINISH SCHEDULE AND INTERIOR ELEVATIONS FOR LOCATIONS OF TILE FINISH
- PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL RESTROOMS, LOCKER ROOMS, AND WET AREAS (WHERE TILE FINISH DOES NOT OCCUR).
- WOOD FRAMING TO BE PRESSURE TREATED WHERE NOTED ON STRUC DWGS. COORDINATE LOCATIONS W/ STRUC DWGS & STRUC SPECS.

GENERAL PLAN NOTES

- REFERENCE CIVIL, STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, FIRE PROTECTION, TELECOM, AND FOOD SERVICE DRAWINGS FOR ADDITIONAL INFORMATION. - **ESCO DRAWINGS**
- ALL DIMENSIONS ARE NOMINAL UNLESS NOTED OTHERWISE.
- ALL CONTRACTORS SHALL BE RESPONSIBLE FOR IDENTIFYING ROOMS, SIGNS, DOORS, KEYS, EQUIPMENT, PANELS, ETC BY THE OWNER'S FINAL NUMBERING - **NOT THE ARCHITECTURAL NUMBERS**
- GC TO PROVIDE FIRE EXTINGUISHERS AS REQUIRED BY CODE.
- ALL NEW WALLS TO
- B - BULLNOSE BLOCK LOCATION, TYPICAL AT ALL OUTSIDE CORNERS
- REFERENCE SHEET G1.00 FOR ANSI 117.1-2009 REQUIRED ADA CLEARANCES.
- PC TO COORDINATE W/ GC FOR ALL PLUMBING FIXTURE LOCATIONS.
- FE - FIRE EXTINGUISHER CABINET
- O.F.O.I. - OWNER FURNISHED OWNER INSTALLED



MARK	CMU SIZE	TOTAL THK	STC	SOUND ATTN	MARK	CMU SIZE	TOTAL THK	STC	SOUND ATTN
A	4"	-	43-45	-	E	12"	-	47-51	-
B	6"	-	44-46	-	F	-	-	-	-
C	8"	-	45-48	-	G	-	-	-	-
D	10"	-	46-50	-	H	-	-	-	-

M1 MASONRY PARTITION NOT TO SCALE


LOCKER SCHEDULE			
LOCATION	TYPE	SIZE	QTY
GIRLS LOCKERS	ML-1	12" X 12" X 72"	14
BOYS LOCKERS	ML-1	12" X 12" X 72"	14

LOCKERS TO BE INSTALLED ON WOOD FRAMED BASE. SEE DETAIL.

NO.	Manufacturer	Description	INSTALLED BY	SUPPLIED BY	COMMENTS
A-1	Bobrick Washroom Equipment, Inc.	Bobrick B-396 Classic Series Recessed Combination Towel and Waste Unit	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-2	Bobrick Washroom Equipment, Inc.	Bobrick B-165 Series Z436 Type 430 Stainless Steel	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-3	Bobrick Washroom Equipment, Inc.	Bobrick B-2111 Surface-Mounted Soap Dispenser	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-4	Bobrick Washroom Equipment, Inc.	Bobrick B-4288 Surface-Mounted Multi-Roll Toilet Tissue Dispenser	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-5	Bobrick Washroom Equipment, Inc.	1 1/4" Diameter Stainless Steel Grab Bars with Snap Flange	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-6	Bobrick Washroom Equipment, Inc.	1 1/4" Diameter Stainless Steel Grab Bars with Snap Flange	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-7	Bobrick Washroom Equipment, Inc.	1 1/4" Diameter Stainless Steel Grab Bars with Snap Flange	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-8	Bobrick Washroom Equipment, Inc.	Bobrick B-270 Contura Series Surface Mounted Sanitary Napkin Disposal	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-9	Bobrick Washroom Equipment, Inc.	Stainless Steel Surface Mounter Double Robe Hook	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-10	Bobrick Washroom Equipment, Inc.	Shower Curtain Rod With White Vinyl Shower Curtain (72" H) And SS Shower Curtain Hooks.	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-11	Bradley Corporation	Restroom Partitions, Urinal Screen	CONTRACTOR	CONTRACTOR	See Specs For Additional Information
A-12	Bradley Corporation	Restroom Partitions	CONTRACTOR	CONTRACTOR	See Specs For Additional Information

KEY PLAN:

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24



1 LEVEL 01 - REFLECTED CEILING PLAN
3/16" = 1'-0"

GC TO COORDINATE WITH MECHANICAL DRAWINGS. THRU ROOF VENTS TO BE PATCH AND REPAIRED

ALTERNATE #2

2A - REPLACE ALL NOTED 5/8" MOISTURE/ABUSE RESISTANT DRYWALL WITH 1/2" MARINE GRADE/FIRE TREATED PLYWOOD, PAINT AS REQUIRED PT-01



2B - REPLACE ALL NOTED 5/8" MOISTURE/ABUSE RESISTANT DRYWALL WITH 1/2" CEMENT BOARD, PAINT AS REQUIRED PT-01

CEILING LEGEND



- EXTENT OF CEILING
- [] 1x4' LED LIGHT FIXTURE
- [] 2'-0" X 2'-0" ACCESS PANEL (COLOR TO MATCH PAINTED CEILING)

GENERAL CEILING NOTES

- REFER TO MECHANICAL, ELECTRICAL, PLUMBING, AND FIRE PROTECTION DRAWINGS FOR CEILING EQUIPMENT INCLUDING BUT NOT LIMITED TO GRILLES, REGISTERS, DIFFUSERS, SPRINKLER HEADS, LIGHTING, AND EMERGENCY FIXTURES.
- REFER TO MEPE DRAWINGS FOR EXACT LOCATIONS, QUANTITIES, AND SIZES OF ALL EQUIPMENT.
- EXPOSED PLYWOOD CEILING TO BE PAINTED. ARCHITECT SHALL SELECT COLOR FROM FULL MANUFACTURER'S RANGE.
- EXPOSED METAL DECK & STEEL STRUCTURE TO BE PAINTED. WHERE APPLICABLE EXPOSED DUCTWORK TO BE PAINTED. ARCHITECT SHALL SELECT COLOR FROM FULL MANUFACTURER'S RANGE.
- EXPOSED WOOD DECK STRUCTURE TO BE PAINTED. ARCHITECT SHALL SELECT COLOR FROM FULL MANUFACTURER'S RANGE.
- PLYWOOD CEILING SYSTEM TO BE ATTACHED TO UNDERSIDE OF JOIST IN RUNNING BOND PATTERN. V.I.F. CEILING HEIGHT
- VERIFY ACCESS PANEL LOCATION PRIOR TO INSTALL.
- GC TO COORDINATE WITH MECHANICAL DRAWINGS. THRU ROOF VENTS TO BE PATCH AND REPAIRED



NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24



1 LEVEL 01 - FINISH PLAN
 1/4" = 1'-0"

ROOM FINISH SCHEDULE - LEVEL 01						
ROOM NO.	ROOM NAME	FLOOR FINISH	WALL BASE		WALL FINISH	COMMENTS
			MATL	HGT		
100	WEIGHT ROOM	CONC-01		--	PT-01, 02	
101	OFFICE	CONC-01		--	PT-01, 02	
102	RESTROOM - B	EP-01		--	PT-01, 02	
103	RESTROOM - A	EP-01		--	PT-01, 02	
104	BOYS RESTROOM	EP-01		--	PT-01, 02	
105	GIRLS RESTROOM	EP-01		--	PT-01, 02	
106	BOYS LOCKERS	EP-01		--	PT-01, 02	
107	GIRLS LOCKERS	EP-01		--	PT-01, 02	
108	STORAGE	CONC-01		--	PT-01, 02	
109	UTILITY	CONC-01		--	PT-01, 02	
110	JAN.	CONC-01		--	PT-01, 02	
111	WRESTLING ROOM	ETR	ETR	--	ETR	N.I.C.

CEILING TO BE PAINTED PT-01
 FOR PT-01 AND PT-02 MATCH EXISTING HEIGHTS

INTERIOR FINISH PLAN FLOORS & WALL BASE	INTERIOR FINISH PLAN WALLS	INTERIOR FINISH PLAN OTHER
CONCRETE Code: CONC-01 Sealed concrete floor with saw-cut joints, ground & waxed. Protect floor from stain-causing materials construction	PAINT Code: PT-01 Basis of Design: Sherwin Williams Color: Extra White SW7006 Finish: Semi-gloss Approved Equals: Benjamin Moore, PPG, Glidden	RESTROOM PARTITIONS Code: RP-01 Basis of Design: Scranton Products - Hiny Hiders Color: Black - Orange Peel Approved Equals: ASI Partitions, General Partitions, Metpar
EPOXY PAINT Code: EP-01 Basis of Design: INSL-X Sure Step Acrylic Anti-Slip Coating Color: Gray Pearl Approved Equals: Sherwin Williams, Behr, Benjamin Moore	PT-02 Basis of Design: Sherwin Williams Color: Blueblood SW6966 Finish: Semi-gloss Approved Equals: Benjamin Moore, PPG, Glidden	RUBBER WALL BASE AND ACCESSORIES Code: RWB-01 Basis of Design: Roppe Color: Blue Jay 664 Size: 4" Approved Equals: Mannington, Tarkett, Armstrong

ROOM FINISH LEGEND

NOTE: DESIGN SELECTION SUMMARY: FOR REFERENCE ONLY, SEE SPECIFICATIONS FOR FULL MATERIAL DOCUMENTATION

FLOORS
WALLS
BASE

GENERAL FINISH NOTES

- REFER TO SHEET A1.60 FOR ALL FINISH SELECTIONS, TYPICAL.
- REFER TO REFLECTED CEILING PLANS ON SHEETS A1.20 FOR SPECIFIC LOCATIONS AND HEIGHTS.
- GC TO PAINT ALL LOCATIONS WHICH INCLUDE, BUT ARE NOT LIMITED TO, ALL EXPOSED WOOD, EXPOSED DECK, EXPOSED SPRINKLER PIPING, EXPOSED CONDUIT, EXPOSED PIPING, EXPOSED DUCTWORK. COLOR SHALL BE SELECTED BY ARCHITECT.
- EPOXY PAINT TO BE PAINTED FULL LENGTH OF CMU WALLS AT LOCATIONS INDICATED ON FINISH SCHEDULE.
- ALL HOLLOW METAL DOOR FRAMES TO BE PRIMED AND PAINTED. FINAL COLOR SELECTION TO BE MADE BY ARCHITECT. REFER TO DOOR SCHEDULE FOR MORE INFORMATION.
- REFER TO DOOR SCHEDULE ON SHEET A6.00 AND DETAILS ON SHEET A6.00 FOR FLOOR TRANSITION DETAILS. GC TO COORDINATE FLOOR TRANSITIONS WITH DOORS.
- GWB CEILINGS TO RECEIVE 2 COATS OF PRIMER AND 1 COAT OF PAINT. COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE.

PROJECT:
**RENOVATIONS TO
 PALMERTON HIGH
 SCHOOL WEIGHT ROOM**

3525 FIRELINE ROAD
 PALMERTON, PA 18071

OWNER:
**PALMERTON AREA
 SCHOOL DISTRICT**

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:

ARCHITECT: ALLOYS ARCHITECTURE
STRUCTURAL: PANY & LENTZ ENGINEERING


CIVIL: KEYSTONE CONSULTING ENGINEERS, INC.
MEPE: SNYDER HOFFMAN & McCLURE COMPANY

SUBMISSIONS:		
NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:




REGISTRATION:
ALLOY5
 ARCHITECTURE
 530 WEST BROAD ST BETHLEHEM, PA 18018
 610.419.4055




SHEET TITLE:
WALL SECTIONS

DATE:	02/16/2024
SCALE:	As Indicated
DRAWN BY:	Author
CHECKED BY:	Checker
PROJ NO:	22-0073


A4.00




4 BUILDING SECTION - TRANSVERSE
 3/16" = 1'-0"



3 BUILDING SECTION - LONGITUDINAL
 3/16" = 1'-0"




1 SECTION 1
 3/4" = 1'-0"



2 SECTION 2
 3/4" = 1'-0"


2/23/2024 11:23:18 AM COPYRIGHT ALLOYS ARCHITECTURE



DOOR & FRAME SCHEDULE - LEVEL 01


NO.	TYPE	DOOR DATA		SIZE		LABEL & RATING	FRAME DATA			DETAILS		HARDWARE SET
		MATERIAL	FINISH	WIDTH	HEIGHT		FRAME TYPE	FRAME MATERIAL	FRAME FINISH	HEAD	JAMB	
101	A	HM	PTD	3'-0"	7'-0"		1	HM	PTD	H1	J1	SEE SPECS
102	A	HM	PTD	3'-0"	7'-0"		1	HM	PTD	H1	J1	SEE SPECS
103	A	HM	PTD	3'-0"	7'-0"		1	HM	PTD	H1	J1	SEE SPECS
104	A	HM	PTD	3'-0"	7'-0"		1	HM	PTD	H1	J1	SEE SPECS
105	A	HM	PTD	3'-0"	7'-0"		1	HM	PTD	H1	J1	SEE SPECS
110	A	HM	PTD	3'-0"	7'-0"		1	HM	PTD	H1	J1	SEE SPECS

NOTE: ALL DOORS TO HAVE 4" HEAD TO ALIGN WITH CMU COURSING




GENERAL DOOR NOTES

- ALL HARDWARE TO BE ACCESSIBLE AND COMPLY WITH ANSI A117.1-2009
- PROVIDE CLOSERS & SMOKE SEALS ON ALL RATED DOORS





H1 HEAD
1 1/2" = 1'-0"

J1 JAMB
1 1/2" = 1'-0"



4 INTERIOR ELEVATION - TYPICAL LOCKER
1/4" = 1'-0"

2 TYPICAL LOCKER BASE DETAIL
1 1/2" = 1'-0"



WINDOW SCHEDULE

LEVEL	TYPE MARK	UNIT TYPE	SIZE		HEAD HEIGHT	MANUF	COMMENTS
			WIDTH	HEIGHT			
Level 01	A	FIXED	3'-0"	4'-0"	6'-8"	SEE SPECS	SEE SPECS/CT GLASS IN WINDOW

GLAZING GENERAL NOTES

- REFERENCE SHEET A6.00 FOR HM FRAME DETAILS.
- REFERENCE DOOR SCHEDULE FOR DOOR INFORMATION.
- ALL DIMENSIONS SHOULD BE VERIFIED IN FIELD PRIOR TO FABRICATION
- ALL WINDOWS, STOREFRONT, CURTAIN WALL, AND DOORS ON THE GROUND FLOOR UP TO 10'-0" ABOVE GRADE TO BE LAMINATED GLAZING (LIG)

GLAZING TYPES

CT CLEAR TEMPERED GLASS

PROJECT:

RENOVATIONS TO PALMERTON HIGH SCHOOL WEIGHT ROOM

3525 FIRELINE ROAD
PALMERTON, PA 18071

OWNER:

PALMERTON AREA SCHOOL DISTRICT

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:

ARCHITECT:
ALLOYS ARCHITECTURE

STRUCTURAL:
PANY & LENTZ ENGINEERING


CIVIL:
KEYSTONE CONSULTING ENGINEERS, INC.

MEP:
SNYDER HOFFMAN & McCLURE COMPANY

SUBMISSIONS:


NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION:

ALLOY5
ARCHITECTURE
530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055



SHEET TITLE:

DOOR SCHEDULE & DETAILS

DATE: 02/14/2024

SCALE: As Indicated

DRAWN BY: Author

CHECKED BY: Checker

PROJ NO: 22-0073

A6.00

PACKAGED ROOFTOP UNIT SCHEDULE - GAS_DX																												
ID	AREA SERVED	NOMINAL TONS	SUPPLY FAN DATA					DX COOLING PERFORMANCE DATA				GAS FURNACE HEATING PERFORMANCE DATA				ELECTRICAL DATA				BASIS OF DESIGN TRANE	REMARKS							
			MAXIMUM TOTAL AIRFLOW (CFM)	MINIMUM TOTAL AIRFLOW (CFM)	MAXIMUM OUTSIDE AIR (CFM)	CO2 CONTROL AIR (CFM)	MINIMUM OUTSIDE AIR (CFM)	ESP (IN. WC)	MOTOR HP	TOTAL CAPACITY (MBH)	SENSIBLE CAPACITY (MBH)	ENTERING AIR TEMP.		LEAVING AIR TEMP.		EER	GAS TYPE	INPUT (MBH)	OUTPUT (MBH)			ENTERING AIR TEMP. DB (°F)	LEAVING AIR TEMP. DB (°F)	VOLTAGE / PHASE	FLA (AMPS)	MCA (AMPS)	MCCP (AMPS)	UNIT WEIGHT (LBS)
RTU-1	WEIGHT/LOCKER ROOMS	10.0	3,600	2,175	3,600	1,450	375	1.83	3.0	120.4	85.5	79.0	65.9	55.5	54.7	11.0	NAT	200.0	162.0	56.0	97.8	460 / 3	25.0	29.0	40	1,258	YSJ120A450M	

- NOTES:
- DESIGN CONDITIONS: UNIT PERFORMANCE DATA BASED ON OUTSIDE AMBIENT TEMPERATURES OF 92.4°F DRY BULB, 76.5°F WET BULB SUMMER; 8.7°F DRY BULB, 62.5°F WET BULB WINTER AND INDOOR TEMPERATURES OF 75.0°F DRY BULB, 62.5°F WET BULB SUMMER; 72.0°F DRY BULB, 55.8°F WET BULB WINTER.
 - AIR CLEANING: UNIT SHALL BE PROVIDED WITH MERV 8 FILTER.
 - UNIT CONTROLS: FACTORY CONTROLS W/ BACNET INTERFACE FOR BAS INTEGRATION, BACNET MSTP_IP PROTOCOL, PHASE/BROWNOUT PROTECTION.
 - DUCTING CONFIGURATION: SUPPLY = DOWN, RETURN = DOWN.
 - UNIT MOUNTING CONFIGURATION: NEW ROOF CURB.
 - UNIT SUPPLY AIR CONTROL: CONSTANT VOLUME.
 - UNIT O/A CONTROL: HUMIDITY.


FAN SCHEDULE													
ID	AREA SERVED	PERFORMANCE				MOTOR DATA		FAN STYLE	DRIVE TYPE	FAN CONTROL	WEIGHT (LBS)	BASIS OF DESIGN GREENHECK	REMARKS
		CFM	EXT. S.P. (IN. WC.)	FAN RPM	SOUND POWER (SONES)	SIZE (HP OR WATTS)	VOLTAGE/ PHASE						
EF-1	RESTROOM A	100	0.35	1214	3.5	0.03	208/1	CEILING MOUNTED	DIRECT	TIME DELAY SWITCH	24	SP-A390-VG	SWITCH BY E.C.
EF-2	GIRLS RESTROOM	100	0.35	1214	3.5	0.03	208/1	CEILING MOUNTED	DIRECT	TIME DELAY SWITCH	24	SP-A390-VG	SWITCH BY E.C.
EF-3	RESTROOM B	100	0.35	1214	3.5	0.03	208/1	CEILING MOUNTED	DIRECT	TIME DELAY SWITCH	24	SP-A390-VG	SWITCH BY E.C.
EF-4	BOYS RESTROOM	100	0.35	1214	3.5	0.03	208/1	CEILING MOUNTED	DIRECT	TIME DELAY SWITCH	24	SP-A390-VG	SWITCH BY E.C.
EF-5	GIRLS LOCKERS	200	0.35	1249	4.0	0.03	208/1	CEILING MOUNTED	DIRECT	TIME DELAY SWITCH	24	SP-A390-VG	SWITCH BY E.C.
EF-6	BOYS LOCKERS	200	0.35	1249	4.0	0.03	208/1	CEILING MOUNTED	DIRECT	TIME DELAY SWITCH	24	SP-A390-VG	SWITCH BY E.C.

- NOTES:
- FAN ID KEY: EF = EXHAUST DUTY, SF = SUPPLY DUTY, RAF = RETURN DUTY, REF = RELIEF DUTY, TF = TRANSFER DUTY


- GENERAL NOTES - HVAC
- ALL SYSTEMS ARE SHOWN SCHEMATICALLY. CHECK AND VERIFY ALL CONDITIONS AT THE SITE WITHIN THE CONTRACT LIMITS.
 - ALL INSTALLATION AND WORK SHALL BE PERFORMED IN A NEAT, WORKMANLIKE MANNER SO AS NOT TO DAMAGE ANY SURFACES, EQUIPMENT, OR MATERIALS.
 - INSTALL ALL EQUIPMENT AND MATERIALS IN STRICT ACCORDANCE WITH RESPECTIVE MANUFACTURER'S WRITTEN INSTRUCTIONS.
 - COORDINATE HVAC WORK WITH THE WORK OF ALL OTHER TRADES.
 - ALL DIMENSIONS, DUCT SIZES AND PIPE SIZES ARE IN INCHES, UNLESS NOTED OTHERWISE.
 - FURNISH AND INSTALL ACCESS PANELS WHERE REQUIRED FOR ACCESS TO ALL CONCEALED VALVES, DAMPERS OR EQUIPMENT WHERE NO OTHER MEANS OF ACCESS IS PROVIDED.
 - ALL EQUIPMENT AND PIPING ABOVE THE CEILING SHALL BE SUPPORTED IN AN APPROVED MANNER FROM THE BUILDING STRUCTURE AND INCLUDES HANGERS AND RESTRAINTS IN ACCORDANCE WITH ALL APPLICABLE CODES AND SPECIFICATIONS.
 - WHERE EQUIPMENT, PIPING, DUCTWORK, CONDUIT, ETC. TO REMAIN IS SUPPORTED FROM EQUIPMENT AND/OR PIPING TO BE REMOVED, EXTEND EXISTING HANGERS OR PROVIDE NEW HANGERS AND SUPPORTS AS REQUIRED TO RE-SUPPORT ITEMS FROM THE BUILDING STRUCTURES.
 - EXISTING EQUIPMENT AND MATERIALS SHALL REMAIN, UNLESS NOTED OTHERWISE.
 - ALL SYSTEMS SHALL BE TESTED FOR PROPER OPERATION IN ACCORDANCE WITH APPLICABLE CODES AND REGULATIONS.
 - INSTALL ALL WORK IN ACCORDANCE WITH ALL APPLICABLE CODES AND REGULATIONS.
 - REMOVE EXISTING CEILING AS NECESSARY TO PERFORM DEMOLITION WORK AND TO INSTALL NEW WORK. REFER TO CONTRACT DOCUMENTS FOR CEILING REUSE OR REPLACEMENT SCOPE OF WORK.

- KEYED NEW WORK NOTES:
- ROUTE 6Ø EXHAUST AIR DUCT UP THROUGH EXISTING ROOF AND PROVIDE GOOSENECK TERMINATION ABOVE. NEW ROOF PENETRATIONS ARE DONE BY OTHERS.
 - WALL PENETRATIONS FOR NEW SUPPLY GRILLES ARE DONE BY OTHERS.
 - ROOF PENETRATIONS OF EXHAUST FANS BY OTHERS.
 - RELOCATION OF CONTROLS AND I.T. IN SPACE BY OTHERS.
 - PAINTING OF EXPOSED DUCTWORK TO BE DONE BY OTHERS.

FOR COORDINATION PURPOSES ONLY




1 PARTIAL FIRST FLOOR NEW WORK PLAN - MECHANICAL
1/8" = 1'-0"




- NOTES:
- DETAIL DOES NOT NECESSARILY SHOW ALL WORK REQUIRED AND SHALL BE MODIFIED AS NEEDED FOR SPECIFIC ROOFTOP UNIT SUPPLIED.
 - ROOF CURB AND ROOFTOP UNIT SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S WRITTEN INSTRUCTIONS.
 - DUCT INSULATION REQUIREMENTS SHALL BE VERIFIED WITH SPECIFICATIONS.

3 PACKAGED DX ROOFTOP UNIT WITH NEW CURB DETAIL



PROVIDE ROOF PROTECTION GUARD IN ACCORDANCE WITH 2018 IBC 304.1.1. GUARD SHALL BE A MINIMUM OF 42" HIGH AND EXTEND A MINIMUM OF 30" BEYOND THE UNIT. GUARD SHALL PREVENT THE PASSAGE OF A 2" SPHERE.


2 PARTIAL ROOF PLAN NEW WORK - MECHANICAL
1/8" = 1'-0"



- NOTES:
- REFER TO SPECIFICATIONS FOR ALLOWABLE CONDENSATE DRAIN PIPE MATERIAL AND INSULATION REQUIREMENTS.
 - MINIMUM CONDENSATE DRAIN PIPE SIZE BASED ON THE AIR CONDITIONING UNIT NOMINAL TONNAGE SHALL BE AS FOLLOWS, BUT IN NO CASE SMALLER THAN THE UNIT CONNECTION:

2.1.	2 TONS & LESS	=	3/4"
2.2.	2-1/2 TONS TO 3 TONS	=	1"
2.3.	4 TONS TO 30 TONS	=	1-1/4"
2.4.	31 TONS TO 50 TONS	=	1-1/2"
2.5.	51 TONS TO 170 TONS	=	2"
 - CONDENSATE DRAIN TRAP DIMENSIONS SHALL BE AS FOLLOWS:
 - DRAW THRU STYLE UNIT:
 - 3.1.1. X = SUPPLY FAN TOTAL (NOT EXTERNAL) STATIC PRESSURE (IN INCHES) + 1". MINIMUM DIMENSION SHALL BE 2'.
 - 3.1.2. Y = X/2 + 1". MINIMUM DIMENSION SHALL BE 2'.
 - BLOW THRU STYLE UNIT:
 - 3.2.1. X = MINIMUM DIMENSION SHALL BE 1/2'.
 - 3.2.2. Y = SUPPLY FAN EXTERNAL (NOT TOTAL) STATIC PRESSURE (IN INCHES) + 1/2'. MINIMUM DIMENSION SHALL BE 2'.

5 AIR CONDITIONING CONDENSATE DRAIN DETAIL



- NOTES:
- REFER TO SCHEDULE FOR REGULATOR SIZING INFORMATION.

4 GAS PRESSURE REGULATOR - INDOOR

REVISION SCHEDULE

No.	Description	Date
1	ISSUE FOR CONSTRUCTION	01/17/2024
2	ISSUE FOR COORDINATION	02/16/2024

MECHANICAL RENOVATIONS TO:

PALMERTON HIGH SCHOOL WEIGHT ROOM RENOVATIONS

PROJECT ADDRESS:
**3525 FIRELINE RD.
PALMERTON, PA 18071**

SHEET NO.

M1.1

PROJECT NO.

51049

DESIGNED BY

MB

DRAWN BY

MB

DATE

02/19/2024

CHECKED BY

JG

DWG. SCALE

As indicated

FIRST FLOOR PLAN - MECHANICAL

4101 NORTH SIXTH ST.
HARRISBURG, PA 17110
(717) - 232-9743
www.mclureco.com

mclure company

THIS DRAWING IS THE SOLE PROPERTY OF MCLURE COMPANY AND IS GRANTED UNDER LICENSE TO THE USER ONLY. DESIGN AND GENERAL ARRANGEMENT AND IS PARTLY DIAGRAMATIC. COPYRIGHT © MCLURE COMPANY

2/22/2024 11:23:39 AM

Table with 3 columns: NO., ISSUE DESCRIPTION, DATE. Includes entries for 100% DD REVIEW, 100% CD REVIEW, and BID SET.



PLUMBING DEMOLITION - GENERAL NOTES. 13 numbered notes detailing demolition procedures, including removal of piping, equipment, and existing materials, and coordination with other trades.

DESIGN CODE REFERENCES. Table listing codes such as PA-UCC, ICC, IFGC, IMC, IPC, IFC, IECC, and FGI.

REFERENCED DESIGN STANDARDS. Table listing standards such as NEMA, NFPA 13, NFPA 99, and NFPA 101.

PLUMBING GENERAL NOTES. 40 numbered notes covering installation requirements, coordination, and specific plumbing details for the project.

PLUMBING MISCELLANEOUS LEGEND. Symbols for flow arrows, pipe cap, cleanout above ceiling, cleanout to grade, expansion loops, pipe cross, pipe drop, pipe rise, pipe stack, pipe tee drop/rise, valve in pipe drop, vent thru roof, and wall cleanout.

PLUMBING DRAIN LEGEND. Symbols for air gap fitting, emergency rain water outlet, floor cleanout, floor drain (funnel, indirect, round, square), floor sink (full grate, half grate, no grate), roof drain (typical, emergency), and roof drain - emergency.

PLUMBING VALVE LEGEND. Symbols for anchor-pipe, ball valve, butterfly valve, check valve, circuit setter valve, compressed air outlet, gas cock, gas regulator, gate valve, globe valve, guide pipe, hose bibb, manual balancing valve, non-freeze wall hydrant, osby valve, pressure-reducing valve, recirculating pump, reduce pressure backflow preventer, shock absorber, solenoid valve, strainer, tempering valve, thermometer, and union pipe.

PLUMBING TAG LEGEND. Symbols for ADA symbol, connect to existing, demolition symbol, drawing tag, invert elevation tag, limit of demolition, note tag (circle, diamond, hexagonal, square), note tag - renovation, note tag - to be removed, plumbing fixture tag, and title revision tag.

PLUMBING ABBREVIATION LEGEND. Table mapping abbreviations (e.g., AAC, AFF, AFG) to full names and descriptions (e.g., Above Accessible Ceiling, General Contractor, Grease Interceptor).

PROJECT:

RENOVATIONS TO PALMERTON HIGH SCHOOL WEIGHT ROOM

3825 FIRELINE ROAD
PALMERTON, PA 18071

OWNER:

PALMERTON AREA SCHOOL DISTRICT

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:

ARCHITECT:
ALLOYS ARCHITECTURE


CIVIL:
KEYSTONE CONSULTING ENGINEERS, INC.

MEPE:
SNYDER HOFFMAN ASSOCIATES, INC.

SUBMISSIONS:

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION:

ALLOY5 ARCHITECTURE

530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055



SHEET TITLE:

DEMOLITION PLAN - PLUMBING

DATE: 02/16/24

SCALE: 1/8" = 1'-0"


DRAWN BY: KP

CHECKED BY: KJF

PROJ NO: 22-0073

P0.01

©COPYRIGHT ALLOYS ARCHITECTURE



1 DEMOLITION PLAN - PLUMBING DEMOLITION
1/8" = 1'-0"

NO WORK THIS PORTION OF BUILDING

PROJECT:
**RENOVATIONS TO
 PALMERTON HIGH
 SCHOOL WEIGHT ROOM**

3525 FIRELINE ROAD
 PALMERTON, PA 18071

OWNER:
**PALMERTON AREA
 SCHOOL DISTRICT**

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:

ARCHITECT:
 ALLOYS
 ARCHITECTURE


CIVIL:
 KEYSTONE CONSULTING
 ENGINEERS, INC.

MEPE:
 SNYDER HOFFMAN
 ASSOCIATES, INC.

SUBMISSIONS:


NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION:

ALLOY5
 ARCHITECTURE
 530 WEST BROAD ST BETHLEHEM, PA 18018
 610.419.4055





SHEET TITLE:

**FLOOR PLANS -
 PLUMBING**



DATE:	02/16/24
SCALE:	As Indicated
DRAWN BY:	KP
CHECKED BY:	KJF
PROJ NO:	22-0073

P1.01




GENERAL NOTES - PLUMBING
 1. P.C. SHALL COORDINATE GAS PIPE ROUTING AND SIZE WITH H.C.

NO.	ISSUE DESCRIPTION	DATE
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24



1 ENLARGED FLOOR PLAN - DRAINAGE & VENT PIPING
1/4" = 1'-0"



2 ENLARGED FLOOR PLAN - SUPPLY PIPING
1/4" = 1'-0"

DRAWING NOTES - PLUMBING

- 1 PROVIDE CIRCUIT SETTER VALVE, CHECK VALVE AND BALL SHUTOFF VALVE ABOVE CEILING IN ACCESSIBLE LOCATION.
- 2 PROVIDE MANUAL BALANCE VALVE, CHECK VALVE AND BALL SHUTOFF VALVE ABOVE CEILING IN ACCESSIBLE LOCATION.


NEW GAS FIRED WATER HEATER - REFER TO DETAIL FOR MORE INFORMATION

1-1/4" UP FROM BG w/ SHUTOFF VALVE TO WATTS 1-1/4" LF007-QT-S BFP OR APPROVED EQUAL

CONNECT NEW 1-1/4" DOMESTIC WATER PIPING BELOW GRADE TO EXISTING DOMESTIC WATER PIPING LEFT FROM DEMOLITION WORK. ROUTE NEW PIPING BELOW FROST DEPTH INTO UTILITY ROOM AS SHOWN. COORDINATE ROUTING WITH ALL OTHER TRADES

Ex. 1 1/4" C (E.T.R.)


NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24



GAS PRESSURE REGULATOR SCHEDULE							
TAG	MANUF.	CHARACTERISTICS	EQUIPMENT SERVED (CONNECTED GAS LOAD)	INLET PRESSURE (PSI)	SET PRESSURE (NOTE 1)	OUTLET PRESSURE (NOTE 1 & NOTE 7)	TOTAL REQUIRED CAPACITY (NOTE 6 & NOTE 7)
GPRV-1	Fisher Controls, Pietro Fiorentini, or Approved Equal	Vented Internal Relief Weatherproof	DWH (200 CFH)	2 PSI	10 IN. W.C.	7 IN. W.C. - 11 IN. W.C.	200 CFH @ 1 PSI INLET (NOTE 6)

GENERAL NOTES


- CONTRACTOR SHALL FIELD VERIFY SET PRESSURE WITH FINAL EQUIPMENT SUBMITTALS PRIOR TO ORDER/INSTALLATION.
- PIPE REGULATOR RELIEF VENT FULL SIZE OR LARGER TO BUILDING EXTERIOR AT SAFE LOCATION. COORDINATE EXACT LOCATION WITH ARCHITECT IN FIELD.
- ALL MP REGULATORS SHALL BE INSTALLED IN ACCORDANCE WITH IFGC AND SHALL BE RATED TO MAINTAIN REDUCED PRESSURE DURING LOCKUP "NO FLOW" CONDITIONS.
- ALL REGULATORS IN 2PSI SYSTEMS SHALL BE ANSI Z21.18/CSA6.3 APPROVED AND TAGGED FOR MINIMUM 5PSI MAXIMUM ALLOWABLE OPERATING PRESSURE. ALL REGULATORS WITH INLET PRESSURE GREATER THAN 2 PSI OR SHALL BE PROVIDED WITH OVERPRESSURE PROTECTION AND INTERNAL RELIEF VALVE.
- ALL REGULATORS SHALL BE CLEARLY TAGGED WITH THE FOLLOWING INFORMATION: FULL MODEL NUMBER INDICATING ORIFICE SIZE, FIELD VERIFIED SET PRESSURE, SPRING NUMBER AND SPRING ADJUSTMENT RANGE, RATED INLET AND OUTLET PRESSURE.
- ALL 2PSI SYSTEM PIPING IS SIZED FOR MAXIMUM 1PSI LOSS FROM SOURCE TO LINE PRESSURE REGULATOR. ALL REGULATORS NOTED ABOVE TO REDUCE FROM 2PSI TO IN. W.C. MUST BE SIZED TO THE NOTED CAPACITY WITH 1PSI INLET PRESSURE.
- ALL REGULATORS SHALL BE SIZED TO MAINTAIN OUTLET PRESSURE WITHIN THE SPECIFIED OUTLET PRESSURE RANGE AT FULL REQUIRED FLOW CAPACITY NOTED ON SCHEDULE. (OR MAXIMUM 20% DROOP WHERE OUTLET PRESSURE RANGE IS NOT INDICATED).
- ALL REGULATORS NOTED TO BE WEATHERPROOF SHALL BE CONSTRUCTED OF CORROSION RESISTANT MATERIALS AND VENTED IN ACCORDANCE WITH MANUFACTURERS REQUIREMENTS FOR EXTERIOR INSTALLATION INCLUDING VENTING AND VENT TERMINATION FITTINGS AND SCREENING.



RECIRCULATING PUMP SCHEDULE						
TAG	MANUF.	MODEL	LOCATION	FLOW	PERFORMANCE	CONST.
RCP-1	Armstrong	ASTRO 22855-7A	STORAGE A106a	75 W	2.0 gpm @ 8.0 ft	Lead Free Bronze


- NOTES:**
- PROVIDE ALL RECIRCULATION PUMPS WITH PROGRAMMABLE TIMER, AQUASTAT, AND FLANGE KITS.
 - ALL POWER WIRING BY E.C.

Domestic Hot Water Recirculating Pump Installation Detail
 Scale: None



Mop Receptor and Accessories Detail
 Scale: None

Gas Pressure Regulator Schedule
 Scale: None




EQUIPMENT SPECIFICATIONS: (REFER TO DIV. 22 SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS)

DWH-1 BRADFORD-WHITE MODEL# EF-100T-109E-3NA (ASME)
 100 GALLON STORAGE CAPACITY, 199.999 BTU/HR INPUT, 245 GPH RECOVERY AT 100' RISE, ASME CONSTRUCTION

MMV-1 POWERS SH-1432-1-1, SINGLE HULL MASTER MIXING VALVE TO SUPPLY 27 GPM @ 10PSI PRESSURE DROP, OUTLET TEMPERATURE SETPOINT TO 120°F.


ET-1 AMTRON ST-12-C THERMAL EXPANSION TANK, 4.7 GAL. CAP, ASME CONSTRUCTION

Domestic Water Heater Installation Detail (Commercial High Efficiency - Natural Gas Fired)
 Scale: None



- MINIMUM 12" EXACT DEPTH TO BE DETERMINED BY ARCHITECT / ENGINEER IN FIELD BASED ON EXISTING UNSUITABLE SUB-SOIL CONDITION.
 - IT IS THE INTENT THAT THE MATERIALS EXCAVATED FROM THE TRENCHES IS NOT TO BE USED FOR TRENCH BACKFILL. REFER TO DETAILS ABOVE FOR APPROVED BACKFILL MATERIALS. RAW EXCAVATED MATERIALS MUST BE DISPOSED OF PROPERLY OFF SITE BY THIS CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER.
- *WITHIN ROAD RIGHT-OF-WAYS, SURFACE RESTORATION, BACKFILL MATERIALS, AND METHODS SHALL MEET THE APPROPRIATE MUNICIPAL OR PENN-DOT REQUIREMENTS.

Typical Pipe Trench Details
 Scale: None




Typical Piping Support Details
 Scale: None




DATE:	02/16/24
SCALE:	
DRAWN BY:	KP
CHECKED BY:	KJF
PROJ NO:	22-0073


NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24




Typical Clevis Hanger Detail
Scale: None



Pipe Sleeve Through Wall Detail
Scale: None




Typical Double Check Backflow Preventer Installation Detail
Scale: None




Vent Thru Roof Detail
Scale: None

NOTES:


1. FLASHING AND SEALING OF NEW VTR PENETRATIONS WITHIN EXISTING ROOF CONSTRUCTION SHALL BE PROVIDED BY THE P.C. AND SHALL BE PERFORMED IN ACCORDANCE WITH ALL REQUIREMENTS OF THE EXISTING ROOF MANUFACTURER TO MAINTAIN ANY EXISTING ROOF WARRANTY. COORDINATE ALL REQUIREMENTS WITH OWNER AND EXISTING ROOF MANUFACTURER IN FIELD.





Typical No-Hub Cast Iron Above Slab to PVC Below Slab Transition
Scale: None



Typical Floor Cleanout Detail
Scale: None



Typical Floor Drain Detail
Scale: None



DATE:	02/16/24
SCALE:	
DRAWN BY:	KP
CHECKED BY:	KJF
PROJ NO:	22-0073

P3.02

PART 1.00 GENERAL

1.01 WORK INCLUDED

- A. FURNISHING OF ALL LABOR, MATERIALS, TOOLS TRANSPORTATION, SERVICES, ETC., NECESSARY TO COMPLETE THE INSTALLATION OF THE PLUMBING SYSTEM AND AS DESCRIBED IN THESE SPECIFICATIONS, AS ILLUSTRATED ON THE ACCOMPANYING DRAWINGS OR AS DIRECTED BY THE ARCHITECT, WORK IS COMPRISED OF BUT NOT LIMITED TO THE FOLLOWING PRINCIPAL ITEMS:
 1. SELECT DEMOLITION OF EXISTING PLUMBING SYSTEMS AS DETAILED ON DRAWINGS AND AS NECESSARY FOR INSTALLATION OF ALL NEW WORK INCLUDING WORK PERFORMED BY OTHER TRADES.
 2. ALL HOT AND COLD WATER SYSTEMS WITH COMPLETE CONNECTIONS AS DETAILED ON CONTRACT DOCUMENTS TO ALL PLUMBING FIXTURES AND EQUIPMENT REQUIRING THE WATER CONNECTIONS. THESE SYSTEMS WILL BE COMPLETE WITH CONTROLS, VALVES, EQUIPMENT, DEVICES AND INSULATION.
 3. ALL SOIL, WASTE, AND VENT INSIDE THE BUILDING AS REQUIRED TO CONNECT TO NEW FIXTURES.
 4. FURNISHING AND SETTING OF PLUMBING FIXTURES, INCLUDING ALL THE REQUIRED TRIM, SUPPORTS AND DEVICES.
 5. FURNISHING OF ALL FINAL PLUMBING CONNECTIONS TO SPACE HEATING AND AIR CONDITIONING EQUIPMENT INCLUDING CONDENSATE DRAINS.

1.02 SUBMITTALS:

- A. SHOP DRAWINGS:
WITHIN 35 DAYS AFTER AWARD OF CONTRACT AND BEFORE ANY PLUMBING MATERIALS ARE DELIVERED TO THE JOBSITE. SUBMIT TO THE ARCHITECT COMPLETE SHOP DRAWINGS, INCLUDING ALL PLUMBING FIXTURES, TRIM, DRAINS, CLEANOUTS, PIPING, VALVES, INSULATION, HANGERS, SUPPORTS, EQUIPMENT, AND DEVICES PROPOSED TO THE FURNISHED AND INSTALLED.
- B. RECORD DRAWINGS:
DURING THE PROGRESS OF THE WORK, MAINTAIN AN ACCURATE RECORD OF ALL CHANGES MADE IN THE PLUMBING SYSTEM. THE RECORD SHALL SHOW CHANGES IN MANUFACTURER (WITH NUMBERS AND TRADE NAMES), MATERIALS, SIZE, LOCATIONS, AND HOOK-UP POINTS.

1.03 PRODUCT HANDLING

- A. PROTECTION:
USE ALL MEANS NECESSARY TO PROTECT PLUMBING MATERIALS BEFORE, DURING AND AFTER INSTALLATION AND TO PROTECT THE INSTALLED WORK AND MATERIALS OF ALL OTHER TRADES.
- B. REPLACEMENTS:
IN THE EVENT OF DAMAGE, IMMEDIATELY MAKE ALL REPAIRS AND REPLACEMENTS NECESSARY TO THE APPROVAL OF THE ARCHITECT AND AT NO ADDITIONAL COST TO THE OWNER.

1.04 EXAMINATION OF THE SITE:

ALL CONTRACTORS SUBMITTING PROPOSALS FOR THIS WORK SHALL FIRST EXAMINE THE SITE AND ALL CONDITIONS THEREIN AND/OR THEREIN ALL PROPOSALS SHALL HAVE TAKE INTO CONSIDERATION ALL CONDITIONS THAT MAY AFFECT THE WORK UNDER THIS CONTRACT LACK OF THE INFORMATION WILL NOT BE CONSIDERED AS JUSTIFICATION FOR EXTRA COST OR ALLOWANCES TO THE CONTRACT PRICE. DRAWING NOTES MAY REFERENCE WORK NOT EXPLICITLY DETAILED ON PLANS, REVIEW OF SITE AND SITE CONDITIONS WILL BE REQUIRED TO DETERMINE THE REQUIRED SCOPE OF WORK INVOLVED. NON SELECTIVE DEMOLITION WILL BEGIN PRIOR TO BIDDING AND MAY CLARIFY OMISSIONS OR UNFORESEEN CONDITIONS NOT DETAILED ON DRAWINGS.

1.05 COMPLIANCES WITH CODES AND PERMITS:

COMPLY WITH ALL APPLICABLE CODES, ORDINANCES, SAFETY ORDERS AND REQUIREMENTS OF THE LOCAL AUTHORITIES HAVING JURISDICTION. CONTRACTOR SHALL PAY ALL FEES MISCELLANEOUS COSTS AND SHALL OBTAIN ALL PERMITS NECESSARY TO CARRY ON THE WORK, BEFORE FINAL ACCEPTANCE OF THE WORK. FURNISH TO THE OWNER CERTIFICATES OF INSPECTIONS STATING THAT THE BUILDING DEPARTMENT HAS INSPECTED THE WORK.

1.06 GUARANTEE:

THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL WORK UNDER THIS SECTION AND SHALL ADJUST ALL VALVES, CONTROLS, VACUUM BREAKERS AND INCIDENTAL ITEMS AND SHALL LEAVE THE SYSTEM IN PERFECT OPERATING CONDITION. HE SHALL REGULATE, REPAIR AND REPLACE AT HIS OWN EXPENSE ANY DEFECTIVE WORKMANSHIP, MATERIALS, AND EQUIPMENT, WHICH MAY BECOME APPARENT WITHIN ONE YEAR AFTER THE DATE OF FINAL ACCEPTANCE OF THE WORK. THE DECISION OF THE OWNER SHALL BE FINAL IN RESPECT TO IMPERFECTIONS. THE CONTRACTOR SHALL FURNISH THE OWNER ALL MANUFACTURERS WRITTEN GUARANTEES OF MATERIALS AND EQUIPMENT, INCLUDING WATER HEATER WARRANTY REQUIREMENTS AND WATER STERILIZATION REPORT.

PART 2.00 PRODUCTS:

2.01 PIPE:

- A. SOIL, WASTE AND VENT PIPING:
 1. SOIL, WASTE, AND VENT PIPING ABOVE SLAB SHALL BE SERVICE WEIGHT CAST IRON "NO-HUB" PIPE (CISPI) AND HEAVY DUTY FITTINGS WITH NEOPRENE SLEEVE GASKETS WITH STAINLESS STEEL BANDS. GALVANIZED STEEL PIPING MAY BE USED FOR VENT PIPING 2 1/2" AND SMALLER.
 2. SOIL, WASTE, AND VENT PIPING BELOW SLAB SHALL BE SCHEDULE 40 PVC WITH SOLVENT CEMENT FITTINGS. ALL TRENCHING AND BEDDING SHALL BE PERFORMED IN ACCORDANCE WITH REQUIREMENTS OF LOCAL AUTHORITY HAVING JURISDICTION.
- B. INDIRECT AND CONDENSATE DRAIN LINES:
 1. SHALL BE TYPE DWV COPPER PIPING WITH WROUGHT COPPER DRAINAGE PATTERN FITTINGS AND 95-5 SILVER SOLDER JOINT.
- C. WATER PIPING ABOVE SLAB:
 1. WATER PIPING SHALL BE TYPE "L", HARD DRAWN COPPER TUBING WITH SOLDER JOINT FITTINGS. ALL MATERIALS USE IN THE POTABLE WATER PIPING SYSTEM SHALL MEET THE "LEAD FREE" REQUIREMENTS OF THE SAFE DRINKING WATER ACT".

2.02 VALVES

- A. WATER SERVICE

ALL SHUTOFF VALVES IN WATER SERVICE SHALL BE FULL PORT BALL VALVES UNLESS OTHERWISE INDICATED ON THE DRAWINGS. ALL MATERIALS USE IN THE POTABLE WATER PIPING SYSTEM SHALL MEET THE "LEAD FREE" REQUIREMENTS OF THE SAFE DRINKING WATER ACT".

 1. BALL VALVES - 150 PSI SWP, 600 PSI CWP, 2-PIECE CAST BRONZE BODY, TFE SEATS, CHROME PLATED BALL, FULL PORT, BLOWOUT PROOF STEM, SOLDERED END CONNECTIONS.
 - NIBCO #S585-70 OR APPROVED EQUAL.
 2. CHECK VALVES - CLASS 125, Y-PATTERN BRONZE BODY, TFE DISC SEATS, SOLDERED END CONNECTIONS.
 - NIBCO #S413-Y OR APPROVED EQUAL.

2.03 PIPE SLEEVE AND ESCUTCHEONS:

- A. ALL PIPE SLEEVES AND ESCUTCHEONS SHALL BE "ADJUSTO-CRETE" OR EQUAL. SLEEVES APPROVED IN ADVANCE BY THE ARCHITECT WITH AMPLE CLEARANCE FOR PIPE AND COVERING AND WITH CHROME PLATED WALL AND FLOOR ESCUTCHEONS OVER PIPE IN ALL FINISHED AREAS.

2.04 HANGERS AND SUPPORTS:

- A. SOIL, WASTE, AND VENT PIPING ON HORIZONTAL LINES, SHALL BE FEE AND MASON #215 ADJUSTABLE RING HANGERS, SPACED NOT MORE THAN FIVE FEET APART. WATER PIPING SHALL BE FEE AND MASON #212 SPLIT RING HANGERS WITH SUPPORTING RODS, SPACED NOT MORE THAN TEN FEET APART FOR 1 1/2" PIPE AND LARGER, AND SIX FEET APART FOR 1 1/4" PIPE AND SMALLER.

2.05 CLEANOUTS

- A. SHALL BE MANUFACTURED BY J.R. SMITH, ZURN OR JOSAM. SEE PLUMBING DRAWINGS FOR DETAILS.

2.06 PLUMBING FIXTURES

- A. AS INDICATED ON DRAWINGS

2.07 INSULATION:

- A. ALL HOT, COLD, RETURN WATER SUPPLY PIPING, ALL SIZES UP TO AND INCLUDING 2" (UNLESS OTHERWISE NOTED ON PLANS) SHALL BE INSULATED WITH 1" THICK, MINERAL FIBER INSULATION WITH ALL SERVICE JACKET. VAPOR RETARDING JACKET REQUIRED ON ALL COLD WATER PIPING. CERTAINTEED MANSION, OWENS-CORNING FIBERGLAS CORP., OR APPROVED EQUAL.
- B. ALL INDIRECT AND CONDENSATE DRAIN LINES SHALL BE INSULATED WITH CLOSED-CELL, SPONGE- OR EXPANDED-RUBBER MATERIALS. COMPLY WITH ASTM C 534, TYPE I FOR TUBULAR MATERIALS AND TYPE II FOR SHEET MATERIALS. 3/8" THICK. ARMSTRONG WORLD INDUSTRIES, INC., RUBATEX CORP., OR APPROVED EQUAL.

PART 3.00 EXECUTION

3.01 INSTALLATION

- A. ALL PIPING SHALL RUN CONCEALED EXCEPT WHERE SHOWN OTHERWISE ON DRAWINGS. WHERE PIPING IS RUN EXPOSED IT SHALL BE PLACED IN UNIMPORTANT AND OUT-OF-THE-WAY PLACES, AN APPROVED BY THE ARCHITECT AND PAINTED WITH COLOR APPROVED BY ARCHITECT.
- B. VALVES, TRAPS, CLEANOUTS, AND OTHER APPARATUS SHALL BE INSTALLED IN AN EASILY ACCESSIBLE LOCATION.
- C. SOIL, WASTE, VENT OFFSETS AND HOUSE DRAINS SHALL BE INSTALLED WITH A MINIMUM UNIFORM GRADE OF 1/4" TO THE FOOT UNLESS INDICATED OTHERWISE.
- D. ALL WATER PIPES SHALL HAVE A MINIMUM CLEARANCE OF 1/2" AND SHALL BE ELECTRICALLY ISOLATED FROM BUILDING STRUCTURE AND OTHER PIPING.
- E. HOT AND COLD WATER LINES SHALL BE AT LEAST 6" APART WHERE PIPING IS PARALLEL.
- F. PIPE ISOLATORS SHALL BE INSTALLED ON ALL WATER PIPING AT RING HANGERS.
- G. ISOLATION FITTING SHALL BE INSTALLED AT ALL JOINTS WHERE COPPER OR BRASS PIPE OR TUBING JOINS FERROUS PIPE, FITTINGS OR EQUIPMENT.
- H. ACCESS PANELS: PROVIDE AND INSTALL ACCESS PANEL OVER ALL EQUIPMENT BUILT INTO WALLS, FLOORS OR CEILINGS SUCH AS VALVES, CLEANOUTS, ETC. VERIFY LOCATION OF PANELS IN FIELD WITH ARCHITECT PRIOR TO ROUGH-IN. ALL SHALL BE OF A SIZE SUITABLE FOR THE SERVICE INTENDED. VERIFY BEFORE START OF ANY WORK TO INSURE THAT NEITHER EQUIPMENT NOR FIXTURES WILL GET IN THE WAY OF THE ACCESS PANELS AFTER COMPLETION.
- I. CLEANOUTS:
 1. CLEANOUTS SHALL BE INSTALLED AT ALL CHANGES IN DIRECTION EXCEEDING 45°, UPPER TERMINALS NOT OVER 100 FEET APART IN ANY RUN, AS SHOWN ON DRAWINGS, AND WHERE REQUIRED BY IPC2018 AND LOCAL PLUMBING ORDINANCES.
 2. EACH CLEANOUT SHALL BE FULLY ACCESSIBLE AND SO INSTALLED AS TO SERVE PURPOSE FOR WHICH IT WAS INTENDED.
- J. ALL FIXTURES SHALL BE SECURELY ATTACHED TO SUPPORTING SURFACES AS SPECIFIED AND SHALL BE INSTALLED PLUMB, LEVEL, WALL HUNG FIXTURES SHALL BE SECURELY ATTACHED TO WOOD BLOCKING SECURELY FRAMED IN.
- K. PROTECTION: PROVIDE ADEQUATE PROTECTION FOR ALL EQUIPMENT AND FIXTURES AND LEAVE WORK IN A NEAT CLEAN CONDITION READY FOR USE AND OPERATION ACCEPTABLE TO THE ARCHITECT.
- J. CUTTING AND PATCHING: THE CONTRACTOR SHALL DO ALL CUTTING AND PATCHING AND SHALL PROVIDE ALL OPENING TOGETHER WITH LINTELS AND SUPPORTS WHICH MAY BE REQUIRED FOR THE INSTALLATION OF THE WORK UNDER THIS SECTION OF SPECIFICATIONS. PATCHING SHALL BE OF THE SAME MATERIALS, WORKMANSHIP AND FINISH AS AND SHALL ACCURATELY MATCH ALL SURROUNDING CONSTRUCTION.
- K. INSULATION: PIPING INSULATION SHALL BE INSTALLED OR APPLIED PER THE MANUFACTURERS WRITTEN INSTRUCTIONS.

3.02 PLUMBING FIXTURES

- A. SEE DRAWING FOR PLUMBING FIXTURE SPECIFICATIONS AND MANUFACTURERS. FURNISH AND INSTALL ALL SUPPORTS NECESSARY FOR THE REQUIRED FIXTURES. PLUMBING FIXTURES SHALL NOT UNDER ANY CIRCUMSTANCES BE SUPPORTED BY PLUMBING CONNECTIONS. ALL LIKE PLUMBING FIXTURES SHALL BE OF ONE MANUFACTURER EXCEPT WHERE CHANGES ARE APPROVED IN WRITING BY THE ARCHITECT.
- B. ALL PLUMBING FIXTURES SHALL BE PROVIDED WITH WATER, DRAIN, AND VENT CONNECTIONS AS SHOWN ON THE DRAWINGS AND AS REQUIRED BY IPC2018 AND ANY APPLICABLE PLUMBING ORDINANCES. FIXTURE DRAINS AND FLOOR DRAINS SHALL HAVE TRAPS; FACTORY-TYPE SHOCK ABSORBERS SHALL BE USED ON HOT AND COLD WATER LINES. ALL PIPING SHALL HAVE CHROME PLATED CAST BRASS FLOOR AND WALL ESCUTCHEONS.
- C. ALL FAUCETS SHALL BE EQUIPPED WITH RENEWABLE SEATS OR CARTRIDGES. ALL EXPOSED METAL PARTS OF FIXTURES SHALL BE CHROME PLATED.
- D. THE CONTRACTOR WILL BE HELD RESPONSIBLE FOR THE PROPER PROTECTION OF ALL FIXTURES AFTER INSTALLATION UNTIL THE PROJECT IS COMPLETED AND ACCEPTED.

3.03 CONNECTIONS TO EQUIPMENT FURNISHED AND INSTALLED BY OTHERS:

- A. PLUMBING CONNECTIONS TO SPACE HEATING AND AIR CONDITIONING EQUIPMENT
 1. MAKE-UP WATER CONNECTIONS.
 2. CONDENSATE DRAINS

3.04 TESTING:

- ALL WORK SHALL BE TESTED UNDER THE SUPERVISION OF THE REPRESENTATIVE OF THE ARCHITECT AND SHALL BE INSPECTED BY ALL AUTHORITIES HAVING JURISDICTION OVER THIS WORK.
- A. TEST SHALL BE MADE ON THE VARIOUS PARTS OF THE SYSTEMS AS REQUIRED BY GOVERNING AUTHORITIES AND SHALL BE PAID FOR BY THIS CONTRACTOR.
 - B. MINIMUM TEST REQUIRED SHALL BE: PRESSURE TESTS: TURN OVER ALL TEST CHARTS TO OWNERS REPRESENTATIVE
 1. SYSTEM TESTED GAUGE PRESSURE AT START OF TEST, THE GAUGE PRESSURE AFTER 4HRS. WATER PIPING: START 125 POUNDS, 110 POUNDS MINIMUM AFTER TIME PERIOD.
 2. FUEL GAS: STARTING 75 PSI, 70 PSI MINIMUM AFTER TIME PERIOD OF 4 HRS.
 3. SEWER, WASTE AND VENT PIPING: TEST IN ACCORDANCE WITH IPC2018. MAINTAIN RECORD OF EACH TEST.
 - C. OPERATING TEST:
 1. TEST SHALL BE PERFORMED BEFORE THE FINAL ACCEPTANCE AND UNDER THE SUPERVISION OF THE ARCHITECT AND/OR OWNER/OPERATOR OF THE TESTS SHALL BE EIGHT (8) HOURS. THE CONTRACTOR SHALL FURNISH ALL LABOR AND INSTRUMENTS FOR THE TESTS.
 2. TEST SHALL DEMONSTRATE THAT THERE IS FREE AND EQUAL CIRCULATION FROM EACH PART OF THE PIPING SYSTEMS AS WELL AS SATISFACTORY OPERATION OF ALL VALVES, PUMPS, EQUIPMENT, AUTOMATION CONTROLS, ETC.
 - D. SHOULD THE CONTRACTOR REFUSE OR NEGLECT TO MAKE ANY TESTS NECESSARY TO SATISFY THE OWNER OR HIS REPRESENTATIVE THAT HE HAS CARRIED OUT THE TRUE INTENT AND MEANING OF THE SPECIFICATIONS. THE OWNER MAY MAKE SUCH TESTS AND CHARGE THE EXPENSE THERE OF TO THE CONTRACTOR.

3.05 CLEANING PIPING SYSTEMS:

AFTER THE PIPING SYSTEMS HAVE BEEN TESTED AND PROVED TIGHT, THE CONTRACTOR SHALL CLEAN THE VARIOUS SYSTEMS, INCLUDING STRAINERS OF DIRT, SCALE, OIL, GREASE, WASTE AND OTHER FOREIGN SUBSTANCES, WHICH MAY HAVE ACCUMULATED DURING THE PROCESS OF INSTALLATION. THE ENTIRE WASTE SYSTEM FROM FLOOR DRAINS AND FLOOR SINKS SHALL BE CLEANED WITH A MECHANICAL SNAKE ROOTER TO INSURE CLEAN FREE-FLOWING WASTE LINES. ALL CHROME-PLATED PARTS AND PIPE SHALL BE POLISHED IN GENERAL SYSTEM SHALL BE LEFT IN A CLEAN, NEAT AND USABLE CONDITION.

3.06 WATER SYSTEM STERILIZATION:

BEFORE ANY USE OF SYSTEM IS MADE FOR DOMESTIC PURPOSES, IT SHALL BE STERILIZED BY SLOWLY FILLING WITH WATER TO WHICH A STERILIZING AGENT HAS BEEN APPLIED. AT A RATE GIVING 50 PPM OF CHLORINE, AS DETERMINED BY RESIDUAL CHLORINE TEST AT EXTREMITIES OF THE LINE. AFTER LINES HAVE BEEN FILLED FOR A PERIOD OF THREE (3) HOURS. TESTS FOR RESIDUAL CHLORINE SHALL SHOW NOT LESS THE 50 PPM. IF LESS THAT 50 PPM IS INDICATED. DRAIN OR FLUSH OUT THE LINE AND REPEAT STRIATION TREATMENT UNIT TEST INDICATE AT LEAST 50 PPM OF RESIDUAL CHLORINE AFTER THREE (3) HOURS. THE LINES SHALL THEN BE FLUSHED OUT UNTIL ALL TRACES OF CHEMICAL HAVE BEEN REMOVED.

3.07 GROUTING:

GROUT BEHIND ALL WALL HUNG PLUMBING FIXTURES WITH HARD, WHITE DURABLE PLASTER MATERIALS, ELIMINATING ALL VOIDS AND CRACKS AND PROVIDING SUFFICIENT PLANE-BEARING SURFACE FOR MOUNTING.

3.09 ADJUSTING:

UPON COMPLETION OF SYSTEM AND AFTER CLEANING OF EQUIPMENT. AUTOMATIC PARTS OF PLUMBING SYSTEMS SHALL BE CAREFULLY ADJUSTED FOR NORMAL OPERATION.

PLUMBING FIXTURE LIST					
*****Note: Refer to Specification Sections 22 1006 and 22 4000 for complete fixture specifications.*****					
FIXTURE TAG	FIXTURE DESCRIPTION	FIXTURE SPECIFICATIONS	DRAIN ROUGH IN CONNECTION	WATER ROUGH IN CONNECTION	
				HOT	COLD
EW-C1	Electric Water Cooler with Bottle Filler Surface Mounted	Electric Water Cooler with Bottle Filler, Single-Level, Filtered - 18ga 304 Stainless Steel body panels - Elevated anti-squirt bubbler with flexible mouth guard - Bottle filler mounted in ABS alcove above lower bowl w/sensor operation and Green Ticker - Cane Touch Skirt (where required for compliance with ANSI A117.1) Basis of Design: Elkay Model: LZS8WSSP	1-1/2"	----	1/2"
EW-C2	Electric Water Cooler with Bottle Filler Bi-Level Surface Mounted	Electric Water Cooler with Bottle Filler, Bi-Level, Filtered - 18ga 304 Stainless Steel body panels - Elevated anti-squirt bubbler with flexible mouth guard - Bottle filler mounted in ABS alcove above lower bowl w/sensor operation and Green Ticker - Cane Touch Skirt (where required for compliance with ANSI A117.1) Basis of Design: Elkay Model: LZSTLWSSP	1-1/2"	----	1/2"
FCO-1	Floor Cleanout	Floor Cleanout - Cast iron body with flashing clamp - Twist to floor adjustable Nickel Bronze top - Cover type coordinated with floor finish Basis of design: J.R. Smith Model 4020	Refer to Plans	----	----
FD-1	Floor Drain General Purpose	Floor Drain - Cast iron body with flashing clamp - 5" Nickel Bronze strainer - Deep Seal P-Trap w/ProSet Trap Guard seal protection. Basis of design: J.R. Smith Model 2005-NB	Refer to Plans	----	----
FD-2	Floor Drain Storage Rooms Mechanical Rooms	Floor Drain - Cast iron body with flashing clamp - 7" Nickel Bronze strainer - Deep Seal P-Trap w/ProSet Trap Guard seal protection. Basis of design: J.R. Smith Model 2350-MBG	Refer to Plans	----	----
NFWH	Hose Bibb	Hose bibb/wall hydrant - Chrome plated, Half turn operation w/interchangeable Wheel handle/Loose Key operation - Anti-Siphon Vacuum Breaker (ASSE 1011 compliant) Basis of design: 55519-WC-CL-NB (verify wall thickness in field)	----	-----	1/2"
LAV-1	Lavatory (Toilet Rooms)	Basin: - Wall hung, Vitreous China, ADA/ANSI A117.1 compliant - White Basis of Design: American Standard: Lucerne 0355.012 Faucet: - Chrome Plated Cast Brass, Lever handle, Manual faucet, 0.5 gpm Vandal Resistant aerator. Basis of Design: Moen Commercial: 8215F05 Accessories: - Floor mounted concealed arm carrier - Below deck ASSE-1070 compliant mixing valve - Truebro Lav Guard supply and drain insulating covers. - Chrome plated, Lead Free, Commercial grade, quarter turn Loose Key Angle Stops - Chrome plated copper supplies - In wall carrier	1-1/2"	1/2"	1/2"
MR-1	Mop Receptor with Utility Faucet	Base: - 32"x32"x12"H, Terazzo mop receptor basin - Basis of Design: Acorn TNC-32 Faucet: - Chrome plated, wall mounted utility faucet w/Integral Vacuum Breaker, integral check stops, 3/4 GHT outlet, Wrist blade handles, Wall brace, and pail hook. - Basis of Design: Moen Commercial, Model 8124 Accessories: - Quick connect drain fitting, (3) bracket Mop Hanger, 30" hose and hose bracket - Stainless Steel wall guards - Refer to detail for additional information.	3"	1/2"	1/2"
SH-1	Shower (Team Rooms)	Shower: - By G.C. Drain: Provide FD-1 w/ Sediment Bucket Option Controls: - Pressure Balancing Thermostatic Valve - ASSE 1016T/P, manual lever control - Low flow 1.5 gpm shower head Basis of design: Powers Controls: Hydropanel II Model 450-7101	2"	1/2"	1/2"
SH-1A	Shower (Team Rooms ADA)	Shower: - By G.C. Drain: Provide FD-1 w/ Sediment Bucket Option Controls: - Pressure Balancing Thermostatic Valve - ASSE 1016T/P, manual lever control - Low flow 1.5 gpm shower head Basis of design: Powers Controls: Hydropanel II Model 450-7108 w/following options: ES-P-141-150 Low Flow Handshower with non-positive shutoff device, 141804A quick disconnect coupling, and 141161D Wall hook	2"	1/2"	1/2"
UR-1	Urinal Wall Hung (Toilet Rooms)	Bowl: - Wall Hung, Vitreous China - Concealed floor mounted carrier Basis of Design: American Standard Inc; Model: Washbrook 6590.001EC Flush Valve: - 0.5 gpf - Exposed Chrome Plated Brass w/integral angle stop - Manual Operated, 0.5 gpf, Exposed chrome plated cast brass Basis of design: Sloan Valve Company; Model: Royal 186-0.5	2"	----	3/4"
WC-1	Water Closet Floor Mount (Toilet Rooms)	Bowl: - Elongated, Floor mounted, Floor outlet, Tank Type with Locking Lid - ASME A112.19 compliant - Vitreous China, white w/eveclean antimicrobial finish Basis of Design: American Standard: Cadet 2462016.020 Seat: Plastic Open Front Seat, white, with self sustaining check hinge	4"	----	1/2"
WC-1A	Water Closet Floor Mount (Toilet Rooms)	Bowl: - Elongated, Floor mounted, Floor outlet, Tank Type with Locking Lid - ICC/ANSI A117.1 & ASME A112.19 compliant - Vitreous China, white w/eveclean antimicrobial finish Basis of Design: American Standard: Cadet 2467016.020 Seat: Plastic Open Front Seat, white, with self sustaining check hinge	4"	----	1/2"

- NOTES:**
1. P.C. shall coordinate all "Accessible" fixture locations with Architectural plans prior to rough in.
 2. Refer to Architectural drawings for all fixture mounting heights.
 3. At all "Accessible" water closet compartments, installation of flush controls shall comply with ANSI 117.1.
 4. Provide deep seal trap and Proset Trapguard trap seal protection in all floor drains. Refer to plans for outlet size/trap size.

PROJECT: RENOVATIONS TO PALMERTON HIGH SCHOOL WEIGHT ROOM

3525 FIRELINE ROAD
PALMERTON, PA 18071

OWNER: PALMERTON AREA SCHOOL DISTRICT

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:

ARCHITECT:
ALLOYS ARCHITECTURE

CIVIL:
KEYSTONE CONSULTING ENGINEERS, INC.

MEPE:
SNYDER HOFFMAN ASSOCIATES, INC.


SUBMISSIONS:

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION: ALLOY5 ARCHITECTURE
530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055



SHEET TITLE: SPECIFICATIONS - PLUMBING

DATE: 02/16/24

SCALE:


DRAWN BY: KP

CHECKED BY: KJF

PROJ NO: 22-0073

P4.01

Table with 3 columns: NO., ISSUE DESCRIPTION, DATE. Rows include 100% DD REVIEW (01/12/24), 100% CD REVIEW (02/09/24), and BID SET (02/16/24).



ELECTRICAL GENERAL NOTES

Table of electrical general notes with 2 columns: Note number and description. Includes notes on wire sizes, lighting layout, GFI receptacles, E.C. coordination, and mounting heights.

OCCUPANCY SENSOR SCHEDULE

Table with 6 columns: SYMBOL, MANUFACTURER, MODEL #, COVERAGE AREA SQ. FT., SENSOR TYPE, ADDITIONAL REMARKS. Lists various occupancy sensor models and their specifications.

NOTES: DISABLE SMART SET TECHNOLOGY IN ALL SPACES. **CONTRACTOR SHALL VERIFY LOCATIONS OF ALL OCCUPANCY SENSORS WITH MANUFACTURER PRIOR TO ROUGH-IN**

EQUIPMENT TAG LEGEND

Table of equipment tag legend with 2 columns: Tag symbol and description. Includes tags for air-cooled chillers, condensers, fans, pumps, heaters, and various electrical units.


ELECTRICAL ABBREVIATIONS

Table of electrical abbreviations with 2 columns: Abbreviation and full name. Includes terms like AMPERE, ARC FAULT INTERRUPTER RECEPTACLE, ARCHITECT, and various contractor types.

ELECTRICAL LEGEND

Table of electrical legend with 2 columns: Symbol and description. Includes symbols for fire alarm stations, fire alarm devices, fire alarm bells, fire alarm pull stations, fire alarm control panels, fire alarm horns, fire alarm strobes, fire alarm speakers, fire alarm intercoms, fire alarm door strikes, fire alarm card readers, fire alarm keypads, fire alarm reset stations, fire alarm push plates, fire alarm emergency off push-buttons, fire alarm emergency killswitches, fire alarm gas solenoid valves, fire alarm security cameras, fire alarm alarm horns, fire alarm electric door strikes, fire alarm card readers, fire alarm keypads, fire alarm reset stations, fire alarm push plates, fire alarm emergency off push-buttons, fire alarm emergency killswitches, fire alarm gas solenoid valves, fire alarm security cameras, fire alarm alarm horns, fire alarm electric door strikes, fire alarm card readers, fire alarm keypads, fire alarm reset stations, fire alarm push plates, fire alarm emergency off push-buttons, fire alarm emergency killswitches, fire alarm gas solenoid valves, fire alarm security cameras.

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24




1 DEMOLITION PLAN - LEVEL 01 - ELECTRICAL
1/8" = 1'-0"

DEMOLITION NOTES

1.	UNLESS OTHERWISE INDICATED OR NOTED, ALL ELECTRICAL ITEMS SHOWN ARE TO BE REMOVED. THIS REMOVAL INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING ITEMS: LIGHTING FIXTURES, RECEPTACLES, JUNCTION BOXES, VARIOUS LOW-VOLTAGE OUTLETS AND JACKS, AND ALL OTHER ELECTRICAL ITEMS SHOWN ON THIS DRAWING. THIS INCLUDES ANY ASSOCIATED BRANCH CIRCUIT OR LOW VOLTAGE WIRING BACK TO ITS SOURCE. THE E.C. IS ALSO RESPONSIBLE FOR THE REMOVAL OF MOUNTING DEVICES, HANGERS, ETC. ASSOCIATED WITH THIS EQUIPMENT.
2.	AN ATTEMPT HAS BEEN MADE TO SHOW ALL THE LIGHTING FIXTURES, RECEPTACLES, JUNCTION BOXES, VARIOUS LOW-VOLTAGE JACKS, AND ALL OTHER ELECTRICAL ITEMS ON THE DEMOLITION DRAWINGS. HOWEVER, THE E.C. SHALL BE RESPONSIBLE FOR THE REMOVAL OF ANY AND ALL OF THESE COMPONENTS THAT EXIST IN THE FIELD AND ARE IN THE WAY OF THE NEW CONSTRUCTION.
3.	NO WIRING SHALL BE ABANDONED IN PLACE, IT SHALL BE REMOVED. ALL CONDUIT SHALL BE REMOVED EXCEPT WHERE IT IS BURIED IN MASONRY WALLS AND IN OR BELOW FLOOR SLABS. IN THESE CASES CUT THE ENDS OF THE CONDUIT FLUSH WITH THE WALL OR FLOOR AND FILL WITH PATCHING MATERIALS TO MATCH ADJACENT SURFACES.
4.	THE E.C. SHALL BE RESPONSIBLE FOR RECONNECTING ANY EXISTING DEVICE WHICH IS TO REMAIN ENERGIZED AND HAS BEEN DISCONNECTED DUE TO THE DEMOLITION. PROVIDE ALL WIRING AND DEVICES NECESSARY TO RECONNECT.

NO WORK THIS
PORTION OF
BUILDING



PROJECT:
**RENOVATIONS TO
 PALMERTON HIGH
 SCHOOL WEIGHT ROOM**

3525 FIRELINE ROAD
 PALMERTON, PA 18071

OWNER:
**PALMERTON AREA
 SCHOOL DISTRICT**

680 FOURTH STREET PALMERTON, PA 18071

PROJECT TEAM:


ARCHITECT:
 ALLOYS
 ARCHITECTURE

CIVIL: KEYSTONE CONSULTING ENGINEERS, INC.
MEPE: SNYDER HOFFMAN ASSOCIATES, INC.

SUBMISSIONS:

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

Lighting Fixture Schedule									
Type	Apparent Load	Manufacturer	Catalog Number	Mounting	Total Depth	No. of Lamps	Lamp Type	Voltage	Additional Remarks
A	44 VA	ILP	VS4-6L-U-40-FRL	SURFACE	N/A	LED	5660LU LED 4000K	UNV	STRIP LIGHT. MOUNT TIGHT TO STRUCTURE.
A1	19 VA	ILP	VS2-2L-U-50-FRL	SURFACE	N/A	LED	2501LU LED 5000K	UNV	STRIP LIGHT. MOUNT TIGHT TO STRUCTURE.
B	32 VA	ILP	VV74-4L-U-40-FRL	SURFACE	N/A	LED	4524LU LED 4000K	UNV	VAPOR TIGHT. MOUNT TIGHT TO STRUCTURE.
EM	360 VA	EVENLITE	H-6E360-2-L247-S D	WALL	N/A	(2) PAR 18	7W	UNV	EMERGENCY BATTERY PACK W/ (2) HEADS.
R	14 VA	EVENLITE	ER4X-2-L247	WALL	N/A	LED	LED	24V DC	DOUBLE REMOTE HEAD, NEMA 4X RATED.
X	3 VA	EVENLITE	AUR-1-BA-CN	UNIVERSAL	N/A	LED	LED	UNV	SINGLE FACE HYBRID EXIT SIGN. PROVIDE CHEVRONS AS INDICATED.




1 FLOOR PLAN - LEVEL 01 - LIGHTING
 1/8" = 1'-0"

GENERAL LIGHTING NOTES:

- REFER TO E0.00 FOR LEGEND AND GENERAL NOTES.
- CIRCUIT ALL EXIT SIGNS TO NEAREST AVAILABLE UN-SWITCHED LIGHTING CIRCUIT.
- NOT ALL CIRCUITING SHOWN. PROVIDE ALL REQUIRED SWITCH LEGS AND LOW-VOLTAGE WIRING AS REQUIRED FOR A FULLY FUNCTIONING LIGHTING SYSTEM.

NO WORK THIS PORTION OF BUILDING

KEY PLAN:



REGISTRATION:

ALLOY5
 ARCHITECTURE
 530 WEST BROAD ST BETHLEHEM, PA 18018
 610.419.4055



SHEET TITLE:

**FLOOR PLAN - LEVEL
 01 - LIGHTING**

DATE: 02/16/24

SCALE: As Indicated

DRAWN BY: DAN

CHECKED BY: DAN

PROJ NO: 22-0073

E1.01

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24


Branch Panel: A

Location: WEIGHT ROOM 100 Volts: 120/240 Single A.I.C. Rating: 10,000
 Supply From: Phases: 1 Mains Type: MCB
 Mounting: Surface Wires: 3 Mains Rating: 100 A
 Enclosure: Type 1 MCB Rating: 100 A
 Modifications:

CKT	Poles	Trip	Circuit Description	Phase A (VA)	Phase B (VA)	Circuit Description	Trip	Poles	CKT
1	1	15 A	Ex. Load	0 / 0	0 / 0	Main Disconnect	100 A	2	2
3	1	20 A	Ex. Load	0 / 0	0 / 0		--	--	4
5	1	20 A	Ex. Load	0 / 0	0 / 0	Parking Lot Floods	20 A	1	6
7	1	20 A	Ex. Load	0 / 0	0 / 0	Ex. Load	20 A	1	8
9	1	20 A	Ex. Load	0 / 0	0 / 0	Ex. Load	20 A	1	10
11	1	20 A	Ex. Load	0 / 0	0 / 0	Ex. Load	20 A	1	12
13	2	60 A	Panel 'B'	0 / 0	0 / 0	Ltg - West	20 A	1	14
15	--	--	--	0 / 0	0 / 0	Fire Alarm	20 A	1	16
17	1	20 A	Ltg - Lockers	408 / 0		C-Cure Access Control	20 A	1	18
19	1	20 A	Ltg - Weight Rm, EM Batt.		1279 / 0	Spare	20 A	1	20
21	1	20 A	Rcpts - Lockers	1080 / 0		Space	--	1	22
23	1	20 A	EWC - Weight Room*		360 / 0	Space	--	1	24
25	1	20 A	Rcpts - Office	1080 / 0		Space	--	1	26
27	1	20 A	Water Heater		960 / 0	Space	--	1	28
29	1	20 A	EWC - Weight Room*	180 / 0		Space	--	1	30
31	1	--	Space		0 / 0	Space	--	1	32
				2748 VA	2589 VA				
				23 A	22 A				


Load Classification	Connected Load	Demand Factor	Estimated...	Panel Totals
				Total Conn. Load: 5332 VA
				Total Est. Demand: 5332 VA
				Total Conn. Current: 22 A
				Total Est. Demand... 22 A

Notes:
 Existing Loads and Breakers Designated By *Italic font*.
 New Loads and Breakers Designated by **Bold Font**.
 Field Verify Existing Panel AIC Rating and provide equivalent AIC Rating for All New Breakers. Provide New Typed Circuit Directory
 *Provide GFCI Class A Breaker
 Existing Panelboard is a Schneider Electric CAT#0032UF



1 FLOOR PLAN - LEVEL 01 - POWER
1/8" = 1'-0"




GENERAL POWER NOTES:
1. REFER TO E0.00 FOR LEGEND AND GENERAL NOTES.






DATE:	02/16/24
SCALE:	As Indicated
DRAWN BY:	DAN
CHECKED BY:	DAN
PROJ NO:	22-0073

E2.01

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24



NOTE: UTILIZE THIS DIAGRAM FOR UP TO THREE OCCUPANCY SENSORS AND ONE CIRCUIT APPLICATIONS.



NOTE: UTILIZE THIS DIAGRAM FOR MORE THAN THREE OCCUPANCY SENSORS AND/OR MULTIPLE CIRCUITS.

RENOVATIONS TO PALMERTON HIGH SCHOOL WEIGHT ROOM

3525 FIRELINE ROAD
PALMERTON, PA 18071

PALMERTON AREA SCHOOL DISTRICT

680 FOURTH STREET PALMERTON, PA 18071

ARCHITECT:

ALLOYS ARCHITECTURE


CIVIL:

KEYSTONE CONSULTING ENGINEERS, INC.

MEPE:

SINVOER HOFFMAN ASSOCIATES, INC.

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24



ALLOY5 ARCHITECTURE

530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055



SPECIFICATIONS - ELECTRICAL

DATE: 02/16/24

SCALE:

DRAWN BY: DAN

CHECKED BY: DAN

PROJ NO: 22-0073

E4.01

ELECTRICAL DRAWING SPECIFICATIONS

GENERAL

IT IS THE INTENT OF THESE SPECIFICATIONS AND ACCOMPANYING DRAWINGS TO GENERALLY DESCRIBE THE WORK NECESSARY FOR THE INSTALLATION OF A COMPLETE ELECTRICAL INSTALLATION.

THESE DRAWINGS AND SPECIFICATIONS ARE NOT INTENDED TO SHOW THE LOCATION OF EVERY WIRE, CONDUIT, FITTING, ETC., BUT IS UNDERSTOOD THAT THE CONTRACTOR SHALL FURNISH AND INSTALL ALL MATERIALS AND LABOR FOR COMPLETE WORKABLE SYSTEMS.

ALL WORK SHALL CONFORM TO THE LATEST ADOPTED IBC, NEC AND NFPA CODES AS WELL AS ALL REQUIRED LOCAL CODES AND REGULATIONS.

ALL EQUIPMENT AND MATERIALS SHALL BEAR THE LABEL OF THE UNDERWRITERS' LABORATORIES, INC. WHERE SO REQUIRED BY THE NFPA REGULATIONS.

FURNISH ALL LABOR, EQUIPMENT HAULING, RIGGING SCAFFOLDING, SYSTEM PROGRAMMING, ETC. NECESSARY FOR COMPLETION OF WORK FOR THE PROJECT.

PERIODS OF SHUTDOWN SHALL BE MINIMAL AND ALL NEW WORK SHALL BE PLANNED AND SCHEDULED TO ACCOMPLISH AS FEW SHUTDOWNS AS POSSIBLE.

COORDINATE PHASING OF WORK INDICATED ON THE DRAWINGS WITH THE OWNER AND OTHER TRADES. PROVIDE ALL PREMIUM LABOR FOR WORK REQUIRED TO BE PERFORMED ON WEEKENDS AND 2ND AND 3RD SHIFTS AS REQUIRED FOR PHASING OF WORK, SHUTDOWNS AND SCHEDULED COMPLETION.

THE ELECTRICAL CONTRACTOR SHALL VISIT THE SITE TO ACQUAINT HIMSELF/HERSELF WITH THE SITE CONDITIONS AND ADDITIONAL COSTS WILL NOT BE PAID FOR FAILURE OF THE E.C. TO FAMILIARIZE HIMSELF/HERSELF WITH EXISTING SITE CONDITIONS AND/OR INFORMING THE ENGINEER OF UNKNOWN CONDITIONS CRUCIAL TO THE COMPLETION OF WORK PRIOR TO SUBMITTING HIS/HER BID.

ALL WORK SHALL BE PERFORMED TO MEET THE MOST RECENT VERSION OF THE NATIONAL ELECTRICAL CODE (NFPA 70). THIS SHALL INCLUDE BUT IS NOT LIMITED TO PROVIDING: GROUND FAULT PROTECTION, ARC-FAULT PROTECTION, WEATHER RESISTANT RECEPTACLES, TAMPER RESISTANT RECEPTACLES, AVAILABLE FAULT-CURRENT LABELING, ARC-FLASH LABELING, ETC.

THE SCOPE OF WORK

THE ELECTRICAL CONTRACT SHALL CONSIST OF THE FOLLOWING, BUT NOT LIMITED TO, THIS WORK:

- EXTEND EXISTING POWER DISTRIBUTION AS INDICATED
- PROVIDE NEW LIGHTING AND LIGHTING CONTROLS
- EXTEND EXISTING FIRE ALARM SYSTEM
- EXTEND EXISTING STRUCTURED CABLING SYSTEM

SUBMITTALS

THE CONTRACTOR SHALL SUBMIT SHOP DRAWINGS SUFFICIENTLY DETAILED TO SHOW THAT THE PROPOSED EQUIPMENT MEETS THE PROJECT SPECIFICATIONS. THE SHOP DRAWING PACKAGE SHALL CONTAIN THE FOLLOWING: CONTRACTORS REVIEW/APPROVAL STAMP, MANUFACTURER, SELECTED CATALOG NUMBER, CATALOG CUTS OF COMPONENTS INCLUDING SYSTEM CABINETS WITH PHYSICAL DIMENSIONS, BLOCK DIAGRAM SHOWING THE TYPES AND ARRANGEMENT OF CONNECTIONS AMONG THE COMPONENTS INCLUDING CABLE TYPES, SUBMIT ON ALL DEVICES, LIGHTING FIXTURES, PANELBOARDS, WIRING ETC. TO THE ARCHITECT FOR APPROVAL PRIOR TO ORDERING ANY EQUIPMENT. THE ARCHITECT SHALL MAKE THE ULTIMATE DECISION ON COLOR AND FINISH FOR ALL DEVICES SUCH AS RECEPTACLES, COMMUNICATION OUTLETS, SWITCHES, SWITCH PLATES, SURFACE RACEWAYS, AS WELL AS ANY OTHER CONTROL DEVICES. THIS APPROVAL SHALL BE MADE BEFORE ANY ITEMS ARE ORDERED.

OWNER INSTRUCTION AND OPERATION MANUALS SHALL BE PROVIDED TO INSTRUCT IN THE PROPER OPERATION AND MAINTENANCE OF ALL WORK. PROVIDE A MINIMUM OF (3) THREE OPERATING MANUALS FOR ALL WORK. WITHOUT THESE, THE PACKAGE WILL BE REJECTED WITHOUT REVIEW.

APPROVALS, CODES, ORDINANCES AND REGULATIONS

ALL WORK AND MATERIALS SHALL CONFORM TO ALL CODES, ORDINANCES, REGULATIONS, STANDARDS AND RULES. ALL PERMITS, UTILITY SERVICE CHARGES, FEES AND COSTS, INSPECTION CERTIFICATES AND APPROVALS SHALL BE SECURED AND PAID BY THE CONTRACTOR.

WORK SHALL NOT BE COVERED UP NOR ENCLOSED UNTIL IT HAS BEEN INSPECTED, TESTED AND APPROVED. ANY WORK THAT IS ENCLOSED OR COVERED UP BEFORE SUCH INSPECTION AND TEST, SHALL BE UNCOVERED, AFTER IT HAS BEEN INSPECTED AND APPROVED. ALL UNCOVERED ITEMS SHALL BE RESTORED TO ITS ORIGINAL COVERED CONDITION AT NO ADDITIONAL COST TO THE OWNER.

SECURE ELECTRICAL INSPECTION CERTIFICATE FROM AUTHORIZED AGENT.

CONTINUITY OF WORK AND COORDINATION

THE CONTRACTOR SHALL PLAN CONSTRUCTION SCHEDULE TO COORDINATE WITH ALL OTHER TRADES, UNLESS A SCHEDULED CHANGE HAS BEEN ARRANGED WITH THE ARCHITECT.

COORDINATION SHALL INCLUDE ADEQUATE CLEARANCES FOR THE INSTALLATION AND MAINTENANCE OF EQUIPMENT AND PHYSICAL AND ELECTRICAL REQUIREMENTS OF ITEMS OR EQUIPMENT REQUIRING CONNECTIONS.

STORAGE AND PRESERVATION OF MATERIALS

EQUIPMENT AND MATERIALS STORED AT THE SITE, PRIOR TO FINAL INSTALLATION, SHALL BE FULLY PROTECTED FROM DAMAGE, DIRT, DEBRIS, AND WEATHER. DENTS, MARRED FINISHES AND OTHERWISE DAMAGED EQUIPMENT SHALL BE REPAIRED TO ITS ORIGINAL CONDITION OR REPLACED. COORDINATE WITH THE OWNER TO DETERMINE ANY STORAGE REQUIREMENTS OR CONSTRAINTS.

CUTTING AND PATCHING

PERFORM ALL CUTTING AND PATCHING OF EVERY NATURE REQUIRED IN CONNECTION WITH THIS CONTRACT.

PERFORM CUTTING CAREFULLY SO AS NOT TO DAMAGE THE STRUCTURE OR LEAVE UNSIGHTLY SURFACES THAT CANNOT BE COVERED WITH PLATES, ESCUTCHEONS, OR OTHER NORMAL CONCEALING CONSTRUCTION.

PATCH UNSIGHTLY CONDITIONS RESULTING FROM CUTTING OR REMOVAL OF EXISTING DEVICES AS DIRECTED BY ARCHITECT. ENGAGE COMPETENT MECHANICS FOR PATCHING. ALL PATCHING SHALL MATCH ADJACENT FINISHES.

ALL GRADES, SEEDING, AND RESTORATION OF MACADAM AND CONCRETE SURFACES DISTURBED BY THIS CONTRACT SHALL BE RESTORED AS DIRECTED BY ARCHITECT AND TO THE SATISFACTION OF THE OWNER.

DEMOLITION

THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REMOVAL OF EXISTING LIGHTING FIXTURES, DEVICES, CONDUIT, WIRING AND APPURTENANCES IN THE EXISTING BUILDING WHICH IS SHOWN ON THE DRAWINGS OR WHICH IS IN CONFLICT WITH NEW CONSTRUCTION OR RENOVATIONS. DISCONNECT EXISTING CONDUIT AND WIRING TO ITEMS BEING REMOVED. WIRING AND CONDUIT SHALL BE REMOVED COMPLETELY BACK TO THE PANEL. NO WIRING SHALL BE ABANDONED IN PLACE.

ALL CONSTRUCTION AND REMOVAL WORK SHALL BE PERFORMED IN A MANNER AS TO KEEP THE EXISTING SYSTEMS IN OPERATION AS THE WORK PROGRESSES, PROVIDE ALL REQUIRED TEMPORARY CONNECTIONS AND PARTITIONS AS REQUIRED TO KEEP ADJACENT OCCUPIED AREAS IN OPERATION THROUGHOUT THE PROJECT.

PERIODS OF SHUTDOWN SHALL BE MINIMAL AND ALL NEW WORK SHALL BE PLANNED AND SCHEDULED TO ACCOMPLISH AS FEW SHUTDOWNS AS POSSIBLE. ANY REQUIRED SHUTDOWNS SHALL BE COORDINATED WITH THE OWNER. THE CONTRACTOR SHALL OBTAIN WRITTEN APPROVAL FROM THE OWNER A MINIMUM OF 72 HOURS IN ADVANCE OF ANY SHUTDOWNS.

THE OWNER SHALL HAVE THE OPTION OF KEEPING ANY OR ALL SALVAGEABLE ITEMS REMOVED FROM THE BUILDING SUCH AS LIGHT FIXTURES, PANELS, BREAKERS, ETC. THE CONTRACTOR SHALL COORDINATE WITH THE OWNER TO DETERMINE WHAT REMOVED ITEMS, IF ANY, THEY WISH TO KEEP IN ADVANCE OF THE DEMOLITION. ANY ITEMS REMOVED FROM THE BUILDING THAT THE OWNER DOES NOT WISH TO KEEP SHALL BECOME THE PROPERTY OF THE CONTRACTOR AND HE SHALL DISPOSE OF THESE ITEMS. DISPOSAL SHALL BE IN ACCORDANCE WITH ALL NATIONAL AND LOCAL CODES. FURNISH ALL LABOR, EQUIPMENT HAULING, RIGGING SCAFFOLDING, ETC. NECESSARY FOR THE REMOVAL PHASE OF THE PROJECT.

IDENTIFICATION

ALL PANELBOARDS, ELECTRICAL POWER AND BRANCH CIRCUIT CONDUCTORS, FEEDER CONDUITS, OUTLET BOXES (INSIDE OF COVER PLATES OR OUTSIDE AS PREFERRED BY OWNER), BREAKERS, TRANSFORMERS, SWITCHGEAR, MOTOR CONTROLLERS, MOTOR CONTROL CENTERS, DISCONNECTS, FIRE ALARM CONTROL PANELS, ETC., SHALL BE LABELED DESIGNATING AREA, BEING FED, TYPE OF SERVICE, CIRCUIT NUMBER, ETC.

NAMEPLATES SHALL GENERALLY BE BLACK TYPED LETTERS WITH WHITE BACKGROUND OR WHITE TYPED LETTERS WITH BLACK BACKGROUND ON LAMINATED PLASTIC WITH BEVELED EDGES. LETTERS SHALL BE A MINIMUM OF 1/8" HIGH. CONDUIT MARKERS SHALL BE STANDARD PRE-PRINTED FLEXIBLE PLASTIC SHEET MATERIAL OR SELF-ADHERING VINYL LABELS. WIRE MARKERS SHALL BE LAMINATED PLASTIC NAMEPLATES, SELF-ADHERING VINYL LABELS OR TAPE.

PROVIDE A TYPED DIRECTORY FOR EACH PANELBOARD INDICATING THE ITEM/ITEMS CONTROLLED BY EACH CIRCUIT. THE DIRECTORY SHALL BE LOCATED ON THE INSIDE OF THE HINGED DOOR TO THE PANEL.

WIRING

ALL BRANCH CIRCUIT WIRING SHALL BE COPPER "THIN" OR "THIN" UNLESS OTHERWISE NOTED ON THE DRAWINGS AND INSTALLED IN ACCORDANCE WITH THE APPLICABLE CODES LISTED ABOVE.

UNLESS OTHERWISE INDICATED, WIRE SIZES SHALL AS FOLLOWS: 20A #12, 30A #10, 40A #8, 50A #6, 70A #4, AND 100A #2. CONDUCTORS #10 AWG AND SMALLER SHALL BE SOLID ROUND COPPER WIRE. CONDUCTORS #8 AWG AND LARGER SHALL BE STRANDED CONCENTRIC COPPER WIRE.

ALL FEEDER AND BRANCH CIRCUIT CONDUCTORS SHALL BE COLOR CODED. A GREEN GROUND WIRE SHALL BE RUN WITH ALL CIRCUITS. SHARED NEUTRALS ARE NOT PERMITTED AND FULL RATED NEUTRALS SHALL BE PROVIDED FOR ALL CIRCUITS.

MULTI-CONDUCTOR METAL CLAD CABLE (MC) WITH GROUND WIRE SHALL BE ACCEPTABLE FOR USE THROUGHOUT THE BUILDING EXCEPT WHERE SPECIFICALLY NOTED OTHERWISE. MULTICONDUCTOR CABLE SHALL BE IDENTIFIED BY APPLICABLE CODES. MULTICONDUCTOR CABLE MAY ONLY BE USED WHERE CONCEALED IN WALLS OR FULLY CONCEALED FROM VIEW ABOVE ACCESSIBLE CEILINGS, AND IN ACCORDANCE WITH THE NEC. MULTICONDUCTOR CABLE SHALL BE SUPPORTED INDEPENDENT OF CEILING STRUCTURE. MULTICONDUCTOR CABLE IN PLENUM SPACES SHALL BE COMPLIANT WITH NEC 300.22 - MC CABLE EMPLOYING A SMOOTH OR CORRUGATED METAL SHEATH WITHOUT AN OVERALL NONMETALLIC COVERING. PROVIDE BUSHINGS ON ALL MC CABLE ENDS.

NON-METALLIC SHEATHED CABLE (ROMEX, ETC.) SHALL NOT BE ACCEPTABLE FOR USE ANYWHERE IN THE BUILDING.

THE CONTRACTOR SHALL ACCOUNT FOR VOLTAGE DROP WHEN PROVIDING LONG LEAD LENGTHS OF CONDUCTORS.

CONDUCTORS OF SPECIAL SERVICE SYSTEMS AND POWER SYSTEMS SHALL NOT OCCUPY THE SAME ENCLOSURE WITH LIGHT AND POWER CONDUCTORS OR THE SAME ENCLOSURE WITH EACH OTHER. CONDUCTORS SHALL BE CONTINUOUS WITH SPLICES AND CONNECTIONS MADE IN OUTLET, JUNCTION OR PULL BOXES ONLY.

WHERE SEVERAL FEEDERS PASS THROUGH A COMMON PULL BOX, THE FEEDERS SHALL BE TAGGED TO CLEARLY INDICATE THE ELECTRICAL CHARACTERISTICS, CIRCUIT NUMBER AND PANEL DESIGNATION.

CIRCUIT CONDUCTORS SHALL BE SAME AWG SIZE FROM SOURCE TO LOAD. NEUTRAL WIRES SHALL BE THE SAME SIZE AS PHASE WIRES EXCEPT AS NOTED ON DRAWINGS.

ALL WIRING SHALL BE INSTALLED CONCEALED IN WALLS AND NOT EXPOSED ON OPEN WALLS. IF WIRING MUST BE EXPOSED, SURFACE RACEWAY WILL BE USED BUT ONLY AS SPECIFICALLY DIRECTED BY THE ARCHITECT.

ALL WIRING AND CONDUITS SHALL BE SUPPORTED IN AN APPROVED NEAT AND ORDERLY FASHION, AND AS REQUIRED BY APPLICABLE CODES. FASTEN CABLES SIMPLY IN PLACE AT INTERVALS NOT EXCEEDING NEC REQUIREMENTS. WIRING AND CONDUITS SHALL BE SUPPORTED DIRECTLY FROM THE BUILDING STRUCTURE UTILIZING MECHANICALLY SECURE CLIPS, TRAPEZE, CLEVIS HANGERS, OR CABLE TRAY. TIE-WRAPS SHALL NOT BE AN ACCEPTABLE MEANS OF SUPPORT EXCEPT WHERE VENDOR TRAP WRAPS ARE APPLICABLE. FOR LOW AND MEDIUM VOLTAGE, CABLE TO SUPPORT FROM MECHANICAL DUCTWORK OR PIPING SHALL NOT BE ACCEPTABLE. ANY WIRING OR CONDUITS DEEMED AS NOT BEING CONCEALED FROM VIEW OR SUPPORTED PROPERLY BY THE ARCHITECT SHALL BE REMOVED AND RE-INSTALLED TO THE SATISFACTION OF THE ARCHITECT/ENGINEER AT THE SOLE EXPENSE OF THE CONTRACTOR.

GROUNDING

PROVIDE ALL ELECTRICAL SYSTEM GROUNDS AS REQUIRED BY THE NATIONAL ELECTRICAL CODE, AND THE NATIONAL ELECTRICAL SAFETY CODE.

THE FOLLOWING SHALL BE SOLIDLY GROUNDED: 1) CONDUIT SYSTEM (NEC ARTICLE 250), 2) ALL EQUIPMENT WITH ELECTRICAL CONNECTIONS, 3) NEUTRAL LEAD OF SECONDARY SERVICE.

A SEPARATE GROUNDING CONDUCTOR SHALL BE FURNISHED AND INSTALLED FOR ALL ELECTRICAL CIRCUITS. ALL ELECTRICAL EQUIPMENT ENCLOSURES AND CONDUCTOR ENCLOSURES SHALL BE GROUNDED.

ALL FEEDER DISCONNECTS AND BREAKERS RATED 1000 AMPERES AND ABOVE IN A SOLIDLY GROUNDED WYE SYSTEM WITH GREATER THAN 150 VOLTS TO GROUND, BUT NOT EXCEEDING 600 VOLTS PHASE TO PHASE SHALL BE PROVIDED WITH GROUND FAULT PROTECTION.

ALL WIRING SHALL BE TESTED WITH A MEGGER FOR GROUNDS AND SHORTS BEFORE ENERGIZING.

CONDUIT

CONDUIT SHALL BE NO SMALLER THAN 3/4 INCH, UNLESS OTHERWISE NOTED FOR INTERIOR APPLICATIONS AND NO SMALLER THAN 1" FOR EXTERIOR APPLICATIONS. CONDUIT JOINTS SHALL BE MADE UP WITH FITTINGS OF THE PROPER TYPE. CONDUIT SHALL BE SIZED AS PER NEC RULES FOR NUMBER AND SIZE OF WIRES THEREIN.

ELECTRICAL METALLIC TUBING (EMT) SHALL BE METALLIC CONDUIT OF THE THIN WALL TYPE IN STRAIGHT LENGTHS, ELBOWS, OR BENDS AND SHALL CONFORM TO ANSI C80.3 AND THE REQUIREMENTS OF UL 797. EMT SHALL BE INSTALLED INDOORS IN DRY LOCATIONS NOT SUBJECT TO MECHANICAL INJURY. ALSO, CONCEALED CIRCUITS AND CIRCUITS LOCATED IN PLENUM SHALL BE EMT UNLESS OTHERWISE NOTED. COUPLINGS AND CONNECTORS FOR EMT SHALL BE HEX-NUT EXPANSION-GLAND, COMPRESSION TYPE. ZINC OR CADMIUM-PLATED, CRIMP, SPRING OR SET-SCREW TYPE FITTINGS ARE NOT ACCEPTABLE. WHERE EMT ENTERS OUTLET BOXES, CABINETS OR OTHER ENCLOSURES, CONNECTORS SHALL BE THE INSULATED-THROAT TYPE, WITH LOCKNUTS. FITTINGS SHALL MEET THE REQUIREMENTS OF ANSINEMA FBI.

FLEXIBLE METALLIC CONDUIT (FMC) SHALL MEET THE REQUIREMENTS OF UL 1. FMC WITH SEPARATE GROUND WIRE SHALL BE INSTALLED IN AREAS SUBJECT TO VIBRATION IN MAXIMUM SIX-FOOT LENGTHS PROPERLY SUPPORTED.

RIGID GALVANIZED STEEL CONDUIT (RMC) SHALL CONFORM TO UL 6 AND ANSI C80.1. RMC WITH THREADED FITTINGS SHALL BE INSTALLED OUTDOORS, WHERE UNDERGROUND, OR IN AREAS SUBJECT TO WEATHER AND/OR MECHANICAL INJURY. RMC CONDUIT SHALL BE USED IN ALL OPEN SHOP AREAS TO A MINIMUM ELEVATION OF 15'-0" AFF. CONDUIT FITTINGS SHALL CONFORM TO ANSINEMA FBI.

LIQUIDTIGHT FLEXIBLE METALLIC CONDUIT (LFMC) SHALL CONSIST OF STEEL, CONSTRUCTED OF SINGLE STRAP, FLEXIBLE CONTINUOUS, INTERLOCKING AND FINISHED WITH A LIQUID-TIGHT JACKET OF FLEXIBLE POLY(VINYL CHLORIDE) (PVC) CONFORMING TO NEMA RN1. LFMC WITH SEPARATE GROUND WIRE SHALL BE INSTALLED IN AREAS SUBJECT TO VIBRATION IN MAXIMUM SIX FOOT LENGTHS PROPERLY SUPPORTED.

RIGID NONMETALLIC CONDUIT (RNC) SHALL COMPLY WITH NEMA TC2, SCHEDULE 40 AND SCHEDULE 80 PVC. RNC SHALL BE INSTALLED BELOW GRADE, FOR RNC, USE SOLVENT-CEMENTED JOINTS IN DUCTS AND FITTINGS AND MAKE WATER-TIGHT ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS. STAGGER COUPLINGS SO THOSE OF ADJACENT DUCTS DO NOT LINE UP. THE END OF THE CONDUIT SHALL BE FINISHED WITH A PLUG. RNC SHALL BE INSTALLED ABOVE GRADE AND SHALL RUN PARALLEL TO CEILING, FLOORS, WALLS OR OTHER PERMANENT STRUCTURES. THE CONTRACTOR SHALL FURNISH AND INSTALL ABOVE GRADE CONDUIT SYSTEMS AS SPECIFIED, INCLUDING ALL NECESSARY SUPPORTS, HANGERS, AND OTHER HARDWARE.

ALL CONDUIT IN FINISHED AREAS SHALL BE INSTALLED CONCEALED. IF CONDUIT MUST BE EXPOSED, SURFACE RACEWAY WILL BE USED BUT ONLY AS SPECIFICALLY DIRECTED BY THE ARCHITECT. ALL EXPOSED CONDUIT SHALL BE PAINTED TO MATCH ADJACENT SURFACE COLORS.

CONDUIT SHALL BE SECURELY CLAMPED AND SUPPORTED AT LEAST EVERY 10 FEET VERTICALLY AND 8 FEET HORIZONTALLY. GALVANIZED PIPE STRAPS SHALL BE INSTALLED TO STRUCTURE WITH BOLTS, SCREWS AND ANCHORS. CONDUIT AND BOXES SHALL NOT BE SUPPORTED FROM 1-BAR CEILING WIRES.

EXPANSION FITTINGS WITH FLEXIBLE GROUND STRAP SHALL BE PROVIDED IN CONDUIT RUNS CROSSING BUILDING EXPANSION JOINTS.

CONTRACTOR SHALL AVOID MORE THAN THREE 90 DEGREE BENDS, OR EQUIVALENT, IN A RUN BETWEEN PULL FITTINGS.

WHERE APPLICABLE, CONDUITS SHALL BE FASTENED TO ALL SHEET METAL BOXES, GUTTERS AND CABINETS WITH TWO LOCKNUTS AND A BUSHING.

EMERGENCY LIGHTING SYSTEM WIRING SHALL BE IN RIGID CONDUIT, EMT.

INSULATED BUSHINGS

FURNISH AND INSTALL ALL INSULATED BUSHINGS, AS MANUFACTURED BY O.Z. OR T&B COMPANIES FOR ALL POWER SYSTEM CONDUITS AND ALL LIGHTING SYSTEM CONDUITS 1/4" AND LARGER. PROVIDE INSULATED BUSHINGS ON ALL CONDUITS USED FOR LOW-VOLTAGE SYSTEMS AND ALL FLEXIBLE METALLIC CONDUITS REGARDLESS OF SIZE.

EMERGENCY LIGHTING AND WIRING SYSTEM

THE CONTRACTOR SHALL FURNISH AND INSTALL AN EMERGENCY LIGHTING SYSTEM AND EMERGENCY WIRING SYSTEM AS INDICATED ON THE DRAWINGS.

ALL EMERGENCY WIRING SHALL BE OF #10 THW OR LARGER DIAMETER. WIRING SHALL BE INSTALLED IN A SEPARATE CONDUIT SYSTEM FROM NORMAL LIGHTING AND POWER CIRCUITS.

JUNCTION, PULL AND OUTLET BOXES

JUNCTION AND PULL BOXES SHALL BE INSTALLED WHERE SHOWN ON THE DRAWINGS, OR AT SUCH LOCATIONS AS MAY BE REQUIRED TO FACILITATE THE PULLING OF CABLES. PULL BOXES SHALL BE FURNISHED AND INSTALLED ON CONDUIT RUNS LONGER THAN 100 FEET OR WITH MORE THAN THREE RIGHT-ANGLE BENDS. JUNCTION BOXES AND PULL BOXES SHALL HAVE SUFFICIENT VOLUME TO ACCOMMODATE THE NUMBER OF CONDUCTORS ENTERING THE BOX IN ACCORDANCE WITH THE REQUIREMENTS OF NEC ARTICLE 314. BOXES SHALL BE CADMIUM-PLATED OR ZINC-COATED SHEET METAL. JUNCTION BOXES AND PULL BOXES FOR USE WITH THE CONDUIT SYSTEMS SHALL NOT BE LESS THAN 2-1/8" DEEP AND 4" BY 4". PULL AND JUNCTION BOXES SHALL BE FURNISHED WITH HINGED OR SCREW-FASTENED COVERS. PROVIDE EXTRA-DEEP BOXES WHERE REQUIRED FOR LOW-VOLTAGE SYSTEM CONNECTIONS.

OUTLET BOXES SHALL CONSIST OF STEEL BOXES OF PROPER TYPE AND NOT LESS THAN 4" SQUARE. COMPLY WITH UL 514B, FITTINGS FOR CONDUIT AND OUTLET BOXES. THE REQUIRED SIZE BY THE N.E.C. SHALL BE PLACED AT ALL LIGHT, RECEPTACLE AND SWITCH OUTLETS. OUTLET BOXES SHALL BE FIRMLY SECURED IN PLACE AND SHALL BE SET TRUE, SQUARE AND FLUSH WITH THE FINISHED SURFACES. OUTLET BOXES SHALL BE EQUIPPED WITH PLASTER RINGS, EXTENSION RINGS AND FIXTURE STUDS WHERE REQUIRED. ALL UNUSED OPENINGS IN BOXES SHALL BE CLOSED WITH FACTORY MADE KNOCKOUT SEALS.

BOXES AND ENCLOSURES SHALL BE SECURELY MOUNTED TO THE BUILDING STRUCTURE WITH SUPPORTING FACILITIES INDEPENDENT OF THE CONDUIT ENTERING OR LEAVING THE BOXES.

SUPPORTING DEVICES AND HANGERS

SECURE ALL EQUIPMENT, DEVICES AND RACEWAYS. ALL CONDUITS SHALL BE SECURELY FASTENED AND SUPPORTED AS APPROVED IN THE NEC. DO NOT FASTEN SUPPORTS TO PIPES, DUCTS, MECHANICAL EQUIPMENT OR CONDUIT. SUPPORTS SHALL NOT BE ATTACHED TO ANY ROOF OR FLOOR DECK.

PROVIDE ALL STEEL SUPPORTS, MOUNTING BRACKETS, ANGLES, THREADED RODS, SLOTTED CHANNELS, ETC. AS REQUIRED FOR SUPPORT OF THE EQUIPMENT FURNISHED AND/OR INSTALLED.

WIRING DEVICES

SWITCHES SHALL BE OF THE A.C. HEAVY DUTY, 277VOLT, FLUSH TOGGLE TYPE RATED AT 20 AMPERES AND U.L. APPROVED. SWITCHES SHALL BE LOCATED ON THE KNOB SIDE OF THE DOOR AND MOUNTED 48" ABOVE THE FINISHED FLOOR. FOR SWITCHES TO BE MOUNTED IN THE SAME GANGED PLATE AS DIMMERS, THE SWITCH SWITCH SHALL MATCH THAT OF THE DIMMERS.

GENERAL PURPOSE RECEPTACLES AND GFCI RECEPTACLES SHALL BE HEAVY DUTY INDUSTRIAL GRADE MINIMUM POLARIZED, GROUNDED, DUPLEX, RATED 20 AMPERES, 120V AND U.L. APPROVED. ALL RECEPTACLES SHALL BE MOUNTED 18 INCHES ABOVE THE FINISHED FLOOR UNLESS OTHERWISE NOTED OR SO DIRECTED BY THE ARCHITECT. RECEPTACLES SHALL BE TAMPER RESISTANT WHERE REQUIRED PER THE NEC.

RECEPTACLES SHALL BE HOSPITAL GRADE WHERE APPLICABLE PER THE NEC.

OUTDOOR RECEPTACLES SHALL BE WEATHER-RESISTANT OUTDOOR GRADE GFCI WITH AN IN-N-USE, METAL, WEATHERPROOF ENCLOSURE.

FOR HOSPITALITY APPLICATIONS AND IN HOSPITAL PATIENT BATHROOMS, BATHROOM GFCI RECEPTACLES SHALL HAVE GUIDE LIGHTS.

PROVIDE TAMPER RESISTANT AND WEATHER RESISTANT RECEPTACLES AS REQUIRED BY CODE.

GFI RECEPTACLES SHOWN ON THE DRAWINGS SHALL BE UNDERSTOOD TO BE THE MINIMUM NUMBER OF GFI RECEPTACLES TO BE PROVIDED. PROVIDE GFI TYPE RECEPTACLES FOR ANY RECEPTACLE LOCATION SHOWN ON THE DRAWINGS AND REQUIRED TO BE GFI TYPE BY THE NEC CODE.

DEVICE PLATES OF ONE PIECE SHALL BE PROVIDED FOR ALL OUTLETS TO SUIT THE DEVICES INSTALLED. PLATES SHALL BE SMOOTH BRUSHED STAINLESS STEEL UNLESS OTHERWISE DIRECTED. PLATES SHALL BE INSTALLED WITH ALL FOUR EDGES IN CONTINUOUS CONTACT WITH THE FINISHED WALL SURFACES OR JUNCTION BOX WITHOUT THE USE OF MATS OR SIMILAR DEVICES. PLATE SHALL BE INSTALLED VERTICALLY AND WITH AN ALIGNMENT TOLERANCE OF +/- 1/16 INCH.

DEVICE PLATES SHALL BE SIMILAR TO LEVITON COMMERCIAL SPECIFICATION GRADE 84001, 84009, 84003, 84016, OR EQUAL BY HUBBELL ETC.

SWITCHES SHALL BE SIMILAR TO LEVITON COMMERCIAL SPECIFICATION GRADE 54521-21, 54523-21, 54524-21, 14514, 14534, OR EQUAL BY HUBBELL ETC.

250 VOLT RECEPTACLES SHALL BE SIMILAR TO LEVITON COMMERCIAL SPECIFICATION GRADE 5823-1, 5028-1 OR EQUAL BY HUBBELL ETC.

DIMMERS SHALL BE BY LUTRON OR AN APPROVED EQUIVALENT. DIMMERS SHALL MATCH THE HOLE OPENING OF NEARBY NEIGHBORING SWITCHES. THEY SHALL BE SPECIFICATION GRADE, SLIDE TYPE OR BUTTON TYPE FOR RAISE AND LOWER FUNCTIONS. THEY SHALL BE RATED FOR 120 VOLTS OR 277 VOLTS AS APPLICABLE. THE RATED WATTAGE SHALL BE DEPENDENT UPON THE LIGHTING LOAD. DIMMER TYPE SHALL MATCH THE LOAD TYPE THAT THEY ARE CONTROLLING - I.E. FLUORESCENT FOR FLUORESCENT DIMMING, ELECTRONIC LOW VOLTAGE FOR DIMMING ELECTRONIC TRANSFORMERS, LED FOR LED LOADS, AND 0-10V FOR 0-10V APPLICATIONS. VERIFY APPLICATION REQUIREMENTS WITH DIMMER MANUFACTURER. PROVIDE ACCESSORIES AND APPURTENANCES AS NECESSARY TO SUPPORT LARGER LOADS OR THOSE DIMMING APPLICATIONS WHICH REQUIRE INTERFACES. DIMMER LOCATIONS TO BE CONFIRMED WITH OWNER PRIOR TO ROUGH-IN. IN THE CASE OF DIMMERS GANGED TOGETHER, THE CONTRACTOR SHALL APPLY THE APPROPRIATE DERATING FACTORS AS THE MULTIPLE DIMMERS ARE GANGED TOGETHER. PROVIDE 3-WAY AND 4-WAY DIMMING OPERATION FROM MULTIPLE LOCATIONS WHERE SHOWN.

WIRING DEVICES SHALL BE INSTALLED AND TESTED TO VERIFY THE UNITS ARE WORKING AS INTENDED. CONTRACTOR SHALL TROUBLESHOOT ANY DEVICES NOT FUNCTIONING PROPERLY OR AS INTENDED. CONTRACTOR SHALL EITHER RESTORE THE PROBLEMATIC DEVICE OR REPLACE IT IN LIKE KIND, REPLY TEST UNTIL DEVICES ARE VERIFIED TO BE IN WORKING CONDITION.

BARRIERS BETWEEN ADJACENT DEVICES SHALL BE INSTALLED WHERE REQUIRED PER NEC 406.4(G).

ALL DEVICES SHALL BE GROUNDED UTILIZING A INSULATED SYSTEM GROUNDING WIRE BACK TO THE POWER SOURCE.

PROVIDE NEUTRAL WIRE AT EACH SWITCH LOCATION.

CONTRACTOR WIRING SYSTEM

THE CONTRACTOR SHALL WIRE EACH WORKSTATION OUTLET SHOWN ON THE DRAWINGS TO THE PATCH PANEL AT THE LOCATION SHOWN ON THE DRAWINGS. ALL WIRING SHALL BE INSTALLED IN AT LEAST 3/4" EMT TO THE ACCESSIBLE CEILING. DATA WIRING SHALL BE INSTALLED IN SEPARATE RACEWAYS FROM POWER WIRING. PROVIDE OUTLETS, HORIZONTAL WIRING, CROSS-CONNECT PATCH PANELS, EQUIPMENT BACKBOARDS, AND OTHER MATERIALS AND LABOR FOR A 10G/2 LOCAL AREA NETWORK (LAN) WIRING SYSTEM.

PROVIDE LISTED SURGE PROTECTION DEVICES (SPD'S) RATED FOR THE APPLICATION ON EVERY LOW-VOLTAGE CABLE FEEDING ANY EXTERIOR DEVICE (CAMERA, WI-FI, ETC.). LOCATE SPD AT A READILY ACCESSIBLE LOCATION NEAR THE INTERIOR BUILDING PENETRATION.

CABLE IDENTIFICATION SHALL BE PROVIDED ON BOTH ENDS OF EACH CABLE AND TERMINATION WITH THE OWNERS ROOM NUMBER AND WIRING BLOCK OR DEVICE TO WHICH IT IS CONNECTED. TAGS SHALL BE PERMANENT AND NEAT.

ALL WIRING SHALL BE INSTALLED IN AT LEAST 3/4" EMT TO THE ACCESSIBLE CEILING. DATA WIRING SHALL BE INSTALLED IN SEPARATE RACEWAYS FROM POWER WIRING.

INSTALL SYSTEMS IN ACCORDANCE WITH NFPA 70 AND OTHER APPLICABLE CODES. INSTALL EQUIPMENT IN ACCORDANCE WITH MANUFACTURERS AND SUPPLIERS INSTRUCTIONS.

ALL WIRING SHALL BE SUPPORTED IN AN APPROVED NEAT AND ORDERLY FASHION UTILIZING ONE OF THE FOLLOWING SUPPORT METHODS: J-HOOKS, TRAPEZE, OR CABLE TRAY. WIRING SUPPORTS AND SUPPORT METHOD SHALL COMPLY WITH ALL APPLICABLE CODES. ANY WIRING DEEMED AS NOT BEING SUPPORTED IN A NEAT AND ORDERLY FASHION BY THE ENGINEER SHALL BE REMOVED AND RE-INSTALLED PROPERLY AT THE EXPENSE OF THE E.C. PROVIDE A PROPERLY GROUNDED, GROUNDING BUS BAR IN EACH DATA/NETWORK CLOSET AND GROUND ALL CABLE TRAYS, RACKS ETC. TO THIS POINT.

IF CROSS TALK, APPRECIABLE LOSS OF VOLUME OR DISTORTION OCCURS AFTER INSTALLATION HAS BEEN COMPLETED, IT SHALL BE SOLE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR TO CORRECT ANY SUCH CONDITION WITHOUT COST TO THE OWNER.

THE SYSTEM IN ITS ENTIRETY SHALL BE WARRANTED FOR 15 YEARS FROM FINAL ACCEPTANCE BY THE OWNER. THIS WARRANTY SHALL INCLUDE COMPONENT AND PERFORMANCE WARRANTIES. COMPLETE TESTING BETWEEN PATCH PANELS AND OUTLET LOCATIONS TO VERIFY COMPLIANCE WITH SPECIFICATIONS.

THE COMPLETE INSTALLATION SHALL CONFORM TO EIA/TIA 568-COMMERCIAL BUILDING TELECOMMUNICATIONS WIRING STANDARDS AND PROPOSED REVISIONS OF EIA/TIA 568-COMMERCIAL BUILDING TELECOMMUNICATIONS WIRING STANDARD.

SHOP DRAWINGS SHALL BE SUBMITTED TO THE ENGINEER PRIOR TO INSTALLATION AND INCLUDE MANUFACTURER'S INFORMATION ON ALL SYSTEM COMPONENTS SPECIFIED. THE INFORMATION SHALL BE SUFFICIENT TO VERIFY COMPLIANCE WITH THE SPECIFICATIONS. THE COMPUTER WIRING SYSTEM COMPONENTS SPECIFIED CONSIST OF THE FOLLOWING:

CATEGORY 6A WIRING SHALL BE 100 OHM, 24AWG COPPER, 8 CONDUCTOR, UNSHIELDED TWISTED PAIR CABLE, PVC JACKET, PLENUM RATED AS MANUFACTURED BY AMP, BELDEN BERK-TEK OR MOHAWK.

TWO PORT COMPUTER OUTLET KEYPAD, 4 PAIR, CATEGORY 6A, RJ45, 110 CONNECTION, T568A MODULAR JACK, WITH MATCHING FACE PLATE OR EQUAL, APPROVED IN ADVANCE.

PATCH PANELS SHALL BE 48-PORT AND/OR 24-PORT, AS REQUIRED, 19" BRACKET MOUNT, CATEGORY 6A, NON-KEYED EIGHT-CONDUCTOR EIA/TIA568A MODULAR

**RENOVATIONS TO
PALMERTON HIGH
SCHOOL WEIGHT ROOM**

3525 FIRELINE ROAD
PALMERTON, PA 18071

**PALMERTON AREA
SCHOOL DISTRICT**

680 FOURTH STREET PALMERTON, PA 18071

ARCHITECT:

ALLOYS
ARCHITECTURE

CIVIL:

KEYSTONE CONSULTING
ENGINEERS, INC.

MEPE:

SNYDER HOFFMAN
ASSOCIATES, INC.

SUBMISSIONS:

NO.	ISSUE DESCRIPTION	DATE
1	100% DD REVIEW	01/12/24
2	100% CD REVIEW	02/09/24
3	BID SET	02/16/24

KEY PLAN:



REGISTRATION:

ALLOY5
ARCHITECTURE
530 WEST BROAD ST BETHLEHEM, PA 18018
610.419.4055



SHEET TITLE:

**SPECIFICATIONS -
ELECTRICAL**

DATE: 02/16/24

SCALE:

DRAWN BY: DAN

CHECKED BY: DAN

PROJ NO: 22-0073

E4.02

FIRE ALARM SYSTEM

THE FIRE ALARM INSTALLATION SHALL BE IN ACCORDANCE WITH NEC, NFPA 72, LOCAL CODE REQUIREMENTS AS WELL AS THE AMERICAN WITH DISABILITIES ACT. THE MANUFACTURER SHALL BE AND EXTENSION OF THE EXISTING SIMPLEX GRINNEL SYSTEM. THE SYSTEM SHALL BE 24V DC OBTAINED FROM 120V AC SERVICE AND A POWER-SUPPLY MODULE. SECONDARY POWER SHALL BE SUPPLIED VIA 24V DC SUPPLY SYSTEM INCLUDING BATTERIES, AUTOMATIC BATTERY CHARGER AND AN AUTOMATIC TRANSFER SWITCH. BATTERY BACK-UP SHALL COMPLY WITH NFPA 72. PROVIDE ALL THE NECESSARY MODULES AND RELAYS REQUIRED. THE SYSTEM SHALL BE UL LISTED FOR THIS SERVICE.

FIRE ALARM SIGNAL INITIATION SHALL BE BY ONE OR MORE OF THE APPLICABLE FOLLOWING DEVICES: MANUAL STATIONS; HEAT DETECTORS; SMOKE DETECTORS; DUCT TYPE SMOKE DETECTORS; SPRINKLER SYSTEM WATER FLOW; FIRE EXTINGUISHING SYSTEM OPERATION; FIRE STANDPIPE SYSTEM. S

FIRE ALARM SIGNAL SHALL INITIATE THE ALL OF THE APPLICABLE FOLLOWING ACTIONS: ALARM NOTIFICATION APPLIANCES SHALL OPERATE CONTINUOUSLY; IDENTIFY ALARM AT THE FACP AND REMOTE ANNUNCIATOR; DE-ENERGIZE ELECTROMAGNETIC DOOR HOLDERS; TRANSMIT AN ALARM SIGNAL TO THE REMOTE ALARM RECEIVING STATION; UNLOCK ELECTRIC DOOR LOCKS IN DESIGNATED EGRESS PATHS; RELEASE FIRE AND SMOKE DOORS HELD OPEN BY MAGNETIC DOOR HOLDERS; SWITCH HEATING, VENTILATING, AND AIR-CONDITIONING EQUIPMENT CONTROLS TO FIRE ALARM MODE; CLOSE SMOKE DAMPERS IN AIR DUCTS OF SYSTEM SERVING ZONE WHERE ALARM WAS INITIATED; ELEVATOR RECALL WHERE APPLICABLE.

SYSTEM TROUBLE SIGNAL INITIATION SHALL BE BY ONE OR MORE OF THE FOLLOWING DEVICES OR ACTIONS: OPEN CIRCUITS, SHORTS AND GROUNDS OF WIRING FOR INITIATING DEVICE; SIGNALING LINE, AND NOTIFICATION-APPLIANCE CIRCUITS; OPENING, TAMPERING, OR REMOVAL OF ALARM-INITIATING AND SUPERVISORY SIGNAL-INITIATING DEVICES; LOSS OF PRIMARY POWER AT THE FACP, GROUND OR A SINGLE BREAK IN FACP INTERNAL CIRCUITS; ABNORMAL AC VOLTAGE AT THE FACP; A BREAK IN STANDBY BATTERY CIRCUITRY; FAILURE OF BATTERY CHARGING; ABNORMAL POSITION OF ANY SWITCH AT THE FACP OR ANNUNCIATOR; FIRE-PUMP POWER FAILURE, INCLUDING A DEAD-PHASE OR PHASE-REVERSAL CONDITION.

SYSTEM TROUBLE AND SUPERVISORY SIGNAL ACTIONS: RING TROUBLE BELL AND ANNUNCIATE AT THE FACP AND REMOTE ANNUNCIATORS. MANUAL PULL STATIONS SHALL BE ADDRESSABLE, DOUBLE ACTION, SURFACE MOUNTED WITH MANUFACTURER'S STANDARD BACKBOX.

HORN/STROBE UNITS SHALL BE WALL MOUNTED WHERE SHOWN AND WHERE REQUIRED IN ACCORDANCE WITH NFPA 72.

SMOKE DETECTORS SHALL BE PHOTOELECTRIC TYPE, CEILING MOUNT SMOKE DETECTORS WITH ADJUSTABLE SENSITIVITY, AUXILIARY RELAY CONTACT, INTEGRAL THERMAL ELEMENT RATED 135 DEGREES F AND VISUAL INDICATION OF DETECTOR ACTIVATION. PROVIDE SOUNDER BASES AND INTEGRAL CARBON MONOXIDE DETECTION AS REQUIRED.

THE ELECTRICAL CONTRACTOR SHALL COORDINATE THE EXACT QUANTITY AND LOCATION OF DUCT DETECTORS REQUIRED WITH THE H.C. FURNISH ALL REQUIRED DUCT DETECTORS AND TURN OVER TO THE H.C. FOR MECHANICAL INSTALLATION OF THE DUCT DETECTOR INTO THE DUCTWORK. THE E.C. SHALL PROVIDE ALL WIRING AND FINAL CONNECTION TO THE FIRE ALARM SYSTEM. PROVIDE DUCT TYPE SMOKE DETECTORS, THEY SHALL BE PHOTOELECTRIC TYPE, WITH (2) AUXILIARY SPDT RELAY CONTACTS, KEY-OPERATED NORMAL-RESET-TEST SWITCH, DUCT SAMPLING TUBES EXTENDING WIDTH OF DUCT, VISUAL INDICATION OF DETECTOR ACTIVATION AT DUCT MOUNTED HOUSING AND SHUT-OFF CONTROL CONNECTED TO THE BUILDING CONTROL SYSTEM. INSTALLATION OF DEVICE AND APPURTENANCES SHALL BE BY HVAC CONTRACTOR. FOR EACH MECHANICAL UNIT WITH DUCT DETECTOR, PROVIDE FIRE ALARM CONTROL RELAY WITHIN 3' OF MECHANICAL UNIT CONTROLLER FOR SHUTDOWN.

STROBES, HORNS, AND HORN/STROBE UNITS SHALL BE PROVIDED AS SHOWN ON DRAWINGS AND IN ACCORDANCE WITH NFPA 72 WITH RATINGS OF 15, 30, 75 OR 110 CANDELA (AS INDICATED ON DRAWINGS). THE STROBES SHALL MEET THE PROVISIONS ALLOWED UNDER THE AMERICANS WITH DISABILITIES ACT.

ADDRESSABLE RELAYS SHALL BE PROVIDED FOR EACH FLOW AND TAMPER SWITCH.

HEAT DETECTOR FIXED TEMPERATURE SENSING SHALL BE INDEPENDENT OF RATE-OF-RISE SENSING AND PROGRAMMABLE TO OPERATE AT 135-DEG F OR 155-DEG F. SENSOR RATE-OF-RISE TEMPERATURE DETECTION SHALL BE SELECTABLE AT THE FACP FOR EITHER 15-DEG F OR 20-DEG F PER MINUTE.

THE ELEVATOR SHAFT HEAT DETECTOR SHALL BE PROGRAMMABLE TO OPERATE AT 15 DEGREES FAHRENHEIT LESS THAN THE SPRINKLER HEAD RATING. PROVIDE ALL RELAYS AND MONITORING MODULES AS REQUIRED FOR THE ELEVATOR RECALL AND SHUNT TRIP OPERATION WHERE APPLICABLE.

THE KITCHEN HEAT DETECTORS SHALL BE PROGRAMMABLE TO OPERATE AT 200 DEGREES FAHRENHEIT FIXED.

THE CONTRACTOR WILL BE REQUIRED TO COORDINATE WITH A MANUFACTURER'S REPRESENTATIVE FOR THE CORRECT EQUIPMENT MODEL NUMBERS PRIOR TO ORDERING.

- MANUAL PULL STATIONS,
- AUDIBLE/VISUAL DEVICES,
- VISUAL ONLY DEVICES,
- DOOR HOLD OPEN DEVICES,
- DOOR RELEASE DEVICES,
- SMOKE DETECTORS,
- HEAT DETECTORS,
- DUCT DETECTORS (TWO ENCAPSULATED RELAYS PER DUCT SMOKE DETECTOR),
- ADDRESSABLE RELAYS,
- PLENUM RATED WIRING.

ALL WIRING SHALL BE AS RECOMMENDED BY THE FIRE ALARM SYSTEM MANUFACTURER, PER NFPA AND UL LISTED. ALL WIRING SHALL BE PROVIDED AND INSTALLED BY THE CONTRACTOR. THE CONTRACTOR WILL BE REQUIRED TO COORDINATE WITH THE MANUFACTURER'S REPRESENTATIVE FOR THE REQUIRED WIRING BETWEEN THE DEVICES, THE NOTIFICATION APPLIANCE EXTENDER PANELS AS WELL AS THE MAIN FIRE ALARM CONTROL PANEL.

CABLE SHALL BE PLENUM RATED. SPECIFIC TYPE RECOMMENDED BY THE EQUIPMENT MANUFACTURER AND APPROVED FOR USE AS A FIRE ALARM CABLE BY THE NATIONAL FIRE CODE AND THE LOCAL AUTHORITY.

INSTALL ALL CABLING EXPOSED TO VIEW AND ABOVE NON-ACCESSIBLE CEILINGS IN CONDUIT. WIRING MAY BE INSTALLED WITHOUT CONDUIT ABOVE ACCESSIBLE CEILINGS. PROVIDE DEDICATED SUPPORTS FOR ALL WIRING AND CONDUITS, DO NOT SHARE WITH OTHER SYSTEMS.

CABLING SHALL BE FIRE ALARM TYPES AS APPLICABLE IN COMPLIANCE WITH NEC ARTICLE 760 AND APPROVED FOR USE AS A FIRE ALARM CABLE BY THE NATIONAL FIRE CODE AND THE LOCAL AUTHORITY. PROVIDE DEDICATED WALL SLEEVES, MINIMUM 3/4" EMT CONDUIT, WITH UL APPROVED PLIABLE FIRE STOPPING.

THE SYSTEM SHALL INCLUDE ALL DEVICES AS SHOWN ON THE DRAWINGS, AND ANY OTHER APPURTENANCES NECESSARY FOR A COMPLETE AND OPERATIONAL SYSTEM AS DESCRIBED IN THE DRAWING SET AND THIS SPECIFICATION.

CONTRACTOR SHALL SUBCONTRACT TO THE FIRE ALARM SYSTEM MANUFACTURER FOR PROGRAMMING AND FINAL SYSTEM CHECKOUT AND TEST.

EACH AND ALL ITEMS OF THE FIRE ALARM SYSTEM SHALL BE LISTED AS A PRODUCT OF A SINGLE FIRE ALARM SYSTEM MANUFACTURER UNDER THE APPROPRIATE CATEGORY BY UNDERWRITERS LABORATORIES, INC. (UL) AND SHALL BEAR THE "UL" LABEL. ALL CONTROL EQUIPMENT IS TO BE LISTED UNDER UL CATEGORY U012 AS A SINGLE CONTROL UNIT. PARTIAL LISTING SHALL NOT BE ACCEPTABLE.

IN ADDITION TO SHOP DRAWING REQUIREMENTS NOTED ELSEWHERE FOR THIS PROJECT, THE CONTRACTOR SHALL BLOCK DIAGRAMS SHOWING THE TYPES AND ARRANGEMENT OF CONNECTIONS AMONG THE COMPONENTS INCLUDING CABLE TYPES, TABULATIONS VERIFYING THE EXTRA POWER CAPACITY REQUIRED (BATTERY CALCULATIONS) FOR FIRE ALARM CONTROL PANELS AND EXTENDER PANELS. SHOW TABULATIONS FOR POINTS AND POWER SUPPLIES.

WHEN THE INSTALLATION IS COMPLETE, IT SHALL BE TESTED BY A REPRESENTATIVE OF THE MANUFACTURER, THE LOCAL FIRE MARSHAL AND OWNER'S REPRESENTATIVE SHALL BE INVITED TO ATTEND THE TESTING. WHEN THE MANUFACTURER'S REPRESENTATIVE HAS VERIFIED THAT THE SYSTEM IS COMPLETE AND OPERATING PROPERLY, HE SHALL PROVIDE THE OWNER WRITTEN CERTIFICATION STATING THE SYSTEM HAS BEEN TESTED AND VERIFIED FOR PROPER OPERATIONS.

EXECUTION

MATERIALS AND EQUIPMENT SHALL BE INSTALLED IN ACCORDANCE WITH REQUIREMENTS INDICATED, THE APPROVED RECOMMENDATIONS OF THE MANUFACTURERS AND NFPA 70. THE INSTALLATION SHALL BE ACCOMPLISHED BY WORKERS SKILLED IN THIS TYPE OF WORK AND SHALL BE DONE IN ACCORDANCE WITH THE BEST PRACTICE OF THE TRADES.

INSTALLATION SHALL CONFORM TO ALL LOCAL CODES AND INDUSTRY STANDARDS. THE CODE OR STANDARD THAT IS MORE STRINGENT SHALL APPLY.

THE CONTRACTOR SHALL DELIVER A COMPLETE AND OPERATIONAL SYSTEM. THE CONTRACTOR SHALL EXAMINE THE DESIGN DOCUMENTS AND PROJECT SITE THOROUGHLY. ANY WORK NOT INCLUDED ON THE DRAWINGS, BUT NECESSARY TO DELIVER A COMPLETE SYSTEM SHALL BE PROVIDED BY THE CONTRACTOR WITHOUT ADDITIONAL COST TO OWNER.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR REVIEWING ARCHITECTURAL AND MECHANICAL DRAWINGS FOR IMPACT ON ELECTRICAL INSTALLATIONS.

THE CONTRACTOR SHALL COMPLY WITH OSHA 191.150 "LOCKOUT AND TAGOUT PROCEDURE".

INSTALLATIONS ARE NOT COMPLETE UNTIL TESTED AND OPERATIONAL. GREEN CARDS, WHEN REQUIRED, MUST BE SIGNED AND APPROVED. PROVIDE NEW TYPED PANEL DIRECTORIES FOR EACH PANEL FURNISH/MODIFIED UNDER THIS PROJECT INCORPORATING DESCRIPTIVE INFORMATION FOR EACH NEW/EXISTING LOAD.

FIELD TESTING

PHASE ROTATION TESTS SHALL BE CONDUCTED ON ALL THREE-PHASE CIRCUITS USING ROTATION INDICATING INSTRUMENT. THE PHASE ROTATION OF ELECTRICAL CONNECTIONS TO ALL CONNECTED EQUIPMENT SHALL BE CLOCKWISE.

ELECTRICAL PROTECTIVE DEVICES SHALL BE TESTED TO DEMONSTRATE PROPER CHARACTERISTICS.

UPON COMPLETION OF THE ELECTRICAL WORK, AND AT SUCH TIME AS THE OWNER'S REPRESENTATIVE MAY DIRECT, AN OPERATING TEST OF THE ELECTRICAL SYSTEMS SHALL BE CONDUCTED. ALL ELECTRICAL EQUIPMENT SHALL BE DEMONSTRATED TO OPERATE IN ACCORDANCE WITH THE REQUIREMENTS SPECIFIED AND INDICATED.

AS-BUILT DRAWINGS

THE CONTRACTOR SHALL COORDINATE ALL FIELD CHANGES AND MAINTAIN A SET OF RECORD PRINTS DURING CONSTRUCTION. HE SHALL RECORD ON THESE PRINTS ALL DEVIATIONS FROM THE CONTRACT DRAWINGS IN CONDUIT SIZING, FEEDER SIZES, BREAKERS SIZES, LIGHTING, EQUIPMENT AND CONDUIT LOCATIONS, ETC. AT THE COMPLETION OF WORK, THE CONTRACTOR SHALL INCORPORATE THE CHANGES INTO AN ELECTRONIC CADREVIEW SET OF DOCUMENTS AND PROVIDE THE OWNER WITH BOTH A HARD COPY AND DIGITAL COPY OF THE REVISED DRAWINGS NOTED ON EACH SHEET WITH "AS-BUILT DRAWINGS".

CERTIFICATE OF APPROVAL

OBTAIN AND DELIVER A FINAL CERTIFICATE OF APPROVAL FROM THE APPLICABLE NEC INSPECTION AUTHORITY HAVING JURISDICTION. THE ELECTRICAL CONTRACTOR SHALL PAY ALL CHARGES MADE BY THE INSPECTION AUTHORITY AND TURN OVER CERTIFICATE TO THE ARCHITECT AT THE TIME OF SUBSTANTIAL COMPLETION.

GUARANTEE

THE CONTRACTOR SHALL UNCONDITIONALLY GUARANTEE HIS MATERIAL AND LABOR FOR A PERIOD OF ONE YEAR AFTER BUILDING ACCEPTANCE BY OWNER.