

UPS5000-E Series

(50-800kVA)

Introduction

UPS5000-E Series (50-800kVA) is an advanced modular UPS based on Huawei's extensive experience in digital technology and power electronics. Benefiting from high performance DSP and high speed communication technology, the UPS5000-E system achieves leading expandability and availability. Its high efficiency, high availability match the requirements of cloud data center perfectly.

Scenarios

- Data centers in headquarter or disaster recovery data centers
- Internet data centers
- Large cloud computing data centers

Features

Reliable

- 138-485Vac ultra-wide input voltage range, suitable for the worst power grid
- Redundant design for modules, elimination of the single point of failure
- iPower pre-warnings for key components in case of power supply interruption

Efficient

- High efficiency up to 95%-96% at most frequently-used load rate
- Intelligent hibernation technology ensures efficient UPS operation
- Single UPS capacity up to 800kVA, 50% footprint saving, more IT rack space

Simple

- Hot swappable power module, bypass module and control module, simple maintenance and expansion in 5 minutes
- iPower real time monitoring system for UPS, PDU and batteries, elimination of manual routing inspection



UPS5000-E-200/300K



UPS5000-E-400/500K

Specifications

Model		UPS5000-E-200K	UPS5000-E-300K	UPS5000-E-400K	UPS5000-E-500K	UPS5000-E-600K	UPS5000-E-800K
Rated Capacity (kVA/kW)		50-200	50-300	50-400	50-500	50-600	50-800
Number of Power Modules		1-4	1-6	1-8	1-10	1-12	1-16
Mains Input	Input Wiring	3Ph+PE (Neutral wire: optional*)					
	Rated Voltage	380/400/415Vac					
	Voltage Range	138-485Vac (305-485Vac for 100% load; 138-305Vac for 40%-100% load)					
	Frequency Range	40-70Hz					
	Total Harmonic Distortion	THDi<3% for 100% linear load					
	Input Power Factor	0.99					
Bypass Input	Rated Voltage	380/400/415Vac					
	Input Frequency	50/60±6Hz					
Battery	Rated Voltage	360-528Vdc (The number of batteries can be selected from 30 to 44; 40 batteries in default)					
Output	Output Wiring	3Ph+N+PE					
	Voltage	380/400/415Vac±1%					
	Frequency	Tracking the bypass input (Normal mode); 50/60Hz±0.05% (Battery mode)					
	Waveform	Sine wave (THDv<1% for linear load)					
	Overload Capacity	Inverter: 110% overload for 60 minutes; 125% overload for 10 minutes; 150% overload for 1 minute					
System	Output Power Factor	1					
	Efficiency	Up to 96%					
	Expandability	8					
Environment	Operating Temperature	0-40°C					
	Storage Temperature	-40 to 70°C					
	Relative Humidity	0%-95% (No condensing)					
	Operating Altitude	0-1000m. Above 1000m, derating rate based on EN/IEC 62040-3					
	Audible Noise	66-75dB					
Others	Height × Width × Depth (mm)	2000 × 600 × 850		2000 × 1200 × 850		2000 × 1400 × 850	2000 × 2400 × 850
	Weight	285~390kg	275~450kg	465~710kg	515~830kg	705~1090kg	1075~1540kg
	Certifications	EN/IEC 62040-1; EN/IEC 62040-2; EN/IEC 62040-3; CE; CB; RoHS, REACH, WEEE, etc.					
	Communications	Dry contacts, RS485, SNMP					

* Without neutral wire, it's TN-C system.

Notice:

1. The UPS series are for commercial/industrial use and not used for life support equipment;
2. The critical systems concerning economic and public security must adopt power supply architecture that comply with Uptime TIER III or TIER IV requirements stated in TIA942.