

L1 PRO8		L1 PRO16	L1 PRO32 + SUB1	L1 PRO32 + SUB2
Loudspeaker Type	8 x articulated cricket drivers w/ integrated 7" x 13" racetrack transducer	16 x articulated cricket drivers w/ integrated 10" x 13" neodymium racetrack transducer	32 x articulated cricket drivers w/ modular 7" x 13" racetrack transducer	32 x articulated cricket drivers w/ modular 10" x 18" neodymium racetrack transducer
Max SPL	112 dB (cont.) /18 dB (peak)	118 dB (cont.) /24 dB (peak)	117 dB (cont.) /23 dB (peak)	122 dB (cont.) /28 dB (peak)
Low-Frequency Coverage	45 Hz 180° H x +/-30° V	42 Hz 180° H x +/-30° V	40 Hz 180° H x 0° V	37 Hz 180° H x 0° V
Vertical Beam Type	C-shape	J-shape	J-shape	Straight-s-shape
Amplifier Design	Class D, 60W mid-high array + 240W sub	Class D, 250W mid-high array + 1000W sub	Class D, 480W mid-high array + 1000W sub	Class D, 480W mid-high array + 1000W sub
Onboard Mixer			3 channel	
Inputs				
Channel 1 and 2 Input Type		Combination XLR or 1/4" TRS connector (mic/instrument/line)		
Channel 1 and 2 Features		Volume, Treble, Bass, Reverb, Mute, Phantom power, ToneMatch presets		
Channel 3 Input Type		1/8" TRS (stereo-summed, line), 1/4" TRS (line), Bluetooth audio streaming (AAC)		
Channel 3 Features		Volume, Treble, Bass, Mute		
Phantom Power	Yes	Yes	Yes	Yes
Bluetooth Streaming	Yes	Yes	Yes	Yes
SUB1 SUB2 Inputs				
Channel 1 and 2 Type	Not applicable	Not applicable	Not applicable	Combination XLR or 1/4" TRS connector (line)
Outputs				SubMatch in
Line Out		XLR connector (full frequency bandwidth)		
ToneMatch Port		Compatible with Bose T4S and T8S Mixer		
SubMatch Connection	Not applicable	Not applicable	Not applicable	Yes, cable included
SUB1 SUB2 Outputs				2 x XLR connector (full frequency bandwidth)
Line Outputs	Not applicable	Not applicable	Not applicable	SubMatch thru
System Control				Yes
Onboard				
Wireless			Yes, via L1 Mix app over Bluetooth LE connection	
Other				
System Includes	1 x mid-high array 1 x array extension Subwoofer power stand AC power cord Carry bag	1 x mid-high array 1 x array extension Subwoofer power stand AC power cord Carry bag	2 x mid-high array Sub1 SubMatch cable AC power cord Carry bags Slip cover	2 x mid-high array Sub2 SubMatch cable AC power cord Carry bags Slip cover
Dimensions (H x W x D)	200.5 x 31.8 x 44 cm (78.9 x 12.5 x 17.3 in)	201.2 x 35.5 x 45.6 cm (79.2 x 14.0 x 18.0 in)	L1 PRO32: 213.5 x 34.5 x 55 cm (84.1 x 13.6 x 21.7 in)	SUB1: 53.0 x 25.0 x 53.0 cm 20.9 x 9.8 x 20.9 in
Net Weight	18 kg (39.8 lb)	24.8 kg (54.8 lb)	L1 PRO32: 13.0 kg (28.6 lb)	SUB2: 23.4 kg (51.7 lb)