

**Spex•Crete™ Commercial Underlayments Product Benefits - 1/2023**

- Spex•Crete™ 350 Super Set**
- Ultra Lightweight 35 pcf, Fast Setting, Great for Deep Fill
  - Pumps Easily at Wide Ranges of Thicknesses and Distances
  - All-In-One; Just Add Water
  - Unsurpassed Yield Per Truck, Up to ~15,960 sq ft at 1”
  - ~ 40% Labor and Logistics Savings
- Spex•Crete™ 70 SLU**
- Lightweight 75 pcf Self Leveler That is Pumpable
  - Single Pass System
  - Labor/Cost Savings Provides Increased Profit per Job
  - High Strength (~4,000 psi); Superior Surface Profile
- Spex•Crete™ 5000 W SLU**
- Wear Surface
  - Shrinkage Compensated
  - Self Curing
  - Water Resistant
  - Excellent Compressive Strengths >6,500 psi!
- Spex•Crete™ 5000 SLU**
- Fast Setting
  - Smooth Finish
  - Shrinkage Compensated
  - Pumpable
  - Excellent Compressive Strengths >5,000 psi
- Spex•Crete™ WB Bonding Agent**
- VOC Compliant
  - Water Based Bonding Agent
  - Not Affected by Alkalinity of Portland Cement
  - Ready to Use – No Site Dilution Needed
  - Bonds to New or Old Concrete, Wood, Gypsum
- Spex•Crete™ G5 LWA**
- Lightweight Sand Replacement
  - Makes Pumpable Lightweight Self Levelers
  - Helps With Excellent Compressive Strengths
  - Provides Superior Surface Profile
  - Non-Toxic, Low Dust
- Spex•Lite® 6724 LWA**
- Proprietary Modified EPS Bead
  - Mix With Portland Cement / Binders to Reduce Density
  - Little To No Dust, No Silicosis
  - Ultra Low Bulk Density; - 80x Lighter Than Sand

\*One or more of the above products are covered by issued and/or pending US patents.