

| Product | Benefits |
|---|--|
| Spex•Crete™ 350 Super Set Ultra Lightweight Deep Fill Leveler | -All In One Pumpable Replacement of Foam Board -Improved Adhesion, PSI, Working Time, Set Time -Up to 40% Labor and Logistics Savings |
| Spex•Crete™ 70 Al1 Lightweight Self Leveler | -Lightweight Single Pass Pumpable Leveler -70-75 pcf; >4,000 psi -8,000 Square Feet Yield at 1" per Truck |
| Spex•Crete™ 5000 W Wear Surface Leveler | -Wear Surface Leveler; Presanded -High Strength; >6,500 psi -Water Resistance, Radiant Floor Compatible |
| Spex•Crete [™] WBBA Water Based Primer | -VOC Compliant; Coat Up to 7 Days after Application -Ready to Use – No Site Dilution -Bonds to New or Old Concrete, Wood, Gypsum |
| Spex•Lite [®] 6724 EPS | -FR Modified EPS Bead -Ultra Lightweight Bead Compatible with Portland -Little to No Dust; No Silicosis |
| Spex•Crete™ G5 LWA | -Lightweight Sand Replacement -Makes Pumpable Levelers with Smooth Surfaces -Non-Toxic, Low Dust |

One or more of these products is covered by issued and/or pending US patents.

440-462-1500 info@SpexCrete.com



29299 Clemens Rd #1-L Westlake, OH 44145