KIT MAPS MANUAL

THE DEVICE OFFERS A SET OF 5 PERFORMANCE MODES, STORM, EASY-RIDER, ROAD, FREEDOM AND ANARCHY.

THERE IS ALSO 5 DIFFERENT ENGINE MAPPING OPTIONS (A B C D E) FOR THIS GROUP OF MODES.

Map A is the default setting for the device and is the most suitable for motorcycles with 107-114-117 engine or stage 1.

Maps B C D E may be necessary for motorcycles with the 103-110 engine or with non-original engine stage 2, stage 3, stage 4, kits or with ECM already modified with non-original devices.

These map options decrease accelerator response slightly so that B is less responsive than A, C less responsive than B and so on.

The device will be delivered with the default group A. To switch to another map follow the instructions below.

(When you receive the device is ready for installation and does not require any settings)

KIT MAPS MANUAL Instructions for changing the maps

Position A anarchy





MAP A (Default)

- Position the SALVAHD R-BY-W switch in position A (Anarchy)
 - Twist accelerator to full throttle
- Turn the key and injection button ON (engine off)
 - Wait 15 seconds
 - Position key and injection button OFF

Map A is ready

Position B freedom



MAP B (Default)

- Position the SALVAHD R-BY-W switch in position B (freedom)
 - Twist accelerator to full throttle
- Turn the key and injection button ON (engine off)
 - Wait 15 seconds
 - Position key and injection button OFF

Map B is ready

Position C road



MAP C (Default)

- Position the SALVAHD R-BY-W switch in position C (road)
 - Twist accelerator to full throttle
- Turn the key and injection button ON (engine off)
 - Wait 15 seconds
 - Position key and injection button OFF

Map C is ready

Position Deasy rider



MAP D (Default)

- Position the SALVAHD R-BY-W switch in position D (easy rider)
 - Twist accelerator to full throttle
- Turn the key and injection button ON (engine off)
 - Wait 15 seconds
 - Position key and injection button OFF

Map D is ready

Position E storm



MAP E (Default)

- Position the SALVAHD R-BY-W switch in position E (storm)
 - Twist accelerator to full throttle
- Turn the key and injection button ON (engine off)
 - Wait 15 seconds
 - Position key and injection button OFF

Map E is ready