

# ANTAEUS MODEL 100-53

## TIER 4 TECHNOLOGY



**Comes with hydraulic trip and US style guides not shown.**



## MODEL D100-42 (10.0 metric ton ram)

### SPECIFICATIONS

Stroke at maximum rated energy	135 in (343 cm)
Maximum rated energy (Setting 4)	248,063 ft-lbs (334.88 kNm)
Setting 3	220,776 ft-lbs (298.05 kNm)
Setting 2	191,008 ft-lbs (257.86 kNm)
Minimum rated energy (Setting 1)	158,760 ft-lbs (214.33 kNm)
<i>(Variable throttle allows for infinite fuel settings)</i>	

Maximum obtainable stroke	150 in (381 cm)
Maximum obtainable energy	288,488 ft-lbs (391 kNm)
Speed (blows per minute)	34-53

### WEIGHTS

Piston	22,050 lbs (10,000 kg)
Anvil	4,670 lbs (2,118 kg)
Anvil cross sectional area	482.8 in <sup>2</sup> (3114.83 cm <sup>2</sup> )
Hammer weight (includes hydraulic trip device)	47,000 lbs (21,318 kg)
Typical operating (weight with offshore leader)	Consult Factory

### CAPACITIES

Fuel tank (runs on diesel or bio-diesel)	40.3 gal (153 liters)
Oil tank	8.3 gal (31.5 liters)

### CONSUMPTION

Diesel or Bio-diesel fuel	7.8 gal/hr (30 liters/hr)
Lubrication	0.67 gal/hr (2.5 liters/hr)
Grease	8 to 10 pumps every 20 minutes of operation time.

### STRIKER PLATE

Weight	1,036 lbs (470 kg)
Diameter	25 in (57.15 cm)
Area	491 in <sup>2</sup> (3167.74 cm <sup>2</sup> )
Thickness	8 in (20.32 cm)

### CUSHION MATERIAL

Type/Qty	Micarta / 2 each
Diameter	25 in (57.15 cm)
Thickness	1 in (25.4 mm)

Type/Qty	Aluminum / 3 each
Thickness	1/2 in (12.7 mm)
Diameter	25 in (57.15 cm)
Total Combined Thickness	3.5 in (8.89 cm)
Area	491 in <sup>2</sup> (3167.74 cm <sup>2</sup> )
Elastic-modulus	285 ksi (1,965 mpa)
Coeff. of restitution	0.8

### STANDARD OFFSHORE LEADER

<b>48, 54, &amp; 66 inch available</b>	Consult Factory
--	-----------------

### MINIMUM BOX LEAD SIZE/OPERATING LENGTH

Minimum box leader size	8 in x 37 in (20.32 cm x 94 cm)
Operating length for offshore leader	396 in (1005.84 cm)

# 206-495-7030

[www.antaesususa.com](http://www.antaesususa.com)

