



VIBRATORY DRIVER / EXTRACTOR

ZEUS 600



554 US TONS
DRIVE FORCE
5,432 kN

21,000 IN-LB
ECCENTRIC MOMENT
242 kg-m

351 US TONS
MAX LINE PULL
3,123 kN

DRIVE PERFORMANCE	US	METRIC
Eccentric moment	21,000 in-lb	242 kg-m
Drive force	554 US tons	5,432 kN
Frequency	0-1,350 VPM	
Maximum line pull	351 US tons	3,123 kN

DIMENSIONS	US	METRIC
Throat width	40 in	101.6 cm
Length	180 in	457 cm
Height without clamp	104.5 in	265 cm

OPERATING WEIGHT	US	METRIC
Vibro without clamps	48,500 lb	21,999 kg
17-ft quad clamp	75,700 lb	34,336 kg
13-ft quad clamp	67,400 lb	30,572 kg
11-ft quad clamp	61,600 lb	27,941 kg

OTHER CLAMP CONFIGURATIONS
Single beam / two clamps or sheet clamp:
consult factory for operating weight.

POWER SYSTEM

800 HP HYDRAULIC POWER UNIT

- TIER 4 / STAGE 5 C18
- UPDRIVE™
- FULL FORWARD / REVERSE
- SPARE HYDRAULIC TANK



ENGINE & HYDRAULICS	US	METRIC
Engine	Tier 4 / Stage 5 C18	
Rated output	800 HP	597 kW
Engine speed	1,800 RPM + UPDRIVE™	
Drive pressure	4,500 PSI	310 bar
Drive flow	231 GPM	874 LPM
Clamp pressure	4,800 PSI	331 bar
Clamp flow	10 GPM	38 LPM

SIZE, WEIGHT & CAPACITY	US	METRIC
Operating weight	23,900 lb	10,840 kg
Length	185 in	470 cm
Width	81.5 in	207 cm
Height	95 in	241 cm
Hydraulic reservoir	800 gal	3,028 L
Spare reservoir	55 gal	208 L
Fuel capacity	150 gal	567 L