

PROYETORES DE JARDIN

Item No.	Picture	Description	
MY-S-G		Solar lamp, ABS, 5.5v, 1.2watts, battery 3.7v 1500mAh lithium, 8-10hrs, 1800-2200K CCT	
HD366		Garden lamp, 85-265V, 6Watts, RGB, remote control, aluminum body, IP54	
HD2530		5W LED Garden Light, With Spike, Black Body, WW, D60MM, 85-265V	
HD2531		5W LED Garden Light, With Spike, Black Body, WW, D60MM, 85-265V	
2506		LED Garden Light: COB7W, AC85-265V, 50/60Hz, IP65, D85*H100mm, Black Body, WW 7Watts 3000K	
HDCD223		Tree lamp, 65*260*260mm, LED COB 10W*1, BridgeLux chips Die casting aluminum body +toughened glass IP:65	
HDF-65-5		D65mm-COB 5W, AC85-265V, aluminium ROUND BASE AND STICK	
HDF-90-10		D90mm-COB 10W, AC85-265V, aluminium ROUND BASE AND STICK	
HDF-108-15		D108mm-COB 15W, AC85-265V, aluminium ROUND BASE AND STICK	

HDF-145-20		D145mm-COB 20W, AC85-265V, aluminium ROUND BASE AND STICK	
CD19C-6W		Voltage : 85-265V 50/60Hz Power : COB 6W*1 CRI: 75-80Ra IP65 Size:φ145*H430mm LED: Epistar	
CD19C-9W		Power : COB 9W*1 Size:φ145*H430mm LED: Epistar	
CD19C-12W		Power : COB 12W*1 Size:φ145*H430mm LED: Epistar	
CD19C-15W		Power : COB 15W*1 Size:φ145*H430mm LED: Epistar	
CD19C-18W		Power : COB 18W*1 Size:φ145*H430mm LED: Epistar	
VV285		Garden lamp, 50watts 3000K, 85-265v	
HDK2503		LED Spike Light: COB5W, AC85-265V, 50/60Hz, IP65, WW. With Spike.	
HDMR2503		Spike casing MR16, D60xH77mm	
K-2501		LED Spike Light: COB3W, AC85-265V, 50/60Hz, IP65, WW. With Spike.	
DF-S02		garden light φ45*H80mm LED 2W*1	
HDS0502		Solar lamp, w/spike, 5 V/2W of solar panels, 3.7 V/2000mAh 18650# Lithium battery, 6 horas.	


30147		Name:Spot Light IP: 65 Rated Power :1*13W Dimension : Φ80*205*350mm Chip: CREE CCT:3000K Beam Angle: 23° Input Voltage: 100-240VAC Driver : Internal Housing: Aluminum Color : Black	
30129		Name: Spot Light IP: 65 Rated Power : 20W Dimension :Φ102*210 Chip: CREE CCT:3000K Beam Angle: 23° Input Voltage: 100-240VAC Driver : Internal Housing: Aluminum Color : BLACK	
30132		Name:Spot Light IP: 65 Rated Power :1*3W Dimension : Φ44*100*288 mm Chip: CREE CCT:3000K Beam Angle: 25° Input Voltage: 100-240VAC Driver : Internal Housing: Aluminum Color : Silver with sand	
DECP-5W-A		Outdoor LED Spotlight, 5W, 3000K, DC12-24V	
TMDM-Y1W-A		SUBACUATICA 1WATT CREE DC12-24 2700/3000k	
TMXD3WA		SUBACUATICA 3WATT CREE DC12-24 2700/3000k	
TMDM-3W-B		SUBACUATICA 3WATT CREE DC12-24 2700/3000k	
50185		Wall Light. IP: 65 Rated Power: 1*5W. Chip: CREE Dimension : Φ90*162mm, CCT:3000K Beam Angle:1 BEAM. Voltage: 100-240VAC, Cut-out: Φ85. Housing: Aluminum	
50136		Name:Wall Light IP:54 Rated Power :1*3W Dimension :75*75*68 mm Chip: CREE CCT:3000K Beam Angle: 30° Input Voltage: 100-240VAC Driver : external Housing: aluminum Color : Silver with sand	

60715-RGBW		Name: Underwater Light IP: 68 Rated Power : 1*4W Dimension :Φ50*77mm Chip: CREE CCT:RGBW Beam Angle: 40 Degree Input Voltage: 24VDC Driver :internal,with power supply,without controller Housing: SS316 Color: SUS Cut-out: Φ63 Cable Length:30m	
60701-RGBW		Name: Underwater Light IP: 68 Rated Power : 3*4W Dimension :Φ120*115mm Chip: CREE CCT:RGBW Beam Angle: 40 Degree Input Voltage: 24VDC Driver :internal,with power supply Housing: SS316 Color: SUS Cut-out: Φ125 Cable Length: 1.5m	
60119		Name: Underwater Light IP: 68 Rated Power : 3*2W Dimension :Φ95*116 Chip: CREE CCT:3000K Beam Angle: 25° Cut-out: Φ85 Input Voltage: 24VDC Driver : Internal Housing: Stainless steel#316 Color : SUS	
HD2812		7W LED underground Light, isolated driver, SS+Aluminum, angle of light 24 degrees, D110*90mm, 2700K y 3000K, IP65, AC85-265V/DP	
HDGX1816	 型号/Model : GX-1816	D65mm-3W-AC85-265V, 3000K, IP68, STAINLESS STEEL	
HDGX1817		D80mm-3W-AC85-265V, 3000K, IP68, STAINLESS STEEL	
HDDM3019SC		D42mm*H70mm-3W-COB-304Ss -AC85-265V, 3000K, IP68, STAINLESS STEEL	
HD3019XS		D32*H60mm, Cutting 28.5*63mm, LED 1W*1, DC24V, Bridgelux chip, 3000K, 304 Stainless Steel, IP68	

HD-DM3019M		1W 3000K, DE PISO SS304, BRIDGESTAR CHIP, IP67	
DF-DM1030		Power: 1W*1 Size: ø65*80mm LED: Epistar Material: 304ss Voltage: 12V	
DF-DM1031		Power: 1W*3 Size: ø80*75mm LED: Epistar Material: 304ss Voltage: 12V	
DF-DM1061		Power: COB 5W*1 Size: ø120*110mm LED: Epistar Material: 304ss Voltage: 12V	
DF-DM8001		Power: 1W*3 Size: ø100*90mm LED: Epistar Voltage: 12V	
11303/4		Name: Inground Light IP: 67 Rated Power : 1*3W Dimension :Φ59*95 mm Chip: CREE CCT:3000K Beam Angle: 1 BEAM 2 BEAMS Input Voltage: 100-240VAC Driver :internal Housing: Aluminum Color : Grey with silver	
11303 brass		Inground Light IP: 67 Rated Power : 1*3W Dimension :Φ59*95 mm Chip: CREE CCT:3000K Beam Angle: 1 BEAM Input Voltage: 100-240VAC Driver :internal Housing: Aluminum Color : Brass Cut-out: Φ63 Cable Length: 3.0mt"□	
HDDM3023/L-IT		ACERO INOXIDABLE SS304, 62X100MM 3WX1, BRIDGESTAR 85/265V IP65	
HDDM130		D130*H140mm, LED COB 10W ,85-265V, Bridgelux , ILUMINACION LATERAL	

SS30RGBA		30W RGB Tree Light 120V	
KD-UG018-1		empotrable, control remoto , 18 Watts, RGB IP67	
HD10090W5		WATERPROOF, D100XH90, STAINLESS STEEL, COB 3000K 5WATTS, 110V	
HD-DM120-7C		D120*H90mm, LED COB 7W*1, AC85-265V, Bridgelux chip, 201SS+die casting aluminium +tempering glass, 2700K	
HD-DM160-15C		D160*H90mm, LED COB 15W*1, AC85-265V, Bridgelux chip,201SS+die casting aluminium +tempering glass, 2700K	
HD-DM180-20C		D180*H90mm, LED COB 20W*1, AC85- 265V, Bridgelux chip,201SS+die casting aluminium +tempering glass, 2700K	
HD-DM220-30C		D220*H90mm, LED COB 30W*1, AC85-265V, Bridgelux chip,201SS+die casting aluminium +tempering glass, 2700K	
SS6RGBUW		STAINLESS STEEL 6W RGB UNDERWATER 24V	

HSDTG80-3W		STAINLESS STEEL 3W 3000K UNDERWATER 82mmX120mm 12V	
RF-SD85-3W		LED Underwater Fountain light 1. Unit Size: Φ85*H125mm 2. Light:3pcs 1W leds 3. Voltage:12VAC 4. Power:3W 5.Color:3000K 6. IP :IP68 7.Material:3104SS+2M cable	
RF-SD95-6W		LED Underwater Fountain light 1. Unit Size: Φ95*H130mm 2. Light:3pcs 2W leds 3. Voltage:12VAC 4. Power:6W 5.Color:3000K 6. IP :IP68 7,Material:3104SS+2M cable	
HDFL50		New ETL IP65 LED flood light 50w 130lm/w, 100-277v,4000k60*120°,ra>70,5 years warranty with bracket	
HDFL100		ETL IP65 LED flood light 100w 130lm/w, 100-277v, 5000k 60*120°, ra>70, 5 years	
HDFL150		ETL led knuckle flood light 150w ,135lm/w 100-277v ,hidden photo sensor, 5000k, 60*120°,ra>70	
PRO/100		outdoor projector 100 watts, IP65, new flat	
PRO/50		outdoor projector 50 watts, IP65, new flat	
PRO/30		outdoor projector 30 watts, IP65, new flat	
PRO/20		outdoor projector 20 watts, IP65 , new flat	
PRO/10		outdoor projector 10 watts, IP65, new flat	
PRO/20/R.B.G.		outdoor projector 20 watts R,B,G	
PRO/30/R.B.G.		outdoor projector 30 watts R,B,G	
PRO/20/RGB		outdoor projector 20 watts RGB	
PRO30/RGB		outdoor projector 30 watts RGB	

HDPR30		Proyector 30W, 36chips, 85-265v, PF 0.9, IP65, 291g, 6000K, 149*125*39.5	
HDPR50		Proyector 50W, 60chips, 85-265v, PF 0.9, IP65, 2426g, 6000K, 190*156*39.5	
HDPR100		Proyector 100W, 162chips, 85-265v, PF 0.9, IP65, 606g, 6000K, 228*185*39.5	
HDPR150		Proyector 150W, 180chips, 85-265v, PF 0.9, IP65, 906g, 6000K, 294*220*39.5	
HDPR200		Proyector 200W, 288chips, 85-265v, PF 0.9, IP65, 6000K, 1266g, 330*251*40	
HDPR300		Proyector 300W, 360chips, 85-265v, PF 0.9, IP65, 6000K, 1564g, 370*280*39.5	
HDTG120650		Input Voltage: 85-265V/AC WATTS:50W 50-60Hz, CRI>80, Surge: 4KV Lumens: >120 lm/w, PF>0.95 Material: Alumiumm	
HDTG1206100		Input Voltage: 85-265V/AC WATTS:100W 50-60Hz, CRI>80, Surge: 4KV Lumens: >120 lm/w, PF>0.95 Material: Alumiumm	
HDXJD50		Proyector lineal, 50watts, NEGRO, IP65, 85-265V, Aluminum	
FLHL40W		ETL smart ip66 led floodlight 40w 95lm/w, RGB+CCT(2700K-6500K), RA>80, and music color changing with USA plug WIFI	
HDFLHL100		etl Tuya/smart life app wifi smart ip66 led floodlight 100w 120lm/w, RGB+CCT(2700K-6500K), RA>80 ,5 years warranty ,working with alexa and google assitant, and music color changing	

HDSW034		PARA FUENTE, 6 WATTS, 2700K, STAINLESS STEEL COVER, ALUMINUM BODY, AC/DC:12/24V, 130mmX85mm	
3201		25W LED Swimming Pool Light,AC12V, RGB, Remote Control	
3202		35W LED Swimming Pool Light,AC12V,WW	
wall washer		wall washer 3000K 18watts	
wall washer		wall washer RGB 18watts	
HDANP50		LAMPARA ARBOTANTE EXTERIOR 50 WATTS, FOTOSENSOR ETL NOM	

BRONZE GARDEN

Item No.	Picture	Description	
LT2703		3W, 7", Casting Aluminium, 2700K, 300lm, Waterproof 9-17V AC/DC	
LT2404		Die-cast brass, Antique Bronze, G4 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	
LT2411		Die-cast brass, Antique Bronze, G4 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire,mini hat	
LT2405		Die-cast brass, Antique Bronze, G4 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	
HDP003B		Body: Solid brass, Wire: 3'SPT-2W 8AWG/2C Color: Antique Bronze, Socket and Stake included, No lamp included, 10 sets/carton	
HD2801		UNDERWATER LAMP, Die-cast brass, antique bronze, for MR16, 72" (1.8 meters) Spt-1W 18 gauge lead wire	
HDJXU001 B		Solid cast brass body, water tight seal, IP68, Clear tempered clear glass, Low voltage MR16 lamp holder.	
LT2302		Die-cast brass, Antique Bronze, G4 or MR16 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire Heavy duty	
LT2202B		PVC&Solid brass, Antique Bronze, MR16 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	

LT2203A		PVC&Solid brass,Antique Bronze, MR16 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	
LT2204A		PVC&Solid brass,Antique Bronze, MR16 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	
LT2204B		PVC&Solid brass,Antique Bronze, MR16 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	
LT2204C		PVC&Solid brass,Antique Bronze, MR16 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	
LT2503		Die-cast Brass, 2W, 2700K-6000K, 240LM, 12VAC CREE chip,12V AC/DC	
LT2506L		Heavy duty Die-cast Brass,3W → 24W adjustable wattage,15° → 60° beam spread.12V AC/DC	
LT402		Brass Mounting Plate	
LT408		Photocell	
LT403		MR16 Louvre	
LT404		Brass Locknut	
HDLT2602		Die-cast brass, Antique Bronze, for MR16, 72" (1.8 meters) Spt-1W 18 gauge lead wire	
LT2101		Die-cast brass,Antique Bronze, MR16 (Lamp not included), 72" (1.8 meters) Spt-1W 18 gauge lead wire	
JXD003B		Solid brass fixture, 10'SVT/18AWG×2C wire, Socket included, MR16 holder, No lamp, Antique bronze finish	

JXF010B		Solid brass fixture, 10'SVT/18AWG×2C wire, Socket and Stake included, MR16 holder but no lamp, Antique bronze finish	
JXI007B		Solid cast brass, 10'SVT/18AWG×2C wire, Socket included, MR16 holder, No lamp, Antique bronze finish, include plastic housing.	
HDF009C		COBRE Y BRONCE SOLIDO, VIDRIO CONVEXO CON CABLE SVT/18AWGX2C 1MTL CON ESTACA MR16	

POSTES

Item No.	Picture	Description	
HD300/600		150*100*H600mm, LED 10W*1, 85/265v , 3000K, black body	
HD-1032/400H		Lawn lamp, D180*H400mm, LED SMD 18W*1, AC85-265V, 3000K, REDONDA O CUADRADA	
HD-1033/600H		Lawn lamp, D180*H600mm, LED SMD 18W*1, AC85-265V 3000K, REDONDA O CUADRADA	
76106-60cm		Garden lights 7 WATTS	
76106-40cm		Garden lights7 WATTS	
76107-60cm		Garden lights7 WATTS	

76107-40cm		Garden lights7 WATTS	
71462-60cm		Garden lights3 WATTS	
DFC-342/600H		D190*H600mm LED 5W, AC85-265V, 3000K	
DFC-348/1-600H		D50*H600mm, LED 5W*1, AC85-265V, 3000K, MOVIBLE	
DFC-346		D200*H800mm LED 10W, AC85-265V, 3000K	
HD-9011A		LAWN LAMP, D145*H800mm, LED COB 10W*1, AC85-265V, BLACK BODY, 3000K	
HD-9012A		LAWN LAMP, D145*H800mm, LED COB 10W*1, AC85-265V, BLACK BODY, 3000K	
		garden light capuchon	

DFC-1911/400H		FLOOR light $\Phi 65 \times H400\text{mm}$ LED 3W*1	
DFC-1911/700H		FLOOR light $\Phi 65 \times H600\text{mm}$ LED 3W*1	
Pole for garden light IP65 E27		12WATTS size: D170*H800 voltage:85-265v color: black Material:Alu	
Pole for garden light IP65 E27		12WATTS size: D170*H800 voltage:85-265v color: black Material:Alu	
lawn light IP65 E27		size: D65*H1000 voltage:85-265v color: black Material:Alu	
40w garden light IP65		40w size: D160*H2500mm voltage:85-265v color: black Material:Alu	

ARBORANTES PARED

Item No.	Picture	Description	
HD23180		28W LED Wall Light ,isolateted driver ,Black Body, 3000k, 1000mmX80mmX45mm, 85-265V	
HD23181		30W LED Wall Light ,isolateted driver ,Black Body, 3000k, 1200mmX80mmX45mm, 85-265V	
HD23182		36W LED Wall Light ,isolateted driver ,Black Body, 3000k, 1500mmX80mmX45mm, 85-265V	
HD23183		40W LED Wall Light ,isolateted driver ,Black Body, 3000k, 1700mmX80mmX45mm, 85-265V	
HDSC2536		Materials:Iron+Acrylic Voltage:100-240V, Power:1-3W*2pcs Led model: led (Bridgelux chips) Size: D3*H50cm, Color: Warm white, IP20	
S07		Material : iron finish:matt black power: E26*2 MAX 60W (Excluding bulb)	
50109		Wall Light IP: 54 Rated Power : 2*1W Dimension :85*60*30mm, Chip: CREE CCT:3000K Beam Angle: 90 ° Input Voltage: 100-240VAC. Housing: Aluminum	
50104		Wall Light IP: 65 Rated Power : 2*2W Dimension :Φ60*130mm, Chip: CREE CCT:3000K Beam Angle: Top 3°+Bottom 40°, Input Voltage: 100-240VAC, Housing: Aluminum	

50107		Wall Light IP: 65 Rated Power : 2-3*2W Dimension :Φ75*130mm, Chip: CREE CCT:3000K Beam Angle: 40° (Up and down), Input Voltage: 100-240VAC. Housing: Aluminum	
LS-BD-6002		1.Power:18*1W*2 3000K 2.Size:Ø160*H360 3.AC110-265V 4.IP65 5.Aluminum+Glass 6.AC110-265V Bridgelux Chips. 7.Emitting Angle:30°	
LS-BD-6003		1.Power:18W, 3000K 2.Size:L160*W160*H200 3.AC110-265V 4.IP65 5.Aluminum+Glass 6.AC110-265V Bridgelux Chips. 7.Emitting Angle:30°	
HDLT2602		Die-cast brass, Antique Bronze, for MR16, 72" (1.8 meters) Spt-1W 18 gauge lead wire	
HDB9020		1x5w size: D90*H200 voltage:85-265v color: black Material:Alu IP44	
HDB9028 - 2603		2x5w size: D90*H280 voltage:85-265v color: black Material:Alu IP44	
HD8922		ROMBOIDE 173X173MM BICOLOR ALUMINIO 5WX2 BRIDGELUX 85/265V	
1509		wall lights 4 WATTS	
6106		wall lights 7 WATTS	

HDFB2123		ARBOTANTE ECLIPSE 150mmX150mm 12Wx1	
HDFB2123B		ARBOTANTE ECLIPSE 180mmX180mm 12Wx1	
6108		wall lights 6 WATTS	
6109		wall lights 12 WATTS	
6107		wall lights 7 WATTS	
50155		Name:Wall Light IP: 65 Rated Power :1*5W Dimension : 200*160*80mm Chip: CREE CCT:3000K Beam Angle: 23° Input Voltage: 100-240VAC Driver : Internal Housing: Aluminum Color : White	
DFB-2055-2		wall light 2 vias	
DFB-2055-3		wall light 2 vias	
DFB-2076		wall light white body. 2 vias	
DFB-2018		wall light 140*145*125mm LED 5W*2	

DFB-2017		wall light 140*103*125mm LED 5W*1	
DFB-2002		160*90*55mm LED 3W*2	
DFB-2008		138*98*60mm LED 3W*2	
HDB8003		Wall lamp, 85/265v. Aluminum body D80*68*H80mm, LED COB 5W*1, IP65, 3000K	
HDDF8004		Wall lamp, 85/265v. Aluminum body, 150*68*80mm, IP65, 3000K, LED 3W*2	
DFB-8018		160*90*55mm LED 3W*2	
HDF-8613-14		1.Size:95*190*110mm 2.Wattage:5W*2, 3000K and 6500K , Bridgelux chips, black and white	

DFB-8001		80*68*H80mm LED 3W*1	
DFB-8002		150*68*H80mm LED 3W*2	
HDF809F-1		3000K, Bridgelux chip, 100*100*100mm, LED 5W*1	
HDF809F-2		3000K, Bridgelux chip, 200*100*100mm, LED 5W*2	
DFB-8064		100*88*33mm LED 3W*1	
DFB-2030		140*100*115mm LED 3W*2	
DFB-2065		165*65*115mm LED 3W*1	

HDB3009 antes 2343		Wall lamp 18watts 110V WW 235*135mm, IP 65	
HD8065		WALL LAMP, 120*145*45mm , LED COB 5W*1 AC85-265V, 3.LED: COB Bridgelux USA, 3000K, BLACK	
HD8005		WALL LAMP, 80X76X63MM, ALUMINIO, COB BRIDGELUX 1X3WATTS, 130LM/W	
HD8006		WALL LAMP, 142X80X63MM, ALUMINIO, COB BRIDGELUX 2X3WATTS, 130LM/W	
HDB-1113		courtesy lamp, 150D*35mm, LED COB 3W, AC85-265V, ROUND, 3000K, aluminum body, IP65	
HDB-1111		courtesy lamp, 150*150*35mm, LED COB 3W, AC85-265V, SQUARE, 3000K, aluminum body, IP65	
HDB-1110		courtesy lamp, 200*90*35mm, LED COB 5W, AC85-265V, SQUARE, 3000K, aluminum body, IP65	
HDB1107F antes 2312		LED Wall Light: COB2*5W, AC85-265V,50/60Hz, IP65, L100*W100*H100mm, BLACK, BROWN, GREY, WHITE, CUADRADA	
HDF1107/F12		OUTDOOR Wall lamp. 120*120*120mm, LED 10W*2, IP54	

HDF1107/F15		OUTDOOR Wall lamp. 150*150*150mm, LED 15W*2, IP54	
HDB1107Y antes 2313		LED Wall Light: COB2*5W, AC85-265V,50/60Hz, IP65, L142*W81*H63mm, Black Body, CURVA	
HD8500L		wall lamp 300*280*105mm, LED 24W*1 SMD GOLD	
HD8500L		wall lamp 300*280*105mm, LED 24W*1 SMD. BLACK	
HD8503M		wall lamp 220*65*65mm, LED 3W+3W COB, +5W SMD	
HD8503L		wall lamp 260*65*65mm,LED 3W+3W COB, +8W SMD	
HD80400		Wall lamp, 80*400mm, E27*2, black and gold color	
HD-2147/S-GD		240*60*50mm, LED COB 3W*2, AC85-265V 3000K	
HD-2147-GD		350*60*50mm, LED COB 3W*2, AC85-265V 3000K	
HD-2147/S-BK		240*60*50mm, LED COB 3W*2, AC85-265V 3000K	
HD-2147-BK		350*60*50mm, LED COB 3W*2, AC85-265V 3000K	
HDB-345		Wall Light,245*145*H100mm, LED SMD 10W*1, sanan chips,AC85-265V, Black body, 3000K	

HD2287		Ceiling wall or post lamp, 55*155*125mm, LED 12W*1 SMD , 85-265V, Sanan, 3000K, IP 44	
HDB8970-L		L300*145*145mm, LED 18W*1, AC85-265V, 3000K	
HDB8969-L		L300*145*145mm, LED 18-18W*1, AC85-265, 3000K	
MA12		MARINE LAMP, GLASS, E27, BLACK, WHITE GRILL, TAMAÑO GRANDE, NO INCLUYE FOCO	
HDFCD-E27SM		MARINE LAMP, GLASS, E27, BLACK, WHITE GRILL, TAMAÑO CHICO, 210*110*90, NO INCLUYE FOCO	
HDANP50		LAMPARA ARBOTANTE EXTERIOR 50 WATTS, FOTSENSOR ETL NOM	
HD7036		Wall lights D236*H201mm, LED 12W SMD , 85-265V, Sanan, 3000K, IP44	
HD7037		Wall lamp, D201*W296*H357mm, LED 12W ,SMD , 85-265V, Sanan, 3000K, IP 44	