

WP2-A3-200 and WP2-H3-200

## Complete system for EAL bio, lubrication, hydraulic and gear oil

The WP2-X3-XXX system is used for cleaning of EAL bio, lubrication, hydraulic and gear oil. The system removes water, soot, particles, varnish and any insolubles in the oil.

The filter system is used in the maritime business and other industries to obtain optimal operating reliability of the equipment and to extend the lifetime of oil.

## **Functions**

This is a pressurized system comprising of two pumps and motor units together with a Green-Oil filter, a built in water separator and integral return tank.

The inlet pump continuously operates and removes the particles and water. The oil is then returned to the equipment via the outlet pump. The patended water separator is unique because the oil passes through and the water is separated by heated air. The process results in removing free, dissolved and bound water without damaging the oil.

The filter insert is replaced without the use of tools, oil spill or physical contact with the oil.

Ideal for thrusters, stern tube systems and propeller applications.

## **KEY FEATURES**

- Integrated oil filter and water sepa-
- Patended water separator remov ing free, emulsified and bound water down to 30 ppm.
- Easy and quick filter change without oil spill.
- No tools required for filter replacement
- No physical contact with oil when replacing filter insert.
- A low maintenance system with many benefits.

WP2-A3-200	WP2-H3-200
200-240	200-240
1	1
6	6
0-460	0-460
110/230-50/60	110/230-50/60
750	570 + 1600
1/2	1/2
727 x 481 x 329	727 x 481 x 329
41	47
AISI 304 Stainless	AISI 304 Stainless
1 x 8	1 x 8
Option	Standard
Option	Option
Standard Local panel	Standard Local panel
	200-240  1 6 0-460 110/230-50/60 750 1/2 727 x 481 x 329 41 AISI 304 Stainless 1 x 8 Option Option



Tel: +45 87 52 00 84 Info@greenoil.dk www.greenoil.dk

