

All-in-one LED Touching Solution





High Definition



Wireless projection



Touching features




Smart Whiteboard



Video Conference



Plug&play



Multiple Interfaces



Remote Control

Appearance



Wide Color Gamut

2K/4K optional. 108" 135" 162" various sizes, easy to splice large scenes.



2K/4K resolution, more refined colors



Wide color gamut, full screen vividness



Ultra-high brightness



High contrast



Integrated design convenient maintenance


- Integrates display controls into an intelligent system.
- The design is highly simplified, eliminating complex wiring and debugging.
- The module and cabinet are connected by a wireless board-to-board connection with magnetic reinforcement, allowing for quick disassembly and full front maintenance.

Efficient and Convenient

- Compatible with leading third-party video conferencing software.
- Supports document, image, and video display for real-time data sharing.
- Enables multi-party video calls, offering an immersive, face-to-face meeting experience.



Wireless Projection with Quad-Split Screen



- Supports wireless projection and split-screen display from various devices, including mobile phones, iPads, and PCs.
- Accommodates documents, pictures, and video playback, meeting the needs of multiple viewers simultaneously.
- USB plug and play.



High-precision infrared touch technology



- Featuring high-precision infrared touch technology, the display supports 10-point multi-touch for a smooth, responsive writing experience with instantaneous display.
- The smart whiteboard function allows for effortless annotation and supports simultaneous collaboration for multiple users.



Single-point touch



Two-finger zoom



Multi-point movement




One-click clear



Smooth writing



Arbitrary annotation




Set color



Choose color and
thickness

Remote control

The remote control can realize the functions of power on and off, brightness adjustment, content switching, page up and down, menu setting, etc





Ultra-thin body

Featuring a rounded-corner, ultra-narrow bezel and an ultra-thin body, with a thickness of just 38.2mm.

Extensive interface integration for more flexible connectivity

Extensive support for all common audio and video device interfaces ensures convenient connectivity.



WIFI



USB



Network Port



HDMI



Audio

Ultra-wide viewing angle


170° ultra-wide viewing angle, immersive panoramic view



High Refresh Rate



High Refresh Rate



Low Refresh Rate

High Grey Level



High Grey Level




Low Grey Level

Installations

Wall Mount



Floor-standing Mobile Stand





Smart Pen

Writing remote control, easy operation

Integrates writing pen, page turning pen, wireless mouse, etc. in one, various functions can be operated with one button, and demonstration writing can be done in one go.



Remote Control

Powerful control, command the overall situation

Control power, brightness, and content. Switch pages and adjust menu settings with a single, precise instruction.



Wireless display dongle.

Wireless control, one-click screen projection

Wireless transmission, plug and play, no need for repeated debugging or driver installation, one-click audio and video synchronization, stable and unstuck same screen picture.



Mobile bracket

Elegant style, convenient movement

Equipped with four universal casters, this unit offers effortless mobility. Its minimalist design and premium finish blend seamlessly into any office environment, and it's built to last.

Application Scenarios

High-end conference rooms



Lecture rooms



Lecture halls




Other fields



Specification	108"	135"	162"	162"
LED Type	SMD1010/COB	SMD1010/COB	SMD1010//1515/GOB	COB
Physical Density(dots/m ²)	640000	409600	284444	1137778
Pixel Pitch	1.25mm	1.56mm	1.875mm	0.9375mm
Screen Size(without base)	2440X1456.5mm	3040X1794mm	3640X2141.5mm	3640X2141.5mm
Whole Screen Size	2440X2168mm	3040X2505.5mm	3640X2505.5mm	3640X2505.5mm
Refresh Rate(Hz)	3840	3840	3840	3840
IP Grade	IP31	IP31	IP31	IP31
Resolution(dots)	1920X1080	1920X1080	1920X1080	3840X2160
Video Interface	HDMI×3(2 input 1 output), USB3.0, USB2.0×2, RF			
Signal Interface	RJ45, USB-B, WiFi, Bluetooth, Infrared			
Audio Interface	Internal 2×5W speakers, External Audio interface			
Installation Mode	Moveable(standard) / Wall mounting(optional)/Front maintenance			
Input Power	AC90-264V,47-63Hz			
Working Temperature/Humidity(°C/RH)	-20~60°C/10%~85%			
Strage Temperature/Humidity(°C/RH)	-20~60°C/10%~85%			
Cert.	CCC/CE/RoHS/FCC/CB/TUV/IEC			

THANKS



LEDGEN

THE NEXT GENERATION OF LED