Villas West Architectural Specification

Specifications for Patio Irrigation System

Specification No: VWAS 17

Issue Date: 12/20/2005 Revision Date: 12/20/2005

Revision Level:

Board Approval Date: 12/20/2005

Page 1

General: An Architectural Alteration Application, Form No. AAA, requesting the installation of a patio irrigation system must be submitted to the Architectural Committee for review. The Architectural Committee will submit its recommendation to the Board of Directors for final approval.

Specifics:

- 1. A galvanized tee shall be threaded to the water supply pipe that is stubbed out from the patio wall.
- 2. A hose bib shall be threaded to one side of the galvanized tee
- 3. A shut off valve for the irrigation system shall be threaded into the other opening of the galvanized tee.
- 4. Threads shall be sealed with appropriate thread sealant and threaded fittings must be made up wrench tight. Either Teflon tape of paste type thread sealant may be used.
- 5. All irrigation components are to be installed to the downstream side of the shut off valve.
- 6. No irrigation emitters shall be installed to supply water to potted plant on the walls of the patio.
- 7. All emitters shall be positioned so that they do not drip on any portion of the patio or villa wall.

		_	
Owner's Signature	Date	Contractor's Signature	Date
		_	
Architectural Chairperson	Date	Association President	Date