

STONE ROBERTS DEMOLITION

DERBY

4 CYL, 6 CYL, 8 CYL

AUTOMOBILES & MINIVANS

- 1) Stock hardtop automobiles or station wagons are allowed. No electric automobiles , must be gasoline or diesel only! This includes foreign automobiles. You may use front wheel drive vehicles. No hearses, limos, ambulances, convertibles, el- caminos, chrysler imperials, or imperial sub frames.) No mini subcompacts or micro vehicles. Wheelbase of 89 inches or greater. Wheelbase is measured from center of hub to center of hub.
- 2) Motor mounts must be in stock location and cannot be relocated. Must have rubber between motor and mount. No complete engine cradles, but a simple motor mount style cradle CAN be used. NO FULL CRADLES , NO PULLEY PROTECTORS ,OR DISTRIBUTOR PROTECTORS! Nothing can be tied to the FRAME or FIREWALL! 2003 and newer crown vic,s can use smith metal works style bolt in mounting system. IF YOU ARE NOT SURE , CALL DONNY 443-309-9065. Transmission mounts must be stock type with rubber mount. Motor swaps are allowed.
- 3) Aftermarket brake and gas pedals, shifters, steering columns, pinion brakes, slider shafts and headers are permitted.
- 4) Front suspension and Rear suspension must be factory. No leaf spring conversions. No solid suspension. Must have 2" (inches) of travel. Front bumper height cannot exceed 20 inches measured from ground to bottom center of bumper.
- 5) Bumpers must be an automotive factory car bumper. (NEW) Bumpers CAN NOT extend past the body of the vehicle ! (NEW) **NO POINTY BUMPERS ALLOWED!** No truck Bumpers. No aftermarket bumpers. Bumpers may be seam welded with maximum of four(4), three-inch welds on top and four(4) , three-inch welds on the bottom. No loaded bumpers. (NEW) Now you are allowed to use 3"x 3" square tubing or 3' pipe. Material thickness MAX 3/16 "inch and can not exstend passed the center of the front tires! You can hardnose (removing bumper shock) by using 6"x6"x 1/4" thick plate on the factory mounting points! (One plate per mount) You can cut the plate as needed to mount the bumper, then weld or bolt bumper on to vehicle. ANY QUESTIONS PLEASE CALL ME ! (443-309-9065). 9 wire can be wrapped around bumper and hooked to core support . 2 spots ONE wrap only each side.
- 6) Frames must be stock! No plating, stuffing, shortening, tilting or seam welding. Rear frame notching or dimpling is permitted.
- 7) Fix it plates may be added with APPROVAL to PRE-RAN cars only! Four (4) plates max (2 per side) 4"x4"x1/4" max on the outside of frame only with one(1) inch gap>

>between plates. **YOU MUST CALL FIRST BEFORE ADDING ANY PLATE** 443-309-9065.

8) Doors can be chained, 9 wired or welded. If welded maximum of three (3) ,three (3) inch welds on each vertical seam only. No welds on top or bottom horizontal seams.

9) Hoods must have hole cut in center 20x20 at minimum. Hood can be chained, 9 wired, or bolted in 6 spots. If bolted use angle iron no bigger than 1/4inch thick and 3 inches long, No all thread through the body mounts to the trunk lid or hoods!

10) Trunks can be chained, 9 wired, or bolted in 4 spots. If bolted use angle iron no bigger than 1/4 inch thick and 3 inches long. NO all thread. You may Tuck trunk. No wedging, canoeing, or dishing of trunks allowed.

11) Factory Body mounts may be removed but body cannot be mounted directly to frame. Must have 1 inch puck or washers in place of factory mounts. No exceptions.

12) A Dash bar and behind seat bar may be installed or a 4 point floating safety cage consisting of dash, behind seat, driver's door and passenger side front door only, may be installed. Cage bar material mut not exceed 4x4 inch or 2x6 inch. Dash bar must be 5 inches from firewall. If running a Halo bar it must go straight up and over the out side of the vehicle. Fuel tanks may be mounted to rear seat bar with a protector but must be 5 inches from rear packing tray. No part of cage can be tied into frame or floor pan of vehicle. Windshield safety bar or chain from cowl to roof is permitted. No rear window bars.

13) Tires must hold air. (NEW) No rims without tires!! You must start the derby with tires on rim! No solid tires, foam filled or doubled tires. Tubes only. No bead locks or lip protectors. Valve stem protectors are permitted. Skid loader and fork lift tires are permitted. NO SOILD TIRES!!!

14) Factory tanks in front of rear axel can stay , BUT MUST HAVE ONLY FIVE GALLONS OF FUEL IN IT!! WE WILL BE CHECKING!! MORE THEN FIVE YOU WILL BE DISQUALIFIED!!

Fuel tanks and Electric pumps can be mounted in rear seat area fastened to rear seat bar or floor securely. Must be steel or aluminum fuel cell or boat tank. FIVE GALLON CAPACITY TANK ONLY !!! No plastic. Gasoline only (Any Octane) No Methanol/Alcohol. Electric pumps must have kill switch mounted at drivers reach. All fuel connections must be covered with rubber if using standard fuel line ! (line with in a line method) unless using steel braided line. ANY QUESTIONS CALL (443-309-9065) Tanks do not require a cover, just connections at the pump and tank.

15) Aftermarket Transmission coolers inside vehicle drivers compartment area are permitted. Must be mounted securely and lines must be high pressure connections. ALL COOLANT SYSTEMS MUST HAVE 18-20 PSI. MAX. PRESSURE CAP! NO ADDITIVES, BIODEGRADABLE ANTIFREEZE ONLY!! SYSTEM WILL BE CLOSLEY INSPECTED !! NO RADIATOR PROTECTERS.

16) One battery per vehicle. Up to 1200 cold cranking amps. Mounted securely inside of drivers compartment of vehicle and covered with rubber mat.

- 17) All glass, plastic, fiberglass and chrome trim MUST be removed before bringing the vehicles to the event. Including the plastic bumper covers and styrofoam . Remove all interior from inside of the vehicle including the carpet! You are allowed to leave the dash in the car. All broken glass and debree must be cleaned from car and inside of doors!!
- 18) 1Airbag systems must be removed. Any airbag that discharges while on track will result in DQ.
- 19) Sunroof holes must be covered with sheet metal.
- 20) Car numbers must be displayed 24" in size and visible from both sides of car.
- 21) Drivers must be 18 years of age with a valid driver's license and sign a release form.
- o Note licensed drivers under 18 must have parents signature on a minor release form.
 - o
- 22) All cars and drivers must be at the event 2 hours before the start time! Inspections end 1 hour before the start time. All drivers must wear DOT helmet and neckbrace. Must wear seatbelts
- 23) All drivers supply their own vehicle. Additional safety regulations may be imposed due to track conditions. All rules and regulations must be observed. Driver and mechanic only in pit area.
- 24) ALL DECISIONS BY JUDGES ARE FINAL! ANY QUESTIONS ABOUT ANY OF THESE RULES PLEASE CONTACT DONNY AT 443-309-9065.
- 25) All Specialty vehicles (Vans, Trucks, SUV, and School Bus) And (NEW) STONEY STREET STOCK CLASS see website for additional rules
- 26) I WILL NOT TOLERATE ANY DISRESPECT TOWARDS MY CREW OR MYSELF, YOU WILL BE BANNED FROM RUNNING ANY STONEY ROBERTS EVENTS !!!