



VHNS SERIES HYDRAULIC NUT SPLITTER



BROKEN NUT WITH TOOL



FEATURES / APPLICATION

- No spark or flame. No risk to volatile surrounding best suited for (Petro Chemical, Fertilizer etc)
- Triangular Chisel providing three cutting edges (Provided with One Spare Blade).
- Light and compact international design for ease of operation and handling.
- Dedicated cylinder with minimal stroke and spring return for faster operation.
- Rear end connection for ease of handling and safe-connection.
- 700 Bar working pressure (Compatible with all reputed brand pumping unit)

RANGE M6 - M48 | MAX. WORKING PRESSURE 700 BAR

Model	Stud Diameter		Nut A/F		A	B	C	D	E	F	Wt
	(mm)	(inch)	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
VHNS-5-1018	M6 - M12	1/4"-3/8"	10-18	1/2"-11/16"	40	52	8	20	20	30	1
VHNS-10-1824	M12-M16	3/8"-9/16"	18-24	11/16"-15/16"	54	67	12	24	24	41	2
VHNS-15-2432	M16-M22	9/16"-3/4"	24-32	15/16"-1 1/4"	64	79	13	30	30	52	3
VHNS-20-3241	M22-M27	3/4"-1"	32-41	1 1/4"-1 5/8"	78	94	20	37	37	69	4.5
VHNS-35-4150	M27-M33	1"-1 1/4"	41-50	1 5/8"-2"	95	113	21	45	45	78	9.6
VHNS-50-5060	M33-M39	1 1/4"-1 1/2"	50-60	2"-2 3/8"	106	128	25	54	54	91	13
VHNS-60-6075	M39-M48	1 1/2"-1 7/8"	60-75	2 3/8"-2 15/16"	156	185	27	75	75	110	34

- Higher capacity and customized solutions on request.
- Specifications are subject to change due to continual improvement.
- Capacity and Stroke specified are maximum safe limits.
- Use at 80% of rating as safe practice.

SELECT SUITABLE PUMPING UNITS AND ACCESSORIES



Vankos & Company (Hyderabad)

Plot No. 457 & 458, S.V.C.I.E, IDA, Phase-I, Jeedimetla, Hyderabad-500055

sales@vankoshyd.com | www.vankoshyd.com