
MANUAL EASY PULLERS - 2/3 WAY






One completed set $(4\sim8 \text{ Ton})$ with two kinds of puller for user's convenience.







SIMPLE AND EASY PULLING JOB

The most simple and efficient design, Screw-Operated Jaws bring the users to position the puller on the part quickly and correctly with just one person operating only.

USER-FRIENDLY

- 3 and/or 2 fixed jaws for easy positioning and selfcentering.
- Available in six sizes with a maximum pulling force from 2 Tons to 12 Tons.

SAFE

 Self-positioning centring prevent the damage to the shaft as well.

SAVING COST

- Conveniently positioning, efficiently pulling help to save manpower and operating time.
- The first 2 / 3 way manual easy puller in the world which brings users the two options in one model as the best choice to save the cost.

SPECIFICATIONS

Capacity	Model No.	Reach (Max. mm)	Spread (Max. mm)	Shaft Dimension		Jaw Tip (mm)			Weight
				Thread	Length(mm)	Α	В	С	(Kg)
2 Ton	PM55	80	120	Ø 5/8"x11T	24	8	6	15	1.6
3 Ton	PM85	120	140	Ø 5/8"x11T	28	6	7	15	2.3
5 Ton	PM105	160	270	Ø 3/4"x10T	34	11	10	25	4.3
8 Ton	PM125	210	300	Ø 3/4"x10T	39	13	14	27	6.1
10 Ton	PM155	250	380	Ø 7/8"x14T	47	14	10	29	9.6
12 Ton	PM175	250	440	Ø 7/8"x14T	47	14	10	29	11.2



Exclusive Marketing & Service Assosiates:

Vankos & Company (Hyderabad)

Plot 457 & 458, S.V.C.I.E, IDA, Phase-1, Jeedimetla,

Dist.: Medchal-Malkajgiri, Hyderabad-500055, Telangana, India

Email: sales@vankoshyd.com Web: www.vankoshyd.com