

Manual Pushing Mobile Scissor Lift

MK Series



PRODUCT DESCRIPTION:

Sturdy design, perfect structural strength, operational safety and functional versatility are the outstanding features of vankos platforms. Motorized have highly precision engineered quality built into each unit for trouble free long life. The hydraulic cylinders (single stage, multistage and multicylinder type) likewise match the technical standards required for top performance including impact loads and heavy knocks under arduous working conditions. All products are individually tested to conform to highest quality standards.

STANDARD CONFIGURATIONS

- Auxiliary Lowering Device
- Anti-burst System
- Adjustable Outriggers
- Rain-proof Cabinet
- Emergency Stop Button

OPTIONAL CONFIGURATIONS

- Motorized Device(forward & backward movement)
- Extension Platform(6-12m)
- DC power or both AC & DC power
- Solid Tyre.



Model	Mk600	Mk900	Mk1100	Mk1200	Mk1400	Mk1600	MK600T	MK900T	MK1200T
S.W.L on Extension	500Kg	500Kg	500Kg	500Kg	500Kg	300Kg	1000Kg	1000Kg	1000Kg
Platform height max	6m	9m	11m	12m	14m	16m	6m	9m	12m
Platform size (L*W)	1.85*0.88m	1.8*1.00m	2.1*1.15m	2.45*1.35m	2.45*1.35m	2.75*1.5m	1.8*1.00m	1.8*1.25m	2.45*1.35m
Overall Size (LxWxH)	2.05x1.08x1.1m	2x1.2x1.68m	2.3x1.35x1.7m	2.65x1.55x1.88m	2.65x1.55x2.00m	2.95x1.75x2.1m	2x1.2x1.45m	2x1.15x1.75m	2.65x1.55x1.88m
Lifting time	55S	70S	80S	125S	165S	173S	60S	100S	135S
Motor Power	1.5kw	1.5kw	2.2kw	3kw	3kw	3kw	2.2kw	3kw	4kw
Power Voltage	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V	AC380V
Weight	800Kg	1200Kg	1580Kg	2450kg	2650Kg	3200Kg	1100Kg	1510Kg	2700Kg
Tyre	Φ 200Polyurethane				Φ 500-8 Pneumatic Tyre				

Optional Motorized Device with DC Power

Driving motor	0.75kw	0.75kw	0.75kw	0.75kw	0.75kw	1.2kw	1.2kw	0.75kw	1.2kw	1.2kw
Lifting motor	2.2kw	2.2kw	2.2kw	3kw	3kw	2*3kw	2*3kw	3kw	3kw	2.3kw
Power source	120AH*2	120AH*2	120AH*2	150AH*2	200AH*2	150AH*4	150AH*4	150AH*2	200AH*2	150AH*4
Charger	1.850.88m	24V/15A	24V/15A	24V/15A	24V/15A	24V/30A	24V/30A	24V/15A	24V/20A	24V/30A
Overall Size(LxWxH)	2.1x1.24x1.5m	2.1x1.24x1.65m	2.4x1.39x1.85m	2.4x1.59x1.85m	2.75x1.59x2.0m	2.75x1.74x2.0m	3.15x1.74x2.0m	1.851.24x1.1m	1.85x1.49x1.65m	2.5x1.59x1.85m

Mini Scissor Lift

MK Series



Description:

Compact and easy to maneuver scissor lift for maintenance activities. The table is versatile and can be moved and operated by a single person with smooth flooring.

STANDARD CONFIGURATIONS

- Auxiliary Lowering Device
- Anti-burst System
- Rain-proof Cabinet
- Emergency Stop Button
- Inter-lock door on the platform
- DC power

OPTIONAL CONFIGURATIONS

- Extension Platform
- AC power



Model	Mk300	MK390
S.W.L	300kgs	300kgs
Platform height max	3 MTRS	3.9MTRS
Stowed length	1.32MTRS	1.32MTRS
Stowed width	0.76MTRS	0.76MTRS
Stowed Height(Rails up)	1.83MTRS	1.92MTRS
Stowed Height(Rails down)	1.43MTRS	1.52MTRS
Platform size (LxW)	1.15*0.6MTRS	1.15*0.6MTRS
Wheelbase	0.99MTRS	0.99MTRS
Max. Workers Number	1	1
Ground clearance	0.05MTRS	0.05MTRS
Raise / Lower time	34/20sec	34/21sec
Tire	6in/8in	6in/8in
Lifting motor	12v/0.8kw	12v/0.8kw
Power source	12v/85Ah	12v/85Ah
Charger	12v/15A	12v/15A
Weight	495kg	520kg