RESIDENTIAL DRIVEWAY PERMIT APPLICATION

	Name of applicant	P.O.Box and address	
			ount.
	request permission to co Phone Number	onstruct a residential driveway on a c	County
		away is to be constructed on the	oido
bad in	side Cusseta-Chattahoochee County. The drive	•	
•			EW
of	Street or Road and House number, if available	_ St. (Rd.) at a pointft.	NOEW/
	Street or Road and House number, if available		NSEW
of the c	centerline of the intersection with		St. (Rd.)
		nearest Street or Road	1 .1. 1
	ning this request, I agree to construct or have cor	•	•
	sed contractor. I also agree that I will be respons	ible for the maintenance of this drive	eway
ncludir	ng pipe, surface course, and slopes.		
DATE	Signature		
	-		
	** Above information is to be provided by	the owner prior to issuance. **	
This	drive to serve a commercial business only and m	•	without
	approval of the U		
	арр. ота. от шо о		
:DECI	AL REQUIREMENTS		
, LOI	AL ILQUINLIMENTO		
1.	Extend pipe as necessary to obtain a 4:1 or flatter slope.		
	The pipe shall be GA DOT High density polyurethane or	TYPICAL PLAN & PROFILE FOR	RDRIVE
	GADOT reinforced concrete pipe. The diameter shall be		
	determined by water calculations per the design engineer.	INFORMATION TO BE PROVIDED BY APPLICANT	PUT ARROWHEAD
	Minimum diameter shall be 18", or approved by the Director	g'MIN V	AT NORTH
	of Public Works. Length of pipe shall be determined by		
	depth of ditch and slopes, as per design engineer.		
	Existing surface flow to remain. Water cannot be diverted to		
	UGOCCC right-of-way.	MAILBOX SAFETY	
1		/ \$ \$ \	END SECTION REQUIR
	No headwalls to be constructed on pipe. Safety End	EDGE OF PAVEMENT	END SECTION REQUIR
		EDGE OF PAVEMENT	END SECTION REQUIR
4.	No headwalls to be constructed on pipe. Safety End	60	END SECTION REQUIRE
4.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum.	EDGE OF PAVEMENT	END SECTION REQUIR
4. 5.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed	EDGE OF PAVEMENT	END SECTION REQUIRE
4. 5. 6. 	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications.	EDGE OF PAVEMENT	END SECTION REQUIR
4. 5. 6. 7.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi	EDGE OF PAVEMENT 1. TO © OF STREET (read) FROM © OF DRIVE. (Show arrow in direction of street.) MILEPOST	END SECTION REQUIR
4. 5. 6. 7.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E.	EDGE OF PAVEMENT #. TO Ç OF STREET (read) FROM Ç OF DRIVE. (Show arrow in direction of street.) MILEPOST 1/4* TO 3/4* © PER FT SLOPE RW	END SECTION REQUIR
4. 5. 6. 7. 6. 8. 6. 6. 6. 6. 6. 6	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain	EDGE OF PAVEMENT ft. TO Ç OF STREET (read) FROM Ç OF DRIVE. (Show arrow in direction of street.) MILEPOST 1/4" TO 3/4"	END SECTION REQUIR
4. 5. 6. 7. 8. 7.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain view until work is inspected and accepted by UGOCCC.	EDGE OF PAVEMENT ft. TO © OF STREET (read) FROM © OF DRIVE. (Show arrow in direction of street.) MILEPOST	ORIGINAL
4. 5. 6. 7. 8. 7. 9. 7.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain view until work is inspected and accepted by UGOCCC. All work to be completed in 30 days for Mobile Homes. For	EDGE OF PAVEMENT ft. TO \$ OF STREET (read) FROM \$ OF DRIVE. (Show arrow in direction of street.) MILEPOST 1/4" TO 3/4" PER FT SLOPE DESIRABLE LOWPOINT	
4. 5. 6. 7. 6. 8. 7. 9. 9	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain view until work is inspected and accepted by UGOCCC. All work to be completed in 30 days for Mobile Homes. For Site Built Homes all work to be completed within 30 days	EDGE OF PAVEMENT #. TO © OF STREET (read) FROM © OF DRIVE. (Show arrow in direction of street.) MILEPOST ### TO 3/4* PER FT SLOPE DESIRABLE LOWPOINT EXISTING PAVEMENT 10' — 18" MIN. COVER	ORIGINAL GROUND
4. 5. 6. 7. 8. 9. 4.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain view until work is inspected and accepted by UGOCCC. All work to be completed in 30 days for Mobile Homes. For Site Built Homes all work to be completed within 30 days after the completion of the home. Applicant to give Public	EDGE OF PAVEMENT #. TO © OF STREET (read) FROM © OF DRIVE. (Show arrow in direction of street.) MILEPOST PER FT SLOPE PER FT SLOPE DESIRABLE LOWPOINT T% max (+) of (-) 18" MIN. OVER PIPE	ORIGINAL GROUND
4. 5. 6. 7. 8. 9. 7.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain view until work is inspected and accepted by UGOCCC. All work to be completed in 30 days for Mobile Homes. For Site Built Homes all work to be completed within 30 days after the completion of the home. Applicant to give Public Works Department 24 hours notice before work begins.	EDGE OF PAVEMENT #. TO © OF STREET (read) FROM © OF DRIVE. (Show arrow in direction of street.) MILEPOST ### TO 3/4* PER FT SLOPE DESIRABLE LOWPOINT EXISTING PAVEMENT 10' — 18" MIN. COVER	ORIGINAL GROUND
4. 5. 6. 7. 8. 9. 3. 10.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain view until work is inspected and accepted by UGOCCC. All work to be completed in 30 days for Mobile Homes. For Site Built Homes all work to be completed within 30 days after the completion of the home. Applicant to give Public Works Department 24 hours notice before work begins. Advance warning signs shall be required while working on	EDGE OF PAVEMENT #. TO © OF STREET (read) FROM © OF DRIVE. (Show arrow in direction of street.) MILEPOST PER FT SLOPE PER FT SLOPE DESIRABLE LOWPOINT T% max (+) of (-) 18" MIN. OVER PIPE	ORIGINAL GROUND
4. 5. 6. 7. 8. 9. 3. 10.	No headwalls to be constructed on pipe. Safety End Sections required as a minimum. No brick or other hazardous mailbox supports allowed on right-of-way. (mailbox shall be located on exit side) All disturbed right-of-way to be regrassed to DOT specifications. Driveway must be stabilized with 4" of concrete 3000psi or 2" of GADOT approved Asphalt Type E. The permit poster must be displayed at the site in plain view until work is inspected and accepted by UGOCCC. All work to be completed in 30 days for Mobile Homes. For Site Built Homes all work to be completed within 30 days after the completion of the home. Applicant to give Public Works Department 24 hours notice before work begins.	EDGE OF PAVEMENT #I. TO © OF STREET (read) FROM © OF DRIVE. (Show arrow in direction of street.) MILEPOST PER FT SLOPE DESIRABLE LOWPOINT T% max (*) of (*) T% max (*) of (*) OVER PIPE OTHER REQUIREMENTS:	ORIGINAL GROUND

Title: ______ This _____ day of ______, 20____