

# BUILT TOUGH AND EASY TO SERVICE

**STRIKE FIRST WET CHEMICAL FIRE EXTINGUISHERS ARE DESIGNED FOR:**



WOOD,  
PAPER,  
CLOTH

**CLASS A**



RESTAURANT,  
KITCHEN HAZARD

**CLASS K**

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Colour and bar-coded labels for accurate service
- Factory filled and pressurized



LISTED

**MEETS OR EXCEEDS:**  
ANSI/UL 8 & 711



LISTED  
HOMOLOGUÉ

**MEETS OR EXCEEDS:**  
CAN/ULC-S554 & S508

- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 35°F to 120°F (2°C to 49°C)



The STRIKE FIRST Class K extinguisher is designed for use on restaurant or commercial cooking appliances. The low Ph wet chemical agent effectively smothers and cools fires involving combustible cooking oil (vegetable) or animal fat.

It is intended to be used as a back-up for an automatic fire suppression system.

CAPACITY	1.6 gallons (6 litres)
Model No.	SF-6LK
UL/ULC Rating	1-A : K
Range	8-10 ft (2.4-3 m)
Discharge Time	55 sec
PSI	100
Height	21 1/2" (54.6 cm)
Width	8 3/4" (22 cm)
Diameter	7 1/8" (18 cm)
Weight	24 1/2 lb (11.1 kg)
Standard Bracket	Wall

