3 3/8" OD LATERAL LOCATOR

Features and Benefits

- CLEAN'S LATERALS WITH ROTATING MILLS AND NOZZLES.
- THE RTLL IS ACTIVATED BY 60 GPM FILTERED FLOW RATE TO ENTER A LATERAL.
- RTLL TOOL CAN DEFLECT UP TO SIX DEGREES TO ENTER ANY LATERAL.
- CAN ENTER OPEN HOLE LATERALS AND LATERALS WITH LINERS.
- UPON ENTERING THE LATERAL THE RTLL WILL LOCK STRAIGHT.
- WORKSTRING ROTATION CAN BE USED TO CLEAN THE LATERAL.
- CLEAN'S YOUR LATERAL IN ONE DAY.
- ONLY ONE TRIP REQUIRED WHEN USING THE RTLL.
- NO NEED TO SET CONCAVES OR FINDERS WHEN USING THE RTLL.
- LARGE FLOW RATES FOR EXTENDED REACH LATERAL CLEANOUTS.
- 3-1/8" X 3-3/8" X 60" WITH HIGH TENSILE CONNECTIONS UTILIZED TO ACCESS 4" ID AND LARGER LATERALS.
- WILL ALSO OPERATE WITH AIR-FOAM AND N2. UNDER BALANCE CLEAN OUTS, POST CLEANOUT AND FORMATION TREATMENT FRIENDLY.

THE RTLL IS IN THE FINAL STAGES OF TESTING FOR USE WITH A WORK STRING AND WILL BE AVAILABLE IN MID JANUARY 2020.

THE RTLL IS ALSO BEING DESIGNED TO RUN WITH COIL TUBING AND A MUD MOTOR USING A SPECIAL FLOW CONTROL VALVE. THIS DESIGN WILL PROVIDE THE SAME RESULTS AS A WORK STRING AT A CONSIDERABLE COST SAVINGS.

AVAILABLE THRU: RT MANUFACTURING, HARVEY LA. CONTACT: ROGER TRUDEAU (504) 368-8176 GERALD CRONLEY (504) 583-1988