

#### **MOST FREQUENT USE**

RETAIL

HOSPITALITY

**CLEANING CONTRACTORS** 

**EDUCATION** 



FOLDABLE HANDLE



SPIN-ON, SPIN-OFF BRUSH



EASY TO USE CONTROLS

#### **AUTOMATIC SCRUBBERS - WALK BEHIND**

## **CT15**

The CT15 is compact in size (14" cleaning path with 4 gallon tank) but provides the high productivity and long battery run-times of a larger scrubber. It is perfect for areas where traditional automatic scrubbers are just too large.

MAX PRODUCTIVITY

 $13,500 \text{ ft}^2/\text{h}$  1.5 h

**BATTERIES RUNNING TIME** 

**KEY SPECS** 

4/5 gal

14" brush drive



#### **INNOVATIONS**











Eco Select permits to decrease energyconsumption and increase running time by 20% in every day cleaning operations. Noiselevel is down to 62Db allowing cleaning operations even in sensitive areas.

Programmed maintenance is longer with consequent cost reduction.





SLS™ SELF LEVELING SYSTEM

### **MECHANICAL SYSTEM**



- $\cdot$  The brush pressure with self-leveling and self-adjusting head allows a perfect fit between the brush and floor
- · System available as mechanical, electro mechanical or electronic according to machine models



# FOLDABLE HANDLE

The adjustable multi-position handle on CT15 allows many applications with maximum comfort to the operator, even in parrow areas





#### **Other Features**

- Brush replacement without tools
- Squeegee blades can be used on four sides before needing replacements
- Easy access to internal compartments
- Tanks and surrounding body in high density polythylene
- Oil bath reduction gear box

- Brush head and squeegee system designed to absorb harsh impact
- Panel control switches protected against water and humidity
- Central Flow System
- Great maneuverability due to optimum weight distribution

#### CT15 TECHNICAL SPECIFICATIONS CT15 BATTERY DISC CT15 ELECTRIC DISC CT15ECSB35 Code CT15B35 CT15E35 CT15E7G635 **PRODUCTIVITY** Max theoretical productivity ft2/h - m2 13,500/ 1,300 m<sup>2</sup> 13,500/ 1,300 m<sup>2</sup> 13,500/ 1,300 m<sup>2</sup> Squeegee Width in/mm 18 in/ 450 mm 18 in/ 450 mm 18 in/ 450 mm in/mm 14 in/350 mm 14 in/ 350 mm 14 in/ 350 mmv Cleaning path 4/5 gal/ 16/19 l 4/5 gal/ 16/19 l 4/5 gal/ 16/19 l Gal/ l Water tank capacity Unlimited Max running time min 90 45 Voltage V-Ah 24V (2x12) 29AGM 24 (2x12) 29AGM 24 (2x12) 29AGM W 400 400 Installed power 550 Max Speed 2.2 mph/ 3.5 kph 2.2 mph/ 3.5 kph 2.2 mph/ 3.5 kph lbs/ kg Brush pressure 55 lbs/ 25 kg 35 lbs/ 16 kg 35 lbs/ 16 kg Weight lbs/ kg 130 lbs/ 59 kg 115 lbs/ 52 kg 115 lbs/ 52 kg 37 x 21 x 48 in 37 x 22 x 48 in 37 x 21 x 48 in **Dimensions** in Cord Length ft N/A 30 ft N/A

#### **AVAILABLE ACCESSORIES**

#### **CLEANING QUALITY**

PAD DRIVER SPPV01273

SPPV01481 (.8 MM) SPPV01480 (.5 MM) TYNEX BRUSH SPPV01482 SOFT NATURAL BRISTLE BRUSH SPPV01485

**12 V 33 AGM** 12V33-AGM **SQUEEGEES**PMVR01885 (COMPLETE)

MPVR05917 (FRONT) MPVR05918 (REAR)













MICROFIBER PAD DRIVER SPPV01268













DIAMOND PADS ECS211636 (RED), ECS211634 (GREEN), ECS212518 (POLISH)



#### **GET RIGHT SIZED**

	Description	Continuous run-time	Theoretical ft²/ h	Maximum Theoretical ft <sup>2</sup> /charge	Ft <sup>2/</sup> charge efficiency (70%)
CT15E35	Electric Brush Drive, 12V33 AGM	Unlimited	13,494	N/A	9,446 per hour
CT15B35	Battery Brush Drive 12V33 AGM	1.5 h	13,494	20,241	14,469 per hour
CT15ECSB35	Battery Brush Drive, 12V33 AGM	.75 h	13,494	10,120	7,084 per hour

