

CREATING A CLEANER, SAFER, HEALTHIER WORLD.



# **M30**

#### LARGE INTEGRATED SWEEPER-SCRUBBER


- Effectively clean in just one pass wet or dry with FloorSmart® integrated cleaning system technology
- Achieve excellent cleaning results with ec-H2O<sup>TM</sup> technology and MaxPro<sup>2TM</sup> hydraulic technology
- Increase visibility with cab-forward design, open sightlines, and steering-wheel-mounted controls
- Improve the operator and supervisor experience with available Pro-Panel<sup>™</sup> technology

#### **INNOVATIVE TECHNOLOGIES**



### AVAILABLE PRO-PANEL™ TECHNOLOGY REDEFINES THE USER EXPERIENCE

Transform your cleaning operation with Pro-Panel<sup>™</sup> technology – a revolutionary breakthrough in user experience. Pro-Panel<sup>™</sup> technology integrates multiple controls into an intuitive, high-visibility touch screen interface.





- Ensure successful starts with Pro-ID<sup>TM</sup> operator login that automatically activates the specific operator's personalized cleaning settings and downloadable Pro-Check<sup>TM</sup> pre-operation checklists.
- Increase cleaning efficiency with programmable Zone Settings<sup>™</sup> that allow you to establish preferred cleaning settings by area of facility.
- Provide operators a view of their cleaning path without having to take their eyes off the direction of travel with **PerformanceView**<sup>TM</sup>.
- Increase visibility with backup camera featuring colored guidelines that help drivers safely dump debris and avoid objects when in reverse.
- Reduce the need for extensive operator training with on-board,
   on-demand videos.
- Increase machine ease of use with 28 different language options.

#### ADDITIONAL EXCLUSIVE TECHNOLOGIES

All technologies increase scrub time up to three times using a single tank of water.




ec-H2O<sup>™</sup> technology electrically converts water into an innovative cleaning solution that cleans effectively, saves money, improves safety, and reduces environmental impact\* compared to daily cleaning floor chemicals and methods.









## AN INNOVATIVE, HIGH-PERFORMANCE, INTEGRATED SWEEPER-SCRUBBER FOCUSED ON DELIVERING CUSTOMIZED SOLUTIONS TO MEET CUSTOMER NEEDS



#### THE M30 ADDRESSES YOUR KEY BUSINESS CHALLENGES



#### **REDUCE COST TO CLEAN**

• Improve productivity by cleaning in a single pass with FloorSmart® integrated cleaning system technology that combines sweeping and scrubbing functions.



#### MAINTAIN HEALTH & SAFETY

• Ensure employee safety with a high-capacity, multi-level hydraulic rear hopper that eliminates the need to manually handle debris.



#### **ENHANCE FACILITY IMAGE**

• Deliver excellent cleaning results with MaxPro<sup>2TM</sup> hydraulic technology that provides consistent power to the brush drive motors regardless of floor surface changes.



#### **EASY OPERATION & MAINTENANCE**

Reduce training and simplify operation with the Touch-n-Go<sup>™</sup> control module featuring 1-Step<sup>™</sup> start button.

# MSIDE THE MANAGEMENT OF THE STATE OF THE STA

Touch-n-Go™ control module •• with 1-Step™ start button allows easy access to all settings without having to remove hands from wheel

Full front shroud ensures operator leg and foot protection

Corrosion-resistant ... Duramer<sup>™</sup> construction on shrouding and solution and recovery tanks for long life

Front-wheel steering and high-traction tires provide excellent maneuverability in congested spaces

Forward operating position improves operator safety and visibility • • •

Optional ec-H2O<sup>™</sup> technology improves productivity and reduces environmental impact


Solution and recovery tanks allow for complete visual inspection and cleanout

Heavy-gauge steel frame with full wraparound bumper and cushioned rollers help protect machine life •

Yellow touch points save time and ensure proper maintenance

Dura-Track<sup>™</sup> parabolic squeegee with SmartRelease<sup>™</sup> improves water pickup and damage resistance

Rugged 18 in/460 mm tires allow easy maneuvering indoors and out



Wet/dry synthetic fiber panel filter with InstantAccess™ provides excellent dust control and shakeback

Scrubbing side brush widens cleaning path from 48 in/1,220 mm up to 62 in/1,575 mm.

Spray hose makes machine spray-down and cleanup quick and easy.

Rear and side steel guards protect squeegee upon impact and prevent it from hooking on to obstacles.









Touch-n-Go™ Control Module



Dura-Track™ Parabolic Squeegee

- Touch-n-Go<sup>™</sup> control module with 1-Step<sup>™</sup> start button allows operators quick access to all settings without removing hands from the steering wheel.
- High-capacity, multi-level hydraulic rear hopper (7 ft<sup>3</sup>/198 L | 650 lbs/295 kg) increases cleaning productivity by eliminating the need to manually handle debris.
- Dura-Track<sup>™</sup> parabolic squeegee with
  SmartRelease<sup>™</sup> delivers exceptional water pickup
  and reduces maintenance and replacement parts
  due to squeegee damage.
- Easy-access design offers quick service access and visibility to on-board diagnostics, helping minimize downtime and reduce maintenance costs.
- Cab-forward position and spacious operator compartment provide outstanding visibility, safety and ergonomics to protect operators, the machine and your facility.
- Easy-to-identify yellow maintenance touch points help save time and money in routine maintenance activity.



**Easy-Access Design** 



**Yellow Maintenance Touch Points** 

Overhead guard protects operators from falling objects.

High-powered pressure washer allows for easy blast-cleaning of hard-to-reach areas.





Safety warning light ensures awareness of machine during operation.

M30



## TENNANT*TRUE®* PARTS, SERVICE AND FINANCE SOLUTIONS

- Reduce rework, labor and safety costs by using only Tennant True parts and service.
- Ensure optimal cleaning performance by selecting a Tennant True Service program provided by a network of over 400 factorytrained Tennant service representatives.
- Improve uptime by leveraging TennantTrue parts and service.
- Simplify budgeting by bundling Tennant*True* service plans, including parts, into the purchase or financing of your machine.



Manage your cleaning program with key performance metrics based on machine data.

Lease. Pre-Owned. Rent. Tennant has flexible options that get you the machines you need, however you need them.

#### M30 LARGE INTEGRATED SWEEPER-SCRUBBER

#### INTEGRATED CLEANING SYSTEM

Cleaning path	48 in / 1,220 mm
With scrubbing side brush	62 in / 1,575 mm
With sweeping side brush	64 in / 1,625 mm
Cylindrical main brushes	
Brush speed	480 rpm
Brush down pressure (up to)	390 lb / 177 kg
Brush diameter (2)	12 in / 305 mm
Side brush	
Brush speed	150 rpm
Scrubbing brush diameter	16 in / 410 mm
Sweeping brush diameter	21 in / 533 mm
Tanks	
Solution tank	75 gal / 284 L
Solution capacity with ES®	100 gal / 379 L
Recovery tank	95 gal / 360 L
Demisting chamber	20 gal / 76 L
Debris hopper	•
Volume capacity	7 ft <sup>3</sup> / 198 L
Weight capacity	650 lb / 295 kg
Dump height (variable to)	60 in / 1,525 mm
Vacuum fans	
Scrubbing fan speed	11,000 rpm
Scrubbing fan water lift	35 in / 890 mm
Sweeping fan speed	6,500 rpm
Sweeping fan airflow	290 cfm / 8.2 m³/mir

#### PROPELLING SYSTEM

Propel speed forward (variable to)	8 mph / 12.9 km/h
Propel speed reverse (variable to)	3 mph / 4.8 km/h
Engine-gasoline (2.0 L)	
Gross Intermittent Power*	50.7 hp / 37.8 kw @ 2800 rpm
Tennant Governed Power	40.6 hp / 30.3 kw @ 2300 rpm
Engine-LPG (2.0 L)	
Gross Intermittent Power*	51.6 hp / 38.5 kw @ 2800 rpm
Tennant Governed Power	42.4 hp / 31.6 kw @ 2300 rpm
Engine-diesel turbo (1.5 L)	
Gross Intermittent Power*	44.2 hp / 33.0 kW @3000 rpm
Tennant Governed Power	41.0 hp / 30.6 kW @2800 rpm
Gradeability	
Transport at gross weight	8.0° / 14%
Working (cleaning)	6.0° / 10%
Ground clearance (transport)	3 in / 80 mm

#### **DUST CONTROL SYSTEM**

Filter system	Synthetic fiber panel
Filter area	78 ft <sup>2</sup> / 7.3 m <sup>2</sup>
Dust filtration (to)	3 microns @ 99% efficiency
Shaker mechanism (automatic)	Timed, beater bar

#### **MACHINE SPECIFICATIONS**

108 in / 2,745 mm
58 in / 1,473 mm
59 in / 1,500 mm
64 in / 1,625 mm
58 in / 1,473 mm
84 in / 2,135 mm
4,000 lb / 1,815 kg
125 in / 3,175 mm

#### WARRANTY

See your local representative for warranty information.

\*Per SAE J1995

Specifications subject to change without notice.

#### **SEEING IS BELIEVING**

For a demonstration or additional information, call +1.800.553.8033 or email info@tennantco.com

Tennant 701 North Lilac Drive Minneapolis, MN 55422 USA

USA/Canada: +1.800.553.8033 Quebec: +1.800.361.9050 Overseas: +1.763.540.1315

www.tennantco.com info@tennantco.com