

SAFETY DATA SHEET



This safety data sheet complies with the requirements of: 29CFR1910.1200

Issue Date 06-Jun-2018 Revision Date 21-Dec-2018

1. IDENTIFICATION

Product identifier

Product Name MS3 Fiber "G" Max Sealant

Other means of identification

Product Code MS3 Fiber "G" Max Sealant

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended UseWhite acrylic elastomeric mastic for use in roof repairs, seal metal roof fasteners, flashing

and protrusions prior to coating with elastomeric roof coatings.

Uses advised against For exterior use only. Do not use indoors.

Details of the supplier of the safety data sheet

Manufacturer Address MS3, LLC.

5306 39th Street Lubbock, Texas 79414 806-773-2169

Emergency telephone number

Emergency Telephone Call CHEM

Call CHEMTREC Day or Night:

Within USA and Canada: 1-800 424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 2

Label elements

Emergency Overview

Warning

Hazard statements

Suspected of causing cancer



Appearance Viscous Physical state Liquid Odor Low

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Unknown acute toxicity 50.3884% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Mixture

This product is a mixture.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Common name Acrylic White Mastic.

Synonyms None.

Chemical nature Aqueous solution.

Chemical Name	CAS No.	Weight-%	Trade Secret
Calcium Carbonate	1317-65-3	10 - 20%	*
Titanium Dioxide	13463-67-7	0 - 10%	*
Amorphous Silica (Silicon Dioxide)	7631-86-9	0 - 10%	*
Aluminum Hydroxide	21645-51-2	0 - 10%	*

4. FIRST AID MEASURES

Description of first aid measures

General advice Under conditions of normal use, no hazards are anticipated which require special first aid

measures.

Eye contact In the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin contact Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a

physician.

Inhalation Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with

breathing is experienced, get medical attention immediately.

Ingestion Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical

attention immediately.

Self-protection of the first aider First aider: Pay attention to self-protection!.

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin irritation. May cause eye irritation.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Sand. Use foam or water FOG as a last resort.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

No information available.

Hazardous combustion productsThermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Explosion data

Sensitivity to Mechanical Impact Notsensitive. Sensitivity to Static Discharge Not sensitive.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions No action should be taken involving any personal risk or without suitable training. Use

personal protective equipment as required.

Other Information Extremely slippery when spilled.

Environmental precautions

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional

ecological information.

Methods and material for containment and cleaning up

Methods for containment Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous

earth, vermiculite.

Methods for cleaning up Pick up the absorbed material (described just above) and transfer to properly labeled

containers for disposal according to local / national regulations (see Section 13).

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing. Keep containers tightly closed in a cool, dry, well-ventilated place.

Incompatible materials Strong acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
		(vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	
Titanium Dioxide 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	IDLH: 5000 mg/m³ TWA: 2.4 mg/m³ CIB 63 fine TWA: 0.3 mg/m³ CIB 63 ultrafine, including engineered nanoscale
Amorphous Silica (Silicon Dioxide) 7631-86-9	-	TWA: 50 µg/m³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m³ <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO2) mg/m³ TWA	IDLH: 3000 mg/m³ TWA: 6 mg/m³
Aluminum Hydroxide 21645-51-2	TWA: 1 mg/m³ respirable particulate matter	-	-

Appropriate engineering controls

Engineering Controls None under normal outdoor use conditions.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing that is resistant to chemical penetration.

Respiratory protection No protective equipment is needed under normal use conditions.

General Hygiene Considerations Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated

clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Viscous

Odor Low **Appearance**

White Color Negligible odor. Odor threshold

Values Remarks • Method **Property**

Not applicable

None / 0 °C None / 32 °F Melting point/freezing point Melting Point is not applicable. Freezing points are

shown.

Boiling point / boiling range > 100 °C / 212 °F

Flash point Not applicable °C / Not applicable °FNon Flammable

Evaporation rate The evaporation rate of the water No data available. Evaporation rate is dependent

component of this emulsion product is upon atmospheric conditions.

dependent upon: 1) The temperature of the water at the air-water surface; 2) The humidity of the air; 3) The area of

the air-water surface; 4) The

Not flammable

No data available.

temperature of the air. No information

available

Flammability (solid, gas) Non Flammable

Flammability Limit in Air

Upper flammability limit:Not applicableLower flammability limit:Not applicable

Vapor pressure 2.33 (kPa) @ 20 °C

Vapor density 5.3 Where: Air = 1 at 68 degrees F (20 degrees C)

Specific Gravity 1.38 Water = 1g/ml

Water solubility Dispersible

Solubility in other solventsSoluble in aromatic and aliphatic

solvents.

Partition coefficient No information available

Autoignition temperature 330 °C / 626 °F

Decomposition temperatureNo information availableKinematic viscosityNo information availableDynamic viscosityNo information availableExplosive propertiesNot an explosive

Oxidizing properties None

Other Information

Softening point Not applicable

Molecular weight No information available

VOC Content (%)

Density

Bulk density

Less than 50 g/l

11.4 to 11.6 lb/gal

Not applicable

10. STABILITY AND REACTIVITY

Reactivity

Not applicable Not applicable

Chemical stability

Stable.

Possibility of Hazardous Reactions

None under normal use.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid

None known for product as a whole.

Incompatible materials

Strong acids. Strong oxidizing agents.

Hazardous Decomposition Products

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Toxicological testing has not been conducted for this product overall. Available toxicological

data for individual ingredients are summarized below.

Inhalation Avoid breathing vapors or mists.

Eye contact Avoid contact with eyes. Contact with eyes may cause irritation.

Skin contact May cause irritation.

Ingestion If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected

route of exposure.

Component Information The IARC Monograph (Vol 93, 2010, Carbon Black, Titanium Dioxide, Talc) states: "No

significant exposure to primary particles of Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints."

 Chemical Name
 Oral LD50
 Dermal LD50
 Inhalation LC50

 Titanium Dioxide
 > 10000 mg/kg (Rat)

 13463-67-7
 Amorphous Silica (Silicon Dioxide)
 = 7900 mg/kg (Rat)
 > 2000 mg/kg (Rabbit)
 > 2.2 mg/L (Rat) 1 h

 7631-86-9
 Aluminum Hydroxide
 > 5000 mg/kg (Rat)

 21645-51-2

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationCan cause skin irritation.

Serious eye damage/eye irritation Irritating to eyes.

Irritation Irritating to eyes and skin.

Corrosivity Not classified.

Sensitization May cause sensitization of susceptible persons.

Germ cell mutagenicityThis product does not contain any ingredients that cause germ cell mutagenicity.

Carcinogenicity The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed

any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium Dioxide	-	Group 2B	-	X
13463-67-7				
Amorphous Silica (Silicon	-	Group 3	Known	X
Dioxide)				
7631-86-9				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen.

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

None known for product as a whole.

None known for product as a whole.

Teratogenicity None known.

STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

12. ECOLOGICAL INFORMATION

Ecotoxicity

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable local, regional, national and international

laws and regulations.

Contaminated packaging Do not reuse container.

Note: This material is not subject to regulation as a hazardous material for shipping

14. TRANSPORT INFORMATION

DOT Not regulated.

TDG Not regulated.

MEX Not regulated.

ICAO (air) Not regulated.

IATA Not regulated.

<u>IMDG</u> Not regulated.

RID Not applicable in the United States. Not regulated.

ADR Not applicable in the United States. Not regulated.

ADN Not applicable in the United States. Not regulated.

15. REGULATORY INFORMATION

International Inventories

TSCA All of the components of this product are listed on the US TSCA (Toxic Substances Control

Act) Inventory or are exempt.

DSL/NDSL All of the components of this product are listed on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium Dioxide - 13463-67-7	Carcinogen
Amorphous Silica (Silicon Dioxide) - 7631-86-9	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Titanium Dioxide 13463-67-7	X	X	X
Amorphous Silica (Silicon Dioxide) 7631-86-9	-	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 1	Flammability 1	Instability 0	Physical and Chemical
<u>HMIS</u>	Health hazards 1	Flammability 1	Physical hazards 0	Properties - Personal protection -

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet