



80% Dry Air Compressors (90-125 PSI)

	dB	Gal	Hp	CFM @90PSI	Cabinet	SMART	vac/Amp
8010DSPC 	40	8	1.0	3.0	✓		110/7.6
8010DSPCAD (with auto drain) 	40	8	1.0	3.0	✓		110/7.6
10020DC/DCAD (with auto drain) 	70	10	2.0	5.3			110/14
10020DC-22060 	70	10	2.0	5.3			220/7.5
10020DCAD-22060 (with auto drain) 	70	10	2.0	5.3			220/7.5
10020DSMAD (with auto drain) 	70	10	2.0	5.3		✓	110/14
20040DC 	75	20	4.0	10.6			220/14
20040DCAD (with auto drain) 	75	20	4.0	10.6			220/14
20040DSPCAD (with auto drain) 	65	20	4.0	10.6	✓		220/14
60040DCAD (with auto drain) 	75	60 ASME	4.0	10.6			220/14

	dB	Gal	Hp	CFM @90PSI	Cabinet	SMART	vac/Amp
10020HDCADC 	70	10	2.0	5.3			110/14
10020HDCADC-22060 	70	10	2.0	5.3			220/7.5
10020HDSMADC 	70	10	2.0	5.3		✓	110/14
10020HDSPCADC 	58	10	2.0	5.3	✓		110/14
20040DCADC 	75	20	4.0	10.6			220/14
20040DSMADC 	75	20	4.0	10.6		✓	220/14
20040DSPCADC 	65	20	4.0	10.6	✓		220/14
60040DCADC 	75	60 ASME	4.0	10.6			220/14
60040DSMADC 	75	60 ASME	4.0	10.6		✓	220/14
20060DCC 	78	20	6.0	14.6			220/22



Sound Proof Cabinet Air Compressors (90-125 PSI)

8010SPC/SPCAD
(with optional auto drain)



8010DSPC/DSPCAD
(with optional auto drain)



10020SPC/SPCAD
(with optional auto drain)



10020SMSPC



10020DSPC



10020DSPCAD
(with auto drain)



10020HDSPCADC
(with auto drain)



20040SPCAD
(with auto drain)



20040DSPCAD
(with auto drain)



20040DSPCADC
(with auto drain)



dB	Gal	Hp	CFM @90PSI	Dry Air	SMART	vac/Amp
40	8	1.0	3.0			110/7.6
40	8	1.0	3.0	80%		110/7.6
58	10	2.0	5.3			110/14
58	10	2.0	5.3		✓	110/14
58	10	2.0	5.3	80%		110/14
58	10	2.0	5.3	80%		110/14
58	10	2.0	5.3	98% (ISO 8573 2.3.1)		110/14
65	20	4.0	10.6			220/14
65	20	4.0	10.6	80%		220/14
65	20	4.0	10.6	98% (ISO 8573 2.3.1)		220/14



Stationary 'Oil-Free' Air Compressors (90-125 PSI)

	dB	Gal	Hp	CFM @90PSI	Cabinet	SMART	vac/Amp
20040C 	75	20	4.0	10.6			220/14
20040SM 	75	20	4.0	10.6		✓	220/14
20040CAD (with auto drain) 	75	20	4.0	10.6			220/14
20040SMAD (with auto drain) 	75	20	4.0	10.6		✓	220/14
20040SPCAD (with auto drain) 	65	20	4.0	10.6	✓		220/14
60040CAD (ASME/with auto drain) 	75	60	4.0	10.6			220/14
60040SMAD (ASME/with auto drain) 	75	60	4.0	10.6		✓	220/14
20060CAD (with auto drain) 	78	20	6.0	14.6			220/24
60065C (ASME/3-Phase 208/230v) 	85	60	6.5	17.0			208-230 15A
80060C (ASME/1-Phase 208/230v) 	76	80	6.0	16.8			208-230 24A

SMART AIR COMPRESSORS

Standard and Dry Air Models

10020DSMAD

10 Gallon
2 HP Motor
125 PSI MAX
5.3 CFM @90PSI
70 Decibels
80% Dry Air

Automatic Drain Valve




SMART CONTROLLER

10020HDSMADC

10 Gallon
2 HP Motor
125 PSI MAX
5.3 CFM @90PSI
70 Decibels
98% Dry Air

ISO 8573 2.3.1 Compliant




SMART CONTROLLER

20040SM

20 Gallon
4 HP Motor
125 PSI MAX
10.6 CFM @90PSI
75 Decibels




SMART CONTROLLER

20040SMAD

20 Gallon
4 HP Motor
125 PSI MAX
10.6 CFM @90PSI
75 Decibels

Automatic Drain Valve




SMART CONTROLLER

20040DSMADC

20 Gallon
4 HP Motor
125 PSI MAX
10.6 CFM @90PSI
75 Decibels
98% Dry Air

Automatic Drain Valve




SMART CONTROLLER

60040SMAD

60 Gallon
4 HP Motor
125 PSI MAX
10.6 CFM @90PSI
75 Decibels

Automatic Drain Valve




SMART CONTROLLER

60040DSMADC

60 Gallon
4 HP Motor
125 PSI MAX
10.6 CFM @90PSI
75 Decibels
98% Dry Air

Automatic Drain Valve




SMART CONTROLLER

Remotely control ON/OFF times, Pressure Levels, etc. with Mobile/Desktop

