

REASONS TO USE SPACERS



Uniform spacing between tiles - Allows expansion & contraction of tiles, thus no cracking of tiles.



No lippage - Spacers

minimize lippage and

chipping of tile corners

is reduced.

Efficient tiling - Use of

No water seepage -Uniform tile spacing filled with Favicrete-100 TILE JOINT doesn't allow water seepage through tile gaps.

Favicrete -100 Epoxy Grout - Two Component .

For Interior & Exterior Applications

Favicrete-100 is a stain free epoxy grout for floor and wall applications on tile & stones, where is hygiene is of utmost importance such as bathroom, kitchens, living room, airports and high traffic areas. It is water & chemical resistant joint filler which is available in accolors, suitable for joints 2mm to 20mm, UV Resistant.

Applications: Kitchens, bathrooms, swimming pools, fountains, water bodies, hospitals, restaurant, cafeterias, light industrial applications and high traffic areas

- Advantages :
 100% Stainfree
- Strong and durable
- Chemical and temperature resistant
 Anti bacterial & Anti Fungal
- Colour-Fast
- Easy to Install and Clean
- Water cleanable When Fresh
- Non-Cracking or Powdering
- Available in a Range of 36 Colours
- Recommended For :

 Ceramic floor & Wall Tile
- Quarry tile Marble
- Stone
- Pavers
- Slate
- Porcelain tile/Vitrified tile

Coverage: Varies with Tile & Stone size and Grout Width

Packing: 1kg & 5kg units

Two Components:

Epoxy Two Component	1 kg	5 kg
Resin & Filler	0.900 kg	4.5 kg
Hardener	0.100 kg	0.5 kg

Colour: 36 Colors

Compliance : Meets the Following Standards °ANSI : 118.3 °EN 13888: RG2 °VOC : Very Low

Tile Size X Thickness					Joint Width			
in mm	1.5mm	2mm	3mm	4mm	6mm	8mm	10mm	12mm
100x100x3	342	264	177	133	90	68	55	46
150x150x4	385	296	198	149	100	75	61	51
200x150x5	348	269	181	136	91	69	55	46
150x300x6	340	263	175	132	88	66	53	44
300x300x6	515	394	263	198	132	100	80	67
450x300x7	530	405	270	202	135	101	81	68
600x450x8	664	506	337	253	169	127	101	85
600x600x8	750	591	394	295	197	148	119	99
600x900x11	654	515	343	258	171	129	103	86
900x900x12	749	590	393	295	197	148	118	99
Approximate sq.ft. coverage for glass mosaic								
TILE SIZE		JOINT W	/IDTH	JOINT DI	PTH			

Coverage: Approximate Sq Feet coverage per # 1 unit (5 kg) of Favicrete 100. As per the actual site the consumption vary accordingly. These Figures are for Inductive Purpose.



Favicrete Unsanded Grout

A carefully prepared blend of Portland cement, graded aggregates, polymer fortifiers and color-fast pigments. It is designed for joint width 1mm to 5mm, for porous & absorbent type tiles, non-vitreous clay tiles, and marble & glazed wall tiles. Suitable for internal and external applications.

Applications: Residential, commercial, external facades.

Mixing Ratio: Use approx.400 ml of water or FAVICRETE Grout Admix for 1 kg of FAVICRETE Unsanded Grout.

Coverage: Varies with tiles size and grout width.

Packaging: 1kg

For Tile Joints 1mm-5mm

Colour: Available in a range of 36 colours

Compliance: Meets the following standards ANSI: 118.6 EN 13888: CGI VOC: Very Low

Advantages:

- Colour-Fast
- Easy Maintenance
- Weather Resistant
- Non-Shrinking
- Non-Cracking
- · Easy Application and Clean up
- Non Wet Curing Required When used with FAVICRETE Grout Admix
- Available in a Range of 36 Colours

Recommended For:

- Ceramic floor & Wall Tile
- Quarry tile
- Stone
- Pavers
- · Porcelain tile/Vitrified tile

Coverage: Approximate sq.ft coverage per 10 kg Packet.

Tile Size X Thickness			Joi		
in mm	1mm	2mm	3mm	4mm	5mm
100x100x3	1057	539	366	278	227
150x150x4	1182	599	404	305	247
200x150x5	1079	545	368	277	224
150x300x6	1047	528	356	268	216
300x300x6	1566	788	529	397	319
450x300x7	1608	808	542	406	327
600x450x8	2007	1007	674	504	405
600x600x8	2341	1174	785	587	471
600x900x11	2041	1023	684	511	410
900x900x12	2338	1171	782	585	469
		1023		• • • •	

For Any Support Contact : +91 9560 870 630

Community Centre . Delhi -110092





Follow us on





Premium Favicrete-100 Epoxy Grout & Unsanded Grout



FAVIERETE

Build for Future

