

G3 CNC  
32 Bit DSP digital micro stepping driver  
DM556D

**Overview:**

The DM556D is a new generation high-performance digital stepper driver based on DSP with advanced control algorithm. The motors driven by DM556D can run with lower heating, smaller noise, and much less vibration than other drivers on the market. The DM556D's voltage is DC 24V-50V. It is suitable for all the 2-phase hybrid stepper motor whose current is less than 5.6A. There are 16 microstep settings on the DM556D. The maximum step number of DM556D is 51200 steps/rev (microstep is 1/256 ). Its current range is 2.1A-5.6A, and its output current has 8 stalls. DM556D has automatic semi-flow, over-voltage, under voltage, and over-current protection function.

**Features:**

1. 32-bit DSP, pure sine wave subdivision technology
2. Low-noise, low-vibration and low temperature rising
3. Voltage 24-50VDC
4. With 8 stalls output current setting, current range 2.1-5.6A
5. With 16 stalls microstep subdivision setting
6. Automatic half current, self-test, over voltage, under voltage, over current protection
7. Internal optical isolation, highest frequency response 200KHZ
8. Suitable for nema 23 to nema 34 stepper motor current under 5.6A

**Current selection:**

Peak	RMS	SW1	SW2	SW3
Default		OFF	OFF	OFF
2.1A	1.5A	ON	OFF	OFF
2.7A	1.9A	OFF	ON	OFF
3.2A	2.3A	ON	ON	OFF
3.8A	2.7A	OFF	OFF	ON
4.3A	3.1A	ON	OFF	ON
4.9A	3.5A	OFF	ON	ON
5.6A	4.0A	ON	ON	ON

**Microstep selection:**

Pulse/Rev	SW5	SW6	SW7	SW8
Default	ON	ON	ON	ON
800	OFF	ON	ON	ON
1600	ON	OFF	ON	ON
3200	OFF	OFF	ON	ON
6400	ON	ON	OFF	ON
12800	OFF	ON	OFF	ON
25600	ON	OFF	OFF	ON
51200	OFF	OFF	OFF	ON

1000	ON	ON	ON	OFF
2000	OFF	ON	ON	OFF
4000	ON	OFF	ON	OFF
5000	OFF	OFF	ON	OFF
8000	ON	ON	OFF	OFF
10000	OF	ON	OFF	OFF
20000	ON	OFF	OFF	OFF
40000	OFF	OFF	OFF	OFF

**Application:**

It can be applied in a variety of small scale automation equipment and instruments, such as labeling machine, cutting machine, packing machine, drawing machine, engraving machine, CNC machine. It always performs well when it is used in equipment which requires for low -vibration, low -noise, high-precision and high-velocity.

**Common Indicator:**

Phenomenon	Reason	Solution
The red indicator is on.	1. A short circuit of motor wires.	Inspect or change wires.
	2. The external voltage is over or low than the driver's working voltage.	Adjust the voltage to a reasonable range.

**Driver functions & descriptions:**

Driver function	Operating instructions
Output current setting	Users can set the driver output current by SW1-SW3 three switches. The setting of the specific output current, please refer to the instructions of the driver panel figure.
Microstep setting	Users can set the driver Microstep by the SW5-SW 8 four switches. The setting of the specific Microstep subdivision, please refer to the instructions of the driver panel figure.
Automatic half current function	Users can set the driver half flow function by SW4. "OFF" indicates the quiescent current is set to half of the dynamic current, that is to say, 0.5 seconds after the cessation of the pulse, current reduce to about half automatically. "ON" indicates the quiescent current and the dynamic current are the same. User can set SW4 to "OFF", in order to reduce motor and driver heating and improve reliability.
Signal interfaces	PUL+ and PUL- are the positive and negative side of control pulse signal; DIR+ and DIR- are the positive and negative side of direction signal; ENA+ and ENA - are the positive and negative side of enable signal.
Motor interfaces	A+ and A- are connected to a phase winding of motor; B+ and Bare connected to another phase winding of motor. If you need to backward, one of the phase windings can be reversed.
Power interfaces	It uses DC power supply. Recommended operating voltage is 24VDC-50VDC, and power consumption should be greater than 100W.
Indicator lights	There are two indicator lights. Power indicator is green. When the driver power on, the green light will always be lit. Fault indicator is red, when there is over-voltage or over-current fault, the red light will always be lit; after the driver fault is cleared, if re-power the red light will be off.

**Dimensions (mm):**



