



SILVERADO

LIGHTS AND ACCESSORIES GUIDE







Allegiant® Max



Allegiant® Max light bar features a low-profile, linear design that provides superior tri-color warning capability with (30) flash patterns, alley ground lights, built-in SignalMaster™, and integrated sync.




Reliant® S2



Reliant® S2 light bar features an ultra low-profile design that provides superior tri-color warning capability with (28) flash patterns and built-in SignalMaster all while being offered at a budget-friendly cost.





DynaFlare™



DynaFlare™ features a low-profile design that provides tri-color warning capability with (25) flash patterns all while being fully sealed with patent-pending, optically clear potting material to protect against harsh conditions.



**MicroPulse®
Wide Angle Pro**



MicroPulse® Wide Angle Pro's curved design and powerful LEDs provide an impressive 180-degree light spread featuring a downward projecting White light, making them ideal for mounting on side mirrors of work truck vehicles.



416300 Series



416300 Series is ideal for flush mounting in a variety of applications such as bumpers, tailgates, running boards, and inside of trunk lids and door panels.





MicroPulse® Ultra with various mounts



MicroPulse® Ultra light heads can be mounted to the interior rear window using adhesive mount kits.



MicroPulse® Ultra light heads have an ultra low-profile design available in three different sizes. Mount to the hood of your vehicle with drill-less hood mount kit.



With lens made of durable polycarbonate to protect against harsh conditions, models feature a fully encapsulated water-proof housing, which provides a barrier against moisture and condensation, making them suitable for a variety of applications.




FSDirect™

SIMPLE SAFER SOLUTION.

Unlock the full potential of your vehicle's operational efficiency with our innovative FSDirect™ solution. Our system is designed to provide unparalleled control and customization. Automated lighting control allows operators to concentrate on their tasks, ensuring that safety on the job remains a top priority.

That's Federal Signal Strength.



Learn more about
FSDirect™
visit fedsig.com

SCAN HERE



FEDERAL SIGNAL STRENGTH



Every moment of every day, we go beyond the call. Every decision driven by the safety of you and your community. Take comfort in our commitment to engineer the most reliable, durable, and high-performing products for your work vehicle.



SAFETY IN THIS MOMENT.

EXCLUSIVE TECHNOLOGIES TO KEEP YOUR COMMUNITY SAFE. THAT'S FEDERAL SIGNAL STRENGTH.



FS CONVERGENCE NETWORK enables true plug-and-play installation and programming.



FSLINK is an embedded software technology that utilizes a shared set of flash patterns and a common five-conductor cable to flash the patterns of Federal Signal's mini-light bars, beacons, and warning devices simultaneously or alternately.



FSJOIN is a programming feature designed to enhance customization across Federal Signal's visual and audible vehicle warning products.



HOTFOOT lighted mounting feet accommodate LED takedown and alley lights.



SPECTRALUX multicolor LED technology provides the ability for a single light head to change color while in operation.



ROC (RELIABLE ONBOARD CIRCUITRY™) technology eliminates approximately 85% of connection failure points found in a typical light bar.



RUMBLER Ideal for dense urban environments, Rumbler is a low-frequency siren that works simultaneously with a primary siren tone to penetrate solid material, allowing vehicle operators and nearby pedestrians to feel the sound waves.



SLR (SOLARIS LED ROTATOR) maximizes the LED light source for full light coverage. SLR rotators provide rotating, oscillating, flashing, and flood light functionality.



SOLARIS LED reflector technology maximizes optical efficiency and provides superior off-axis warning.



V-SHAPE light bar is mechanically designed to have a non-linear shape (V-Shape), providing an advantage in terms of off-axis warning performance compared to light bars with a traditional linear shape.




Q-SIREN The sound of the Q-Siren is a registered trademark of Federal Signal Corporation, and it provides a distinct, recognizable long-distance warning.

RISK REDUCTION DURING ON-ROAD WORK TRUCK OPERATIONS

How Vehicle Warning Lights Reduce the Risk of Accidents in Work Zones




Every second in a work zone matters to protect crews and motorists. Work truck operators face risk while performing essential tasks near traffic. Proper use of warning lights on work trucks provide clear, visual alerts that help drivers and pedestrians detect, recognize, and respond—reducing the risk of accidents and improving overall work zone safety.

It is all about safety in the moment—reducing accidents and making work zones safer.



WHAT ARE THE RISKS?

Risks to work truck operators and the public during an emergency response include:

- 
Physical Risks
 Risks of injury or death due to vehicle accidents
- 
Financial Implications
 Increased property damage, increased insurance premiums, and downtime for out of service work trucks
- 
Legal Exposure
 Potential for lawsuits

4 ELEMENTS OF RISK REDUCTION

An understanding of the factors associated with effective work truck warning light solutions that can minimize risks

Awareness of Human Factors

Humans process signals in three phases: detection, recognition, and response.

Proper Installation, Operation, and Maintenance

Ensuring the right system is installed, operated, and maintained for optimal safety.

Suitably Engineered Equipment


Choose and specify the products and technologies designed and best suited for your vehicle's specific vocation or application.

Knowledge of Industry Standards

Become familiar with the organizations that have established minimum performance standards for warning light devices.



HUMANS PROCESS SIGNALS IN THREE PHASES



- 1 Detection:**
 The driver's initial awareness of a signal
- 2 Recognition:**
 The driver determines what the signal is and what it means
- 3 Response:**
 The driver modifies behavior

CHEVROLET SILVERADO

MODEL	DESCRIPTION
Roof Mount Bars & Accessories	
HKB-UNH2	Hook mount kit, standard height foot, 51- and 53-inch light bars, 1500 2019-2026, 44-, 45-, and 48-inch light bars, 2500/3500 2019-2026
HKB-UNH3	Hook mount kit, standard height foot, 44-, 45-, and 48-inch light bars, 1500 2019-2026, 51- and 53-inch light bars, 2500/3500 2019-2026
210960-46	Roof mount bar, 46-inch
Grille Light Bracket	
MPSM6-LB	L-bracket for (1) MPS6U/MPSWP light
Hood Mount Bracket	
MPSM6U-HOOD	Hood mount bracket for (1) MPS6U/MPSWP light
Side Mirror Bracket	
MPSMW9-SIL19MIR	Pair of side mirror brackets, each bracket holds (1) MPSWP/MPSW9 light, 1500 2019-2026
Rocker Panel Brackets	
MPSM3-LB	L-bracket for (1) MPS3U light
MPSM3-DL	L-bracket for (2) MPS3U lights, side-by-side
MPSM6-LB	L-bracket for (1) MPS6U/MPSWP light
MPSM6-DL	L-bracket for (2) MPS6U/MPSWP lights, side-by-side
Running Board Bracket	
DR6BKT-RB-SIL19B	(1) 6-foot DynaFlare™ running board mounting bracket, 2019-2026
Rear Spoiler Bracket	
MPS6U-SIL19RS6	Rear spoiler bracket kit for (6) MPS6U lights, 2019-2026
Interior Mounts	
DRBKT-RW-SIL23	Rear window bracket kit for (1) 3-foot DynaFlare, 2023-2026
MPSM6U-WIN	Adhesive mount for (1) MPS6U light; kit includes 90°, 67°, 46°, and 30° shrouds
MPSM6U-WIN2	Adhesive mount for (2) MPS6U light; kit includes 90°, 67°, 46°, and 30° shrouds
MPSM12U-WIN	Adhesive mount for (1) MPS12U light; kit includes 90°, 67°, 46°, and 30° shrouds
MPSM12U-WIN2	Adhesive mount for (2) MPS12U light; kit includes 90°, 67°, 46°, and 30° shrouds
SIFMJS-AMBR2CS6	SpectraLux® ILS low-profile, split-front headliner, center-focused, Amber/White, Six-button Controller; -AMBR2CSP (splitter); -AMBR2CSM (interface module)
SLB-SIL19ND	8-head bracket, CN SignalMaster™ or Latitude™, drill-less, 2019-2026
XSMBKT01	Slip-on visor mount kit for (1) single- or dual-head XStream®
XSMBKT03	Universal headliner mount kit for (1) single- or dual-head XStream
OBDII Integration Cables	
OBDCABLE4-5	4-ft OBDII interface cable, 1500 2022-2026, 2500/3500 2023-2026
OBDCABLE20-5	20-ft OBDII interface cable, 1500 2022-2026, 2500/3500 2023-2026

