

OPTIMA BATTERY – INTERSTATE BATTERY

1. Remove support bumps from the underside of the top cover using fine grit sand paper.
2. Align the top cover holes with the battery posts and apply gentle pressure to the top of the cover with a toothpick in several locations until the cover is against the battery, (No glue is necessary but is optional)
3. Remove 1/16 in of insulation from the red wire. Dip the end of the wire in super glue and insert into the terminal end while still attached to the supports. Repeat the process again for the black wire.
4. Gently remove the battery terminals from the supports using a toothpick.
5. Apply even pressure onto the terminal over the battery post using a toothpick (again, glue is optional)
6. For a better appearance, dab the terminals and top posts with a Molotov Chrome Pen after installation

VINTAGE BATTERY

1. Remove cell caps from the supports with tweezers and insert them into the 6 vent holes in the top of the battery. No glue is necessary. **CAUTION:** these tiny caps are impossible to find in carpet! We highly recommend building a 3 sided shield with foam board anytime you are working with small parts!
2. Remove 1/16 in of insulation from the red wire. Dip the end of the wire in super glue and insert into the terminal end while still attached to the supports. Repeat the process again for the black wire.
3. Gently remove the battery terminals from the supports using a toothpick.
4. Apply even pressure onto the terminal over the battery post using a toothpick (again, glue is optional.
5. For a better appearance, dab the terminals and top posts with a Molotov Chrome Pen after installation

DECAL

1. Cut decal as close as possible to the graphics using scissors or hobby knife.
2. Soak decal in luke warm distilled water for 20 seconds
3. Set decal to the side and wait for 30-45 seconds
4. Use a toothpick to slide the decal onto the battery
5. Once decal is in desired position, dab with a q-tip
6. Use a decal set solution over decal if more movement is required. We like Testors decal set 8804TT and a paint brush. Dab once more with a q-tip.
7. Seal decal to the battery with some clear spray. Tamiya clear is our preference.

If you loose any parts or ruin a decal.....simply mention your needs on your next order and a replacement will be provided at no extra charge.