



Technical Data Sheet

PRODUCT NAME:	KARMA PREMIER
DESCRIPTION:	Karma Premier is a high performance bitumen coating containing Gilsonite and synthetic resin which exhibits a deep black gloss finish. It is suitable for application to iron & steel and weathered masonry.
USE:	Having excellent weather and abrasion resistance, allied to a degree of oil & diesel resistance Karma Premier will have a longer life than conventional bitumen coatings. Easy to apply, Karma Premier makes an ideal refresher coat over any narrow boat bottom blacking.
SURFACE PREPARATION:	New Work: Clean/de-rust to bright metal. Abrade with coarse wet & dry. Degrease. Refurbishment: Pressure clean; de-rust as required and patch treat before full application.
APPLICATION:	Apply by brush; roller or airless spray. Use as supplied; if required thin with White Spirit. Apply 3 coats on new work; 1-2 coats on refurbishment Minimum application temperature: 10°C
DRYING/OVERCOATING:	Drying time(10°C) 6-8 hours Overcoating time(10°C) 24 hours Launch time(10°C) 48 hours
PHYSICAL PROPERTIES:	Mixing Ratio Single pack product Thinner/Cleaner White Spirit Supply Viscosity 240 Seconds/ISO 6 Cup/23°C ± 5% Supply SG 0.92 Colour Deep Black Gloss Level Gloss Theoretical Coverage: 8 square metres per litre per coat VOC Content: 440 grammes per litre Flash Point / Class / UN No ≥32°C & ≤55°C / III / UN 1263 Pack Size 5 & 20 litre containers Shelf Life 12 months unopened, stored at UK ambient temperatures. Health & safety: Refer to Product Safety Data Sheet before use.
CLEANUP:	All equipment should be cleaned immediately after use with White Spirit. Waste materials, including packaging, must be disposed of in accordance with local regulations.

This information is given in good faith for the guidance of users, but is without warranty or liability. Any queries should be referred to our technical department,

Karma Coatings Limited
2 Sefton Road, Litherland, Liverpool, L21 7PG
Tel: 0151 284 9091 Fax: 0151 284 3305 Email: sales@karmacoatings.co.uk