









### Yaweh Telescopic Arm

A. Size			D. Engine		
1	Outline (mm)	7400*2000*2850	1	Model	YN 4102
2	Wheelbase (mm)	2600	2	Type	Turbo
3	Wheeltrack (mm)	1560	3	Rated Power (KW)	88
4	Min Ground Clearance (mm)	320	4	Rated Speed (r/min)	2400
<b>B. Performances</b>			5	Cylinders # - Dia.	4-102
1	System Pressure (Mpa)	16	<b>E. Driving System</b>		
2	Weight (kg)	6500	1	Transmission	power shift
3	Max Speed (Km/h)	35	2	Gear	front 2 and back 2
4	Max Climbing Capability (°)	35	3	Hyd. Torque Converter	280 high/low speed
5	Minimum Turning Radius (mm)	5330	<b>F. Steering System</b>		
<b>C. Telescopic Arm</b>			1	Type	Hinged hyd. rotary
1	Max Lifting Height (mm)	9000	2	Turning Angle (°)	38
2	Max Unloading Height (mm)	6800	<b>J. Bridge</b>		
3	Max Unloading Distance (mm)	1200	1	Type	Mid/Large Wheel Edge
4	Max Loading Cap.	2500	<b>H. Tyre</b>		
5	Max Loading Cap. At Longest	1000	1	Dimention	16/70-20
6	Bucket Width (mm)	2000	2	Service Brake	Air/Oil Disc Brake
7	Bucket Capacity (m <sup>3</sup> )	1	3	Parking Brake	Hand Brake
			<b>I. Others</b>		
			1	Driving Type	Four Wheel
			2	Gear Type	Hydraulic
			3	Operating System	Electric-Hydraulic
Specific parameter changes are subject to the actual object					