


Advanced Strip Fixture

ASF

Features

- Shallow depth provides low profile appeal
- Surface mounting, pendant mounting, or chain hanging as single or continuous row
- Socket bars, end plates, and ballast covers snap on for tool free assembly
- Body is die formed 22 ga. baked white enamel with embossed ceiling bumps
- Ballast covers are die formed 24 ga. baked white enamel
- Made in the USA



Electrical Components

- All ballasts and lamp holders are UL and CSA listed
- Ballasts are Class P Thermally Protected, Type 1 Outdoor, Class A Sound Rated
- Quick Disconnect
- UL listed to US and Canadian safety standards
- Lamps and ballasts warranted through their respective manufacturer

Ordering Options

Example: ASF42T8-IL-L3241

Kit	Dimensions/Watts		Ballast Type (120v-277v or Custom)		Lamps			
					Wattage	Color		
ASF	4' 2 Lamp T8	42T8	IS, High-Efficiency, Low BF (.78)	IL	32W	L32	5000K	50
	4' 1 Lamp T8	41T8	IS, High-Efficiency, Normal BF (.88)	IN	30W	L30	4100K	41
	8' 4 Lamp T8	84T8	IS, High-Efficiency, High BF (1.2)	IH	28W	L28	3500K	35
	8' 2 Lamp T8	82T8	Programmed Start, Low BF (.71)	PL	Custom	CU		
			Programmed Start, Normal BF (.88)	PN				
			Programmed Start, High BF (1.2)	PH				
			Custom	CU				