

## Features


- Surface mount, pendant mounting, or chain hanging as single or continuous row
- Body constructed with 22 ga. steel, baked white enamel
- Reflector constructed with 24 ga. steel with high reflective paint
- Reflector secured by quarter turn or screws
- Socket bars and end caps snap in for tool free assembly
- Made in the USA



## Electrical Components

- All ballasts and lamp holders are UL and CSA listed
- Ballasts are Class P Thermally Protected, Type 1 Outdoor, Class A Sound Rated
- Quick Disconnect
- Lamps and ballasts warranted through their respective manufacturer
- UL listed to US and Canadian safety standards

## Dimensions



## Ordering Options

Example: ASIF84T8-IL-L3241

Kit	Dimensions/		Shield			Ballast Type (120v-277v or Custom)		Lamps			
	Watts						Wattage		Color		
ASIF	4' 2 Lamp T8	42T8	Solid	(blank)		IS, High-Efficiency, Low BF (.78)	IL	32W	L32	5000K	50
	4' 1 Lamp T8	41T8	Slotted	SL		IS, High-Efficiency, Normal BF (.88)	IN	30W	L30	4100K	41
	8' 2 Lamp T8	82T8				IS, High-Efficiency, High BF (1.2)	IH	28W	L28	3500K	35
	8' 4 Lamp T8	84T8				Programmed Start, Low BF (.71)	PL	Custom	CU		
						Programmed Start, Normal BF (.88)	PN				
						Programmed Start, High BF (1.2)	PH				
						Custom	CU				

### Aligner Clips

Metal	M
Plastic	P