

<b>EMP Shield Product Specifications</b>	<b>ANT-S200</b>
Phase:	N/A
Nominal System Voltage:	300V DC
Maximum Surge Per Phase:	N/A
Maximum Surge Per Line	32kA (8-20 microseconds)
Short Circuit Current Rating:	N/A
Nominal Discharge Current:	32kA (8-20 microseconds)
Number of Poles:	N/A
Enclosure Material	Plastic
NEMA Rating:	NEMA 4
Application:	Coax plug to antenna
Color:	Black
Features:	Coax connectors (SO-39)
For Maximum Wire Size:	N/A
For Use With:	200 Watt Antenna
Frequency:	N/A
IP Rating Met:	IP66
Maximum Continuing Operating Voltage:	N/A
Maximum Surge Current Per Mode:	32kA (8-20 microseconds)
Modes of Protection:	N/A
Mounting Style:	Coax connectors (SO-39)
Number of Wires:	N/A
Overall Height:	1-1/2"
Overall Length:	4"
Overall Width:	1-1/2"
Specification Met:	UL 1449; CE; IP66; MIL-STD-188-125-1; MIL-STD-461G; MIL-STD-464C; and RS105
Voltage Protection Rating:	400V DC
Response Time:	< 1 nanoseconds