




Revolutionary Solar Racking Systems



IR MultiBallast INSTALL INSTRUCTIONS

Warranty & Disclaimer	2
Included Components & Required Tools	3
MultiBallast Configurations	4
Layout Planning	5
Solar Panel Spacing	6
Electrical Bonding	7
UL 2703 & Mounting Restrictions	8
Assembly & Fastener Locations	9
IR-W5MBCB - Layout & Bonding Example	10
IR-08MBCB - Layout & Bonding Example	11
Interlocking Components	12
H Brackets & Mounting Options	13
IR-W5MBCB Assembly & Install	14
IR-08MBCB Assembly & Install	17
Solar Panel Mounting	19



IntegraRack® backs all of its products with a 25 year limited product warranty. We fully stand by the quality and guarantee that they will hold up under the harshest conditions when properly installed.

Disclaimer



The instructions detailed in this manual will provide the knowledge and requirements necessary for proper installation of the given product. Be sure to read them thoroughly and make sure that you fully understand them before proceeding with installation. Any improper use or installation of these products will void any and all warranty coverage, and may cause failure, property damage or personal injury. IntegraRack is not responsible for any damages caused by improper use.

IT IS THE RESPONSIBILITY OF THE INSTALLER TO:

- Comply with any and all applicable local or national codes and regulations.
- Ensure all products are appropriate for the installation according to the environmental and loading conditions.
- Ensure roof structure is in good condition prior to installation
- Disconnect AC power before servicing or removing panels, micro-inverters or power optimizers.
- Review manufacturer's documentation for compatibility and compliance for solar panels and 3rd party systems.
- If loose components or loose fasteners are found during periodic inspection, re-tighten immediately. Any components showing signs of corrosion or damage that compromise safety shall be replaced immediately.
- Provide an appropriate method of direct-to-earth grounding according to the latest edition of the National Electrical Code, including NEC 250: Grounding and Bonding, and NEC 690: Solar Photovoltaic Systems.
- Ensure safe installation of all electrical aspects of the solar system (All electrical installation and procedures should be conducted by a licensed and bonded electrician or solar contractor). Regular maintenance of a panel or panel shall not involve breaking or disturbing the bonding path of the system. All work must comply with national, state and local installation procedures, product and safety standards.
- Ensure bare copper grounding wire does not contact aluminum and zinc-plated steel components, to prevent risk of galvanic corrosion.
- Ensure provided information is accurate. Issues resulting from inaccurate information are the installer's responsibility.

Included Components & Required Tools

Included Components




IR-W5MBCB

- (2) Base Mounts
- (2) H Module Mounting Brackets
- (4) IR-F2 Flange Clamp Bonding Brackets
- (2) Bolt Bs

IR-08MBCB

- (2) Base Mounts
- (2) Riser Brackets
- (2) H Module Mounting Brackets
- (4) IR-F2 Flange Clamp Bonding Brackets
- (2) Bolt As
- (2) Bolt Bs



Base Mount



Riser Bracket



H Module Mounting Bracket



IR-F2 Solar Panel Flange Clamp Bonding Bracket



Bolt A (10mm)



Bolt B (20mm)

Ballasting - Required Materials (Not Included)

IR-W5MBCB

- (2) CMU Blocks Per Kit

IR-08MBCB

- (2) CMU Blocks Per Kit
- (1) Wind Spoiler Per Solar Panel

IR-13MBCB

- (4) CMU Blocks Per Kit
- (1) Wind Spoiler Per Solar Panel
- (1) Wind Spoiler Per Row

IR-20MBCB

- (6) CMU Blocks Per Kit
- (2) Wind Spoiler Per Solar Panel

Adhesive Bonding - Required Materials (Not Included)

IR-W5MBCB

- (1) Tube of Sikaflex Polyurethane Sealant for every ten mounts

IR-08MBCB

- (1) Tube of Sikaflex Polyurethane Sealant for every ten mounts

IR-13MBCB

- (1) Tube of Sikaflex Polyurethane Sealant for every ten mounts

IR-20MBCB

- (1) Tube of Sikaflex Polyurethane Sealant for every ten mounts

Required Tools


- 1/2" (13mm) Ratchet Wrench
- Line Chalk
- Tape Measure
- Hammer

MultiBallast Configurations


Configurations

IR-W5MBCB MultiBallast

5° East/West 'W' Configuration




0° Flat Configuration



IR-08MBCB MultiBallast

8° North/South Configuration



IntegraRack MultiBallast Kits

All IntegraRack MultiBallast mounts are sold in "Per Solar Panel Kits". For most MultiBallast configuration you will need one kit for each installed solar panel plus one additional kit to start each row of solar panels. The MultiBallast system is meant to be ballasted using a standard solid CMU block (Dimensions: 4x8x16"), but can also be directly bonded to the roof using our recommended polyurethane adhesive. With the IR-8MBCB MultiBallast system, one Wind Spoiler (sold separately) will be required for each solar panel installed.

How Many Kits Will I Need?

IR-W5MBCB MultiBallast

- (1) IR-W5MBCB Kit per solar panel
- (1) IR-W5MBCB Kit to start each row

IR-08MBCB MultiBallast

- (1) IR-08MBCB Kit per solar panel
- (1) IR-W5MBCB Kit to start each row

Planning the Layout of the Solar Array

MultiBallast Pair Spacing

This system is designed to fit solar panels of any size in landscape orientation. The spacing measurement is the spacing between the pair of MultiBallast mounts in front of each panel and will be determined by the length of your panel and the manufacturer recommended mounting points (see Mounting Restrictions on page 8). The typical mounting points are going to be 15-25% of the length of your solar panel measuring from the nearest end (see Figure A). For easier calculations, place the center of the MultiBallast at the recommended mounting points according to the solar panel manufacturers specified mounting points.

**In order to meet the expected wind and snow load ratings, the overhang of your solar panel should never exceed 25% of its total length.*




Figure A

Spacing Between MultiBallast Pairs

To determine the spacing between rows, you will need to use the overhang measurement from the previous step. Multiply the overhang measurement by 2 and add the required 1/4" minimum space in between the panels. This spacing measurement will be from center to center of the MultiBallast mounts.





Figure B

Solar Panel Spacing


Determining Spacing For Your Panels

Return to this step after completing assembly



Lay out four assembled mounts in order to test mount a single solar panel. Measure the width of your solar panel and space each pair of mounts apart that width, plus about $\frac{1}{8}$ " from H Bracket to H Bracket



Rest your solar panel onto the mounts and push the rear mounts forward until the panel is firmly fitted in between the closest H Brackets




Measure the space in between the Base Mounts to determine your spacing for the entire system



Electrical Bonding


Electrical Bonding Between Panels / IR-F2 Clamps



Solar Module Mounting


The IR-F2 is designed to clamp the solar module firmly to the racking system, while also bonding the solar panels together. The two sharp piercing barbs are designed to penetrate the anodized aluminum solar panel frame for proper bonding / grounding from solar panel to solar panel.

INTEGRATED ZIP TIE SLOT FOR WIRE MANAGEMENT



Integrated Wire Management

When using the integrated wire management with the IR BallastRack system, it is best to run your wires near the front legs with enough slack for the panels to move freely during seasonal adjustment.




Pre-Inspection of IR-F2 Clamps

Before or during any installation or re-installation of this component, it is important to ensure that all fasteners are clean and free of damage or signs of corrosion. It is also important to make sure that the bolt is tightened properly. If the bolt is able to move in any way, the inner nut must be tightened.

Torque Specs: 10 ft-lbs (120 in-lbs)

Electrical Bonding Between Rows / IR-B1 Jumpers



IR-B1 Bonding Jumpers

For bonding between rows of panels, we offer our 8" and 12" IR-B1 Bonding Jumpers that are UL 2703 recognized. The bonding jumpers have small internal bonding barbs and they clamp to the bottom inner flange of the solar panels to provide bonding from row to row.

UL 2703 & Mounting Restrictions


UL 2703 Compliance

The IR-F2 Flange Clamp Bonding Bracket has been evaluated by UL to ensure compliance with the bonding and grounding requirements has been met. As specified in UL 61730-1 5.2.3DV, PV modules are considered to be in compliance with the mechanical loading and bonding and grounding requirements of UL 61730-1 when mounted, bonded and grounded in the manner specified by either the PV module mounting instructions, or the mounting system manufacturer's instructions when the mounting, bonding, and grounding means have been evaluated with the PV module to UL 2703.



Bonding Overcurrent Protection Rating: 25A

Mounting Restrictions


The IR-F2 can be mounted anywhere along the flange of the solar panel, but it is important to install this bracket in accordance with the solar panel manufacturer's recommended clamping zones, typically found in the installation instructions provided by the solar panel manufacturer. For most solar panels, the ideal clamping zone is $\frac{1}{4}$ of the solar panels length in from each end, leaving $\frac{1}{2}$ of the solar panels length between two of the clamps (see example below)




Assembly & Fastener Locations



IR-W5MBCB - Layout & Bonding Example



IR-08MBCB - Layout & Bonding Example



Interlocking Components




IMPORTANT



Male to Female Extrusions

Note that all Base Mounts and Riser Brackets have both male and female extrusions for interlocking the parts together to form the configurations. Pay attention to the orientation of each component as you read the instructions. The male extrusion also doubles as the H Module Bracket slot.

MALE



FEMALE




Riser
Connecting Slot

H Brackets & Mounting Options


Installing H Brackets

The MultiBallast Riser Brackets already have the H Module Mounting Brackets installed, but you will need to install the H Module Brackets on your Base Mounts. The position of the H Module Mounting Brackets are dependent on your chosen configuration (see assembly instructions for exact mounting location of the H Brackets).


1. Slide the H Module Mounting Bracket into the slot as far as you can by hand



2. Use a hammer to tap the H Module Mounting Bracket all the way into the slot until it is flush with the side of the Base Mount (The H Module Mounting Bracket does not need to be centered on the Base Mount)




3. The specific mounting locations for the H Module Mounting Brackets can be found in the assembly instructions for your chosen configuration



Placing the Ballast Block

Skip to the page below to see assembly instructions for your chosen configuration for steps on how to lock the CMU blocks in position


- IR-W5MBCB - Page 12
- IR-08MBCB - Page 15
- IR-13MBCB - Page 17
- IR-20MBCB - Page 20



CMU Block Dimensions

Adhesive Bonding (Optional)


If ballasting is not an option for your install, up to ten Base Mounts can be directly bonded to the roof surface using one tube of Sikaflex 1A Polyurethane Sealant. Apply a bead to each of the roof-touching-surfaces of the Base Mounts in a zig-zag pattern.




IR-W5MBCB Assembly & Install

IR-W5MBCB Assembly - East/West 'W' Conf.


1. Install an H Module Mounting Bracket into Slot M3 of each row-starting Base Mount and half of the other Base Mounts




2. Install an H Module Mounting Bracket into Slot M1 of each of the remaining Base Mounts



3. Place the CMU blocks in all Base Mounts





4. Lock the CMU block in place by inserting 1x Bolt B into the marked hole on each Base Mount and use a ½" (13mm) wrench to tighten the bolts until they start to dig into the CMU block







IR-W5MBCB Assembly & Install

IR-W5MBCB Layout - East/West 'W' Conf.

5. Place the row-starting Base Mounts








6. Place the upright Base Mounts next



7. Repeat this formation for the rest of the row




Skip to page 19 for solar panel mounting




IR-W5MBCB Assembly & Install

IR-W5MBCB Assembly - 0° Flat Conf.


1. Install an H Module Mounting Bracket into Slot M3 on all Base Mounts



2. Place the CMU blocks in all Base Mounts




3. Lock the CMU block in place by inserting 1x Bolt B into the marked hole on each Base Mount and use a ½" (13mm) wrench to tighten the bolts until they start to dig into the CMU block



IR-W5MBCB Layout - 0° Flat Conf.

4. Place all Base Mounts in position on the roof




Skip to page 19 for solar panel mounting


IR-08MBCB Assembly & Install

IR-08MBCB Assembly


1. Install an H Module Mounting Bracket into Slot M3 on all Base Mounts (including all row-starters)




2. Place the CMU blocks in all Base Mounts




3. Lock the CMU block in place by inserting 1x Bolt B into the marked hole on each Base Mount and use a ½" (13mm) wrench to tighten the bolts until they start to dig into the CMU block



4. Slide the Riser Bracket onto Slot M2 on all Base Mounts









5. Insert 1x Bolt A into the hole at the bottom of the Riser Bracket and use a ½" (13mm) wrench to lock the Riser Bracket in place



IR-08MBCB Assembly & Install

IR-08MBCB Layout


6. Place the row-starting Base Mounts



7. Place all remaining IR-08MBCB mounts to the end of the row


IR-08MBCB Wind Spoiler

8. Slide the Wind Spoiler into the cutouts on each Riser Bracket



9. Insert 1x Bolt B into the front of each Riser Bracket and tighten it until it is tight against the Wind Spoiler (DO NOT overtighten)

10. Install 1x Wind Spoiler behind each panel




Go to the next page for solar panel mounting

Solar Panel Mounting


The solar panel mounting steps below are for all MultiBallast configurations

- 11.** Set the solar panel onto the mounts and make sure it fits snug in between the H Module Mounting Brackets




- 12.** Remove the serrated nut from the end of each IR-F2 Solar Module Flange Clamp Bonding Bracket

- 13.** Lift up the solar panel and slide the open slot on the sides of the IR-F2 onto the inner flange of the panel



- 14.** Drop the bolt of the IR-F2 into the open slot of the H Module Mounting Bracket

- 15.** Fasten the serrated nut onto the end of the IR-F2 bolt and tighten by hand for now



- 16.** Install the remaining IR-F2s and tighten all of the serrated nuts with a ½" (13mm) wrench



More MultiBallast Info



**See Our Other
Revolutionary Products**



©IntegraRack 2024, All Rights Reserved. Multiple US Patents Pending

www.IntegraRack.com