

Black Carbon Steel Pipe

STANDARD: ASTM A795

CERTIFICATIONS: FM, UL, API

SURFACE PREPARATION: black painted

QUALITY TOLERANCE: +/- 5%

LENGTH: 19ft

COUNTRY OF ORIGIN: China

NOMINAL DIAMETER		OUTSIDE DIAMETER		SCH	WALL THICKNESS		NOMINAL WEIGHT		TEST PRESSURE		TYPE
(mm)	(inch)	(mm)	(inch)		(mm)	(inch)	(kg/m)	(lb/ft)	PSI	MPa	
10	3/8	17.10	0.675	40	2.31	0.91	0.84	0.57	700	4.8	seamless
15	1/2	21.30	0.839	40	2.77	0.109	1.27	0.86	700	4.8	seamless
25	1	33.4	1.315	40	3.38	0.133	2.50	1.69	700	4.8	seamless
32	1 1/4	42.2	1.66	40	3.56	0.140	3.39	2.27	1000	6.9	seamless
40	1 1/2	48.3	1.90	40	3.68	0.145	4.04	2.74	1100	7.6	seamless
50	2	60.3	2.375	40	3.91	0.154	5.46	3.68	2500	17.2	seamless
65	2 1/2	73.0	2.875	40	5.16	0.203	8.67	5.85	2500	17.2	seamless
80	3	88.90	3.5	40	5.49	0.216	11.29	7.58	2500	17.2	seamless
150	6	168.10	6.618	80	10.97	0.432	43.05	28.88	2700	18.6	seamless
65	2 1/2	73	2.875	10	3.05	0.12	5.26	3.53	1000	6.9	ERW
80	3	88.90	3.5	10	3.18	0.125	6.72	4.51	1500	10	ERW
100	4	114.3	4.50	10	3.18	0.125	8.71	5.85	1170	8.1	ERW
150	6	168.3	6.625	10	4.78	0.188	19.27	12.94	1190	8.2	ERW



V.S.V. Industrial Solutions Ltd.
 Pacific Avenue, Point Lisas Industrial Estate, Point Lisas
admin@vsvtt.com
vsvtt.com
 1-868-348-4VSV



V.S.V. Industrial Solutions Ltd.
Pacific Avenue, Point Lisas Industrial Estate, Point Lisas
admin@vsvtt.com
vsvtt.com
1-868-348-4VSV

