

Unified youth compacts 2024

Top Tech Promotions

Oklahoma Boys Promotions

Outlaw Promotions

- 1) All car prep is same as other classes. All debris, glass, and any flammable must be removed. Carburetor conversions are allowed. Will allow a simple carb protector. Headers allowed as well.
- 2) Wheel base is 110" max!
- 3) No trucks, SUV, or mini vans. No V8s
- 4) Bumpers may be interchangeable. Bumpers must be an OEM factory car bumper of some sort! No Chrysler pointys period! If you don't have the access or the funds to buy a bumper will allow a single piece of 4x4x1/4" square tube to be used as the bumper, but the ends must be open and nothing added to the square tube! No bumper brackets allowed unless they are the factory brackets and shocks for that car.. bumper may be welded to the shock. May collapse the shock.. do not weld the the shock or the brackets to the frame.. may use 1 piece of 3/8" chain per side to bolt bumper to frame rail. You may hard-nose if you choose. May only weld bumper to frame with one 1/2" pass all the way around. If doing so factory shocks and brackets must be removed. No other material may be used at all!
- 5) No body bolts may be changed. Do not even touch them period! If one is rotted out or missing you may use a single loop of 9 wire to tie it back. If body bolts or cradle bolts have been changed you will remove them or will not be permitted to run!
- 6) No after market suspension, no reinforcing steering or suspension components period! May weld struts to gain bumper height but don't reinforce them. All parts must be stock.
- 7) You may run aftermarket pedal setup.. must not re inforce car in any way! After market steering allowed also may not re inforce car in any way.

- 8) A 4pt. Cage will be allowed. May have 1 down bar per side of the car in the middle of the front doors. Must be cage to sheet metal only! This is for safety period!. Door bars or and seat bar Cannot go any further back than 6 inches behind front door seam!! Halo is allowed. Must be vertical and go to top side of cage..cannot go to the floor. Gas tank protector is allowed. Must be positioned in center of seat bar. Can only be 24" wide. Must be 6" from any sheet metal, this includes doors, wheel wells, floor, and package tray. I know cars are different but you choose the cars not us! No cage material may exceed 4" material.

- 9) Hood may be left on stock hinges. Hoods may be secured in 2 spots per side using one of two ways. You may have two pieces of 3/8" chain max per side or 2 hood clips per side. Max of 2x2x2 long with (1) 1/2" bolt per clip to bolt hoods down. In addition you can have (1) 3/4" piece of all thread per side. All thread can run through the core support mount extending through the hood as a hood bolt. Factory rubber bushing must be in place. No welding all thread in place.

- 10) Trunk deck may be folded with 1 90° bend, left in complete stock location, or removed.. no v wedging. If you run a deck lid it may be fastened one of 3 ways, but must pick one of the 3. May have 3 places with 3/8" chain, 3 places with "9 wire, or you may have 3- 2"x3" by 1/8" strap welded. Pick one method not all 3.

- 11) Car must have a window bar of some sort. Piece of strap welded, 9 wire, or ratchet straps but must have something!!

- 12.) You may run factory metal tank as long as it is in front of the rear axle or moved inside the driver's compartment, covered and securely fastened.. no plastic tanks!! Aftermarket fuel cell is encouraged.

- 13) Driver's door may be welded solid with 3" wide by 1/8" thick strap. All other doors may have 2 3x4" x 1/8" pieces of strap welded.. pillars may be duct taped.. if you choose to chain or 9 wire doors that is fine may have 3 pieces per door and may duct tape pillars as well... only 1 of the 3 methods may be used!!

- 14) No frame welding whatsoever!!! Only exception is on pre-ran cars you may have 1 4x6x1/4" plate per rail... must be on the rail not the cradle.. may be located on any

side of the exterior of the frame.. if it covers a frame hole have a 1/2" hole pre cut or you will cut one.. any questions call!!!!

15) Solid fork lift tires will be allowed on the back of fwd cars. All other wheels may only have a small center.. skidders are allowed no foam filled tires or solid tires allowed on the drives axels period!

16) Rwd cars all leaf springs must remain factory. No added leafs or leaf clamps period!

17) All cars are permitted 3 places of 9 wire. 2 loops making 4 strands... may be ran however you'd like.

18) All cars must have a 1/2" inspection hole 3" behind the front bumper, in the middle of the frame, on the wheel side of the frame for tech. Anything found inside the frame you will be loaded.

19) Any other damage repair on pre ran cars will be at promoters discretion. Call the promoter for that show with any questions.

All judges decisions are final. Any arguing or fighting and you will not run.

Outlaw Promotions and Oklahoma Boys Promotions shows have age requirements are 10yrs old to 15yrs old.

Top Tech Promotions is 12yrs old to 15yrs old. Any other questions reach out to the contacts below.

Gage Lahey- Top Tech Promotions

620-423-5054

Rusty Owens- Outlaw Promotions

620-388-0510

Wade Daniels- Oklahoma Boys Promotions

620-778-0119