



Article 310 Conductors for General Wiring Comparison Chart (2017 NEC to 2020 NEC)

2020 NEC	Topic	2017 NEC
Part I	General	Part I
310.1	Scope	310.1
310.2	Definitions	310.2
310.3	Conductors	310.106
310.3(A)	Minimum Size of Conductors	310.106(A)
310.3(B)	Conductor Material	310.106(B)
310.3(C)	Stranded Conductors	310.106(C)
310.3(D)	Insulated	310.106(D)
Part II	Construction Specifications	Part III
310.4	Conductor Constructions and Applications	310.104
Table 310.4(A)	Conductor Applications and Insulations Rated 600 Volts	Table 310.104(A)
Table 310.4(B)	Thickness of Insulation for Nonshielded Types RHH and RHW Solid Dielectric Insulated Conductors Rated 2000 Volts	Table 310.104(B)
310.6	Conductor Identification	310.110
310.6(A)	Grounded Conductors	310.110(A)
310.6(B)	Equipment Grounding Conductors	310.110(B)
310.6(C)	Ungrounded Conductors	310.110(C)



Article 310 Conductors for General Wiring Comparison Chart (2017 NEC to 2020 NEC)

2020 NEC	Topic	2017 NEC
310.8	Marking	310.120
310.8(A)	Required Information	310.120(A)
310.8(B)	Method of Marking	310.120(B)
310.8(B)(1)	Surface Marking	310.120(B)(1)
310.8(B)(2)	Marker Tape	310.120(B)(2)
310.8(B)(3)	Tag Marking	310.120(B)(3)
310.8(B)(4)	Optional Marking of Wire Size	310.120(B)(4)
310.8(C)	Suffixes to Designate Number of Conductors	310.120(C)
310.8(D)	Optional Markings	310.120(D)
Part III	Installation	Part II
310.10	Uses Permitted	310.10
310.10(A)	Dry Locations	310.10(A)
310.10(B)	Dry and Damp Locations	310.10(B)
310.10(C)	Wet Locations	310.10(C)
310.10(D)	Locations Exposed to Direct Sunlight	310.10(D)
310.10(E)	Shielding	310.10(E)
310.10(E)	Direct-Burial Conductors	310.10(F)



Article 310 Conductors for General Wiring Comparison Chart (2017 NEC to 2020 NEC)

2020 NEC	Topic	2017 NEC
310.10(F)	Corrosive Conditions	310.10(G)
310.10(G)	Conductors in Parallel	310.10(H)
310.10(G)(1)	General	310.10(H)(1)
310.10(G)(2)	Conductor and Installation Characteristics	310.10(H)(2)
310.10(G)(3)	Separate Cables or Raceways	310.10(H)(3)
310.10(G)(4)	Ampacity Adjustment	310.10(H)(4)
310.10(G)(5)	Equipment Grounding Conductors	310.10(H)(5)
310.10(G)(6)	Bonding Jumpers	310.10(H)(6)
310.12	Single-Phase Dwelling Services and Feeders	310.15(B)(7)
310.12(A)	Services	310.15(B)(7)(1)
310.12(B)	Feeders	310.15(B)(7)(2)
310.12(C)	Feeder Ampacities	310.15(B)(7)(3)
310.12(D)	Grounded Conductors	310.15(B)(7)(4)
Table 310.12	Single-Phase Dwelling Services and Feeders	Table 310.15(B)(7) [2011 NEC]
310.14	Ampacities for Conductors Rated 0-2000 Volts	310.15
310.14(A)	General	310.15(A)



Article 310 Conductors for General Wiring Comparison Chart (2017 NEC to 2020 NEC)

2020 NEC	Topic	2017 NEC
310.14(A)(1)	Tables or Engineering Supervision	310.15(A)(1)
310.14(A)(2)	Selection of Ampacity	310.15(A)(2)
310.14(A)(3)	Temperature Limitation of Conductors	310.15(A)(3)
310.14(B)	Engineering Supervision	NEW
310.15	Ampacity Tables	310.15(B)
310.15(A)	General	310.15(B)(1)
310.15(B)	Ambient Temperature Correction Factors	310.15(B)(2)
310.15(B)(1)	General	310.15(B)(2)
310.15(B)(2)	Rooftop	310.15(B)(3)(c)
Table 310.15(B)(1)	Ambient Temperature Correction Factors Based on 30°C (86°F)	Table 310.15(B)(2)(a)
Table 310.15(B)(2)	Ambient Temperature Correction Factors Based on 40°C (104°F)	Table 310.15(B)(2)(b)
310.15(C)	Adjustment Factors	310.15(B)(3)
310.15(C)(1)	More than Three Current-Carrying Conductors	310.15(B)(3)(a)
Table 310.15(C)(1)	Adjustment Factors for More Than Three Current-Carrying Conductors	Table 310.15(B)(3)(a)



Article 310 Conductors for General Wiring Comparison Chart (2017 NEC to 2020 NEC)

2020 NEC	Topic	2017 NEC
310.15(C)(2)	Raceway Spacing	310.15(B)(3)(b)
310.15(D)	Bare or Covered Conductors	310.15(B)(4)
310.15(E)	Neutral Conductor	310.15(B)(5)
310.15(F)	Grounding or Bonding Conductor	310.15(B)(6)
310.16	Ampacities of Insulated Conductors in Raceway, Cable, or Earth (Directly Buried) (86°F)	NEW
310.17	Ampacities of Single-Insulated Conductors in Free Air (86°F)	NEW
310.18	Ampacities of Insulated Conductors in Raceway or Cable (104°F)	NEW
310.19	Ampacities of Single-Insulated Conductors in Free Air (104°F)	NEW
310.20	Ampacities of Conductors Supported on a Messenger (104°F)	NEW
310.21	Ampacities of Bare or Covered Conductors in Free Air (104°F)	NEW
Table 310.16	Ampacities of Insulated Conductors Not More Than Three Current-Carrying Conductors in Raceway, Cable, or Earth (Directly Buried) (86°F)	Table 310.15(B)(16)
Table 310.17	Ampacities of Single-Insulated Conductors in Free Air (86°F)	Table 310.15(B)(17)
Table 310.18	Ampacities of Insulated Conductors Not More Than Three Current-Carrying Conductors in Raceway or Cable (104°F)	Table 310.15(B)(18)



Article 310 Conductors for General Wiring Comparison Chart (2017 NEC to 2020 NEC)

2020 NEC	Topic	2017 NEC
Table 310.19	Ampacities of Single-Insulated Conductors in Free Air (104°F)	Table 310.15(B)(19)
Table 310.20	Ampacities of Conductors Supported on a Messenger (104°F)	Table 310.15(B)(20)
Table 310.21	Ampacities of Bare or Covered Conductors in Free Air (104°F)	Table 310.15(B)(21)
310.60	Conductors Rated 2001 to 35,000 Volts	Moved to new Article 311