

Pen Type PH Meter



Features

1. Can be used in Test Tube
2. Automatically correction, Automatically power-off, Low power alarm, electrode no effective alert.
3. IP 57 dust and water proof.
4. Electrode is replaceable when it is no effective.
5. Equipped with ph buffer, Electrode soaking solution and 2 spare Lithium Batteries.

Technical Parameters

Model		P301	P302
PH	Measurement Range Resolution Accuracy Temp. Compensation Calibration	-1.00 ~ 15.00 pH 0.01pH ±0.2pH 0 ~ 60°C 1-3 Points (pH4.00/7.00/9.18)	-1.00 ~ 15.00 pH 0.01pH ±0.05pH 0 ~ 60°C 1-3 Points (pH4.00/7.00/9.18)
Other Parameter	Power Diemsnion(Max)/Weight IP Grade	CR2032 Lithium Battery × 2, which can service over 100 hours non-stop. Net: 148×29×14mm / 43g Package: 168×96×28mm / 180g IP57	
Standard Accessory		1. P301 Instrument 1 Unit 2. Electrode soaking solution(10ml) 1 bottle 3. PH Buffer(pH4.00, pH7.00, pH9.181/10ml) 1 bottle each 4. CR2032 Battery x2 Spare Units 5. One Package Box 6. Operation x 1	1. P302Instrument 1 Unit 2. Electrode soaking solution(10ml) 1 bottle 3. PH Buffer(pH4.00, pH7.00, pH9.181/10ml) 1 bottle each 4. CR2032 Battery x2 Spare Units 5. One Package Box 6. Operation x 1